



Part Number: 8471

Electronic, 2 C #16 Str TC, PVC Ins, PVC Jkt, CMG

[Request Sample](#)

Product Description

Electronic, 2 Conductor 16AWG (19x29) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

Technical Specifications

MetricTDS:	8471
------------	------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
16	19x29	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1
Conductor Size:	16 AWG

Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.023 in

Color Chart

Number	Color
1	Black & White

Outer Shield Material

Material
Unshielded

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.274 in	0.032 in

Construction and Dimensions

Cabling

Lay Direction	Twists
Left Hand	6 twist/ft

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
4.49 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor
33 pF/ft

Inductance

Nominal Inductance

0.19 µH/ft

Current

Element	Max. Recommended Current [A]
10C temperature rise	6.1 Amps per conductor @ 25°C ambient

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	36 lbs/1000ft
Max Recommended Pulling Tension:	61 lbs
Min Bend Radius/Minor Axis:	2.75 in

Standards

NEC Articles:	800, 725
NEC/(UL) Specification:	CL3, CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2598 (300 V 60°C)
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
8471.00305	Chrome	
8471.00U152	Chrome	
8471.00U305	Chrome	
8471.01152	Chrome	
8471 0601000	Chrome	C

8471 060500	Chrome	C
8471 0605000	Chrome	
8471 060U1000	Chrome	
8471 060U500	Chrome	

Footnote: C - CRATE REEL PUT-UP.

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.