

## Ankerskinne AML3518, slisset 16,5 mm




Type	Mål B x H mm	Material- tykkelse mm	Lengde mm	bunt m	Vekt kg/100 stk.	Art.-nr.	Art.-nr. El-Nr.
AML3518P0200FT	35 x 18	1,5	200	25	17,800	1119696	
AML3518P0300FT	35 x 18	1,5	300	25	26,700	1119693	
AML3518P0400FT	35 x 18	1,5	400	10	35,600	1119690	
AML3518P0500FT	35 x 18	1,5	500	10	44,500	1119687	1301768
AML3518P0600FT	35 x 18	1,5	600	10	53,400	1119684	
AML3518P0700FT	35 x 18	1,5	700	10	62,300	1119681	
AML3518P0800FT	35 x 18	1,5	800	10	71,200	1119678	

St stål

€/100 stk.

FT varmgalvanisert (dypp)

Profilskinne med 16,5 mm slissevidde.



## Ankerskinne AMS3518, slisset 16,5 mm



Type	Mål B x H mm	Material- tykkelse mm	Lengde mm	bunt m	Vekt kg/100 m	Art.-nr.
AMS3518P1000FS	35 x 18	2	1000	—	115,000	1112735
AMS3518P2000FS	35 x 18	2	2000	20	115,000	1112708
AMS3518P1000FT	35 x 18	2	1000	—	122,000	1112755
AMS3518P2000FT	35 x 18	2	2000	20	122,000	1112759
AMS3518P1000A2	35 x 18	2	1000	—	107,000	1118421
AMS3518P2000A2	35 x 18	2	2000	20	107,000	1112709

St stål V2A spesialstål, rustfritt 1.4301 V2A Rustfritt stål A2

€/100 m

FS kontinuerlig galvanisert FT varmgalvanisert (dypp)

Profilskinne, perforert, med 16,5 mm slissevidde.

Statistiske verdier:

A = 1,31 cm<sup>2</sup>I<sub>y</sub> = 0,5377 cm<sup>4</sup>I<sub>z</sub> = 2,3149 cm<sup>4</sup>W<sub>y</sub> = 0,516 cm<sup>3</sup>W<sub>z</sub> = 1,322 cm<sup>3</sup>