

### Quick clip, light grey



OBO Quick clip, type 2955/...: for all metric steel armoured pipes, as well as light-duty and heavy-duty metric insulation pipes. Suitable for mounting the OBO Quick pipe. Pipe centring aids allow optimal attachment of the pipe and automatically turn the clip into the correct position.

Universal fastening option; can be arranged with the OBO Multi-quick and starQuick clip. Slot for side alignment during mounting with wood screw or knock-in anchor.


Size M16-M32 can be screwed onto an M6 thread.

Recommended fastening spacing 50–60 cm, for max. extraction values F at a room temperature of 20 °C, see the table.

| Type     | Nominal size | Colour     | Pack. pcs | Weight kg/100 pcs. | Item No. |
|----------|--------------|------------|-----------|--------------------|----------|
| 2955 M16 | M16          | Light grey | 100       | 0,252              | 2149004  |
| 2955 M20 | M20          | Light grey | 100       | 0,325              | 2149010  |
| 2955 M25 | M25          | Light grey | 100       | 0,433              | 2149016  |
| 2955 M32 | M32          | Light grey | 50        | 0,630              | 2149022  |
| 2955 M40 | M40          | Light grey | 50        | 0,835              | 2149028  |
| 2955 M50 | M50          | Light grey | 25        | 1,454              | 2149034  |
| 2955 M63 | M63          | Light grey | 20        | 2,203              | 2149040  |

PP Polypropylene

#### Dimensions



| Type     | Nominal size | Dimension A mm | Dimension B mm | Dimension C mm | Dimension D mm | Dimension E mm | Dimension F mm | Dimension H mm | Dimension h mm | Pull out value N |
|----------|--------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|
| 2955 M16 | M16          | 25,3           | 16             | 12             | 15,5           | 7              | 4,2            | 25             | 10             | 75               |
| 2955 M20 | M20          | 30,3           | 16             | 14             | 19,4           | 9              | 4,2            | 29,5           | 10             | 90               |
| 2955 M25 | M25          | 36,3           | 16             | 18             | 24,3           | 12             | 4,2            | 34             | 10             | 100              |
| 2955 M32 | M32          | 46,3           | 16             | 22             | 31,4           | 12             | 4,2            | 42             | 11             | 120              |
| 2955 M40 | M40          | 57,3           | 16             | 26             | 39,2           | 11             | 4,6            | 51             | 12             | 140              |
| 2955 M50 | M50          | 70,3           | 18             | 32             | 49             | 12             | 6              | 63             | 14             | 165              |
| 2955 M63 | M63          | 87,3           | 20             | 43             | 61,5           | 12             | 6              | 74,5           | 15             | 230              |