



Terminal block 1 pole, 250A, 11 output terminals, ALU

Part no. BPZ-KB-11/250-ALU
Article no. 102705

Delivery program

Mounting type			Floor standing distribution board Surface mounted Flush mounted
Material			Aluminium
Degree of Protection			IP20
Mounting position			universal
Number of poles			1 pole
Width		mm	44
Depth		mm	49
Height		mm	95
Number of clamping units per pole			12
Rated device current		A	250

Technical data

General

Standards			IEC 60 947 -7 -1
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			conform
Heat deflection temperature		?C	100
UL 94 flame classification			V-0
Comparative tracking index		V	600
Degree of Protection			IP20
Assembly details			Clicks on DIN-rail or on base plate. Save time on wiring. Save 80% on space used. Modular construction, 1-4 pole Systems can be built with several blocks.
Important			This Power Distribution Block is suitable for ALU and CU conductors. Please pay attention to the common handling guidelines when connecting the Aluminium conductors. Clean and brush the contact surfaces and lubricate them with an appropriate grease. As precaution the connections should get retightened regularly.

Electrical

IEC			
Max. electrical load / Cu		A	200
Max. operating voltage / Cu		V AC	1000
Max. operating voltage / Cu		V DC	1500
Rated peak withstand current	I_{pk}	kA	51
Rated short-time withstand current (t=1s)	I_{cw}	kA	21

Material characteristics

Material			
Clamping body			Brass
Housing			PA66
Hexagon socket set screw			Steel
Surface finish			
Clamping body			Nickel plated
Hexagon socket set screw			Zn-Plated
Colour			
Housing			grey, RAL 7035

Terminal capacity

Incomer			
single wire/multi wire		mm ²	35 - 120
single wire/multi wire		AWG	2 - 4/0
fine wire (with sleeve)		mm ²	35 - 95

fine wire (with sleeve)	AWG	2 - 3/0
Torque	N/m	19 - 21
Torque	lbf	168.1 - 185.8
Outgoings		
single wire/multi wire	mm ²	2.5 - 35 2.5 - 16 2.5 - 10
single wire/multi wire	AWG	14 - 2 14 - 6 14 - 8
fine wire (with sleeve)	mm ²	2.5 - 25 2.5 - 16 2.5 - 10
fine wire (with sleeve)	AWG	14 - 4 14 - 6 14 - 8
Torque	N/m	3.5 - 7 2 - 3 2 - 3
Torque	lbf	31 - 62 17.7 - 26.5 17.7 - 26.5

Technical data ETIM 6.0

Energy distribution systems (EG000015) / Distributor assembly terminal blocks (EC001894)

Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly terminal blocks
(ecl@ss8.1-27-40-06-09 [ACO381008])

Height	mm	95.4
Width	mm	44.5
Depth	mm	49
Max. rated current	A	250
Number of poles		1
Conductor cross section flexible (fine-strand) with cable end sleeve	mm ²	2.5 - 120
Conductor cross section solid (solid, stranded)	mm ²	2.5 - 120
Number of clamp positions per pole		12
With PE-rail		No
With N-rail		No

Dimensions

