

Product Description

Glas fibre reinforced for maximum mechanical stability; Bearing surface avoids scratchings on the housing while mounting with an wrench



Application range

- For locking of SKINTOP® cable glands in boreholes without thread.

Benefits

- Glas fibre reinforced for maximum mechanical stability
- Bearing surface avoids scratchings on the housing while mounting with an wrench

Design

- PG connection thread

Note

- UL approval only when used with the UL approved SKINTOP® polyamide cable glands
- Designed for use in connection with SKINTOP® ST(R)



Technical Data

On request

Available without collar (without surface for assembling tool)

Colour delivered

RAL 7001 silver-grey RAL 7035 light grey RAL 9005 black / UV resistant

Material

Polyamide, glass fibre reinforced

Range of temperature

-20°C up to +100°C

Article List

Part number	Part designation / size	SW mm	Pieces / PU
SKINTOP® GMP-GL silver grey with collar			
53019000	GMP-GL 7	19	100
53019010	GMP-GL 9	22	100
53019020	GMP-GL 11	24	100
53019030	GMP-GL 13,5	27	100
53019040	GMP-GL 16	30	100
53019050	GMP-GL 21	36	50
53019060	GMP-GL 29	46	50
53019070	GMP-GL 36	60	25
53019080	GMP-GL 42	65	25
53019090	GMP-GL 48	70	25
SKINTOP® GMP-GL black with collar			
53019200	GMP-GL 7	19	100
53019210	GMP-GL 9	22	100
53019220	GMP-GL 11	24	100
53019230	GMP-GL 13,5	27	100
53019240	GMP-GL 16	30	100
53019250	GMP-GL 21	36	50
53019260	GMP-GL 29	46	50
53019270	GMP-GL 36	60	25
53019280	GMP-GL 42	65	25
53019290	GMP-GL 48	70	25
SKINTOP® GMP-GL light grey with collar			
53019001	GMP-GL 7	19	100
53019011	GMP-GL 9	22	100



53019021	GMP-GL 11	24	100
53019031	GMP-GL 13,5	27	100
53019041	GMP-GL 16	30	100
53019051	GMP-GL 21	36	50
53019061	GMP-GL 29	46	50
53019071	GMP-GL 36	60	25
53019081	GMP-GL 42	65	25
53019091	GMP-GL 48	70	25

Footnote:

Photographs are not to scale and do not represent detailed images of the respective products.