



Insulated enclosure, HxWxD=375x250x225mm, for size 1

Part no. NZM1-XCI43/2-TVDVR
Article no. 104646

Similar to illustration

Delivery program

Product range			Accessories
Accessories			Insulated enclosures
Description			With door coupling rotary handle Complete with all required functional parts
Function			Red-yellow for emergency switching off
Locking facility			Lockable in the 0 position using up to 3 padlocks on the handle and/or switch each. Additionally with cover interlock.
Accessories			Accessories, others
Number of poles			3/4 pole
Standard/Approval			IEC
Construction size			NZM1
Degree of Protection			IP64
Rated uninterrupted current I_u at max. cross-section	I_u	A	160 A
Basic enclosure			CI43-200
Terminal for retrofitting of 5th conductor (neutral conductor)			K10/1, K25/1, K50/1, K95/1N/BR
For use with			NZM1(-4), PN1(-4), N(S)1(-4)
Notes			
Suitable for installation of circuit-breakers and switch-disconnectors Enclosure for separate mounting with top and bottom cable entry.			
Include fixing straps for wall mounting.			
Cannot be used in combination with NZM...-XR... remote operator...			
NZM...-XSV plug-in unit or NZM...-XAV withdrawable unit.			
Insulated additional terminal for 4th or 5th pole should be ordered separately.			
CI-K5 enclosure with hard metric knock-outs			
CI23 enclosure with flanges			
CI43, CI45 and CI48 feature gland plates.			
Only for switches with box terminal for direct connection of cables.			

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ec1@ss8.1-27-37-13-01 [AKN343011])			
Material housing			Plastic
Width		mm	250
Height		mm	375
Depth		mm	225
With transparent cover			Yes
Suitable for emergency stop			Yes
Model			Surface mounting
Degree of protection (IP)			IP65

Dimensions

