



016838

TM-2-8177/EZ

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per IEC/EN 61439](#)

[Technical data ETIM7.0](#)

[Approvals](#)

[Dimensions](#)

## DELIVERY PROGRAM

Product range  
Control switches

Part group reference  
TM


Basic function  
Spring-return switch

with black thumb grip and front plate


Contacts  
4

Degree of Protection  
Front IP65

Design  
centre mounting



#### Contact sequence



Switching angle  
60°

Switching performance  
momentary/maintained  
With 0 (Off) position  
with spring-return from both directions

Design number  
8177

Front plate no.



F 121

front plate  
START>1-0-2<START

#### Motor rating AC-23A, 50 - 60 Hz [P]

400 V [P]  
3 kW

Rated uninterrupted current [ $I_u$ ]  
10 A

Note on rated uninterrupted current  $I_u$   
Rated uninterrupted current  $I_u$  is specified for max.  
cross-section.

Number of contact units  
2 contact unit(s)

## TECHNICAL DATA

### General

#### Standards

IEC/EN 60947, VDE 0660, CSA, UL

Control switch as per IEC/EN 60947-5-1

Auxiliary switch as per IEC/EN 60947-5-1

#### Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

#### Ambient temperature

Open

-25 - +50 °C

#### Overvoltage category/pollution degree

III/3

#### Rated impulse withstand voltage [ $U_{imp}$ ]

4000 V AC

#### Mounting position

As required

### Contacts

#### Electrical characteristics

Rated operational voltage [ $U_e$ ]

500 V AC

#### Electrical characteristics

Rated uninterrupted current [ $I_u$ ]

10 A

#### Electrical characteristics

Note on rated uninterrupted current  $I_u$

Rated uninterrupted current  $I_u$  is specified for max. cross-section.

#### Short-circuit rating

Fuse  
10 A gG/gL

## Switching capacity

Safe isolation to EN61140  
Current heat loss per contact at  $I_e$   
0.15 W

Safe isolation to EN61140  
Current heat loss per auxiliary circuit at  $I_e$  (AC-  
15/230 V)  
0.15 CO

Lifespan, mechanical [Operations]  
> 1 x 10<sup>6</sup>

Maximum operating frequency [Operations/h]  
1200

AC  
AC-23A  
Motor rating AC-23A, 50 - 60 Hz [P]  
400 V 415 V [P]  
3 kW

Control circuit reliability at 24 V DC, 10 mA [Fault  
probability]  
< 10<sup>-5</sup>, < 1 failure in 100,000 switching operations  
H<sub>F</sub>

## Terminal capacities

Solid or stranded  
1 x 1,5  
2 x 1,5 mm<sup>2</sup>

Flexible with ferrules to DIN 46228  
1 x 1.0  
2 x 1.0 mm<sup>2</sup>

Flexible  
1 x 1.5  
2 x 1.5 mm<sup>2</sup>

Terminal screw  
M2.5

Tightening torque for terminal screw  
0.4 Nm

### Rating data for approved types

Contacts  
Rated operational voltage [ $U_e$ ]  
300 V AC

Contacts  
Rated uninterrupted current max.  
Main conducting paths  
General use  
10 A

Contacts  
Rated uninterrupted current max.  
Auxiliary contacts  
General Use [ $I_u$ ]  
10 A

Contacts  
Rated uninterrupted current max.  
Auxiliary contacts  
Plot Duty  
A 300

Switching capacity  
Maximum motor rating  
Single-phase  
120 V AC  
0.33 HP

Switching capacity  
Maximum motor rating  
Single-phase  
240 V AC  
0.75 HP

Switching capacity  
Maximum motor rating  
Single-phase  
277 V AC  
0.75 HP

Switching capacity  
Maximum motor rating  
Three-phase  
120 V AC

0.75 HP

Switching capacity  
Maximum motor rating  
Three-phase  
240 V AC  
1 HP

Terminal capacity  
Solid or flexible conductor with ferrule  
14 AWG

Terminal capacity  
Terminal screw  
M2.5

Terminal capacity  
Tightening torque  
3.5 lb-in

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_n$ ]  
10 A

Heat dissipation per pole, current-dependent [ $P_{id}$ ]  
0.15 W

Equipment heat dissipation, current-dependent  
[ $P_{id}$ ]  
0 W

Static heat dissipation, non-current-dependent [ $P_{is}$ ]  
0 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+50 °C

## IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
UV resistance only in connection with protective shield.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the



information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Control switch (EC002611)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Control switch (ec@ss10.0.1-27-37-14-14 [ACN998011])

Type of switch  
On/Off switch

Number of poles  
4

Max. rated operation voltage  $U_e$  AC  
500 V

Rated permanent current  $I_u$   
10 A

Number of switch positions  
5

With 0 (off) position  
Yes

With retraction in 0-position  
No

Device construction  
Built-in device

Width in number of modular spacings  
0

Suitable for ground mounting  
No

Suitable for front mounting 4-hole

Yes

Suitable for distribution board installation  
No

Suitable for intermediate mounting  
No

Complete device in housing  
No

Type of control element  
Toggle

Front shield size  
48x48 mm

Degree of protection (IP), front side  
IP65

Degree of protection (NEMA), front side  
Other

## APPROVALS

Product Standards  
UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94;  
IEC/EN 60947-3; CE marking

UL File No.  
E36332

UL Category Control No.  
NLRV

CSA File No.  
UL report applies to both US and Canada

North America Certification  
UL listed, certified by UL for use in Canada

Degree of Protection  
IEC: IP65; UL/CSA Type: –

## DIMENSIONS



Key operation lock mechanism

Door drilling dimensions

Drilling dimensions: either 16.2 mm = without  
reduction  RMQ16 or 22.3 mm = with reduction   
RMQ Titan



