

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



ZFS60-P3 - Clamp with label, For use with T5, T5B, P3, 88 x 27 mm, Blank, can be engraved, Language None



022297 ZFS60-P3

[Overview](#) [Specifications](#) [Resources](#)



## 022297 ZFS60-P3

Clamp with label, For use with T5, T5B, P3, 88 x 27 mm, Blank, can be engraved, Language None  
EL-Nummer (Norway) 1456507

Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure, flush mounting, centre mounting, rear mounting I/S service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities.

- Delivery program
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Approvals

### Delivery program

Basic function  
Front plates  
Function  
add-on front plates  
For mechanisms with padlocking feature  
Consists of label mount and insert label  
Plug-in type  
For use with  
T5, T5B, P3  
Dimensions (W x H)  
88 x 27 mm  
Name  
Blank, can be engraved  
Language  
None

### Design verification as per IEC/EN 61439

Technical data for design verification  
Rated operational current for specified heat dissipation [ $I_t$ ]  
0 A  
Heat dissipation per pole, current-dependent [ $P_{vid}$ ]  
0 W  
Equipment heat dissipation, current-dependent [ $P_{vid}$ ]  
0 W  
Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
0 W  
Heat dissipation capacity [ $P_{diss}$ ]  
0 W  
Operating ambient temperature min.  
-25 °C  
Operating ambient temperature max.

+50 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

Type of accessory

Other

## Approvals

North America Certification

UL/CSA certification not required

## 3D drawing



1151009

Line drawing

Add-on front plate, blank

# Product photo



115A023

Photo

Add-on front plate/external warning plate

# Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH