

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



DE-T0 - Coupling drive



093487 DE-T0

[Overview](#) [Specifications](#) [Resources](#)



# 093487 DE-T0

Coupling drive

EL-Nummer (Norway)

1456545

Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure , flush mounting, centre mounting, rear mounting I/S service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities.



Delivery program

- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Approvals

Basic function  
 Assembly kits  
 Function  
 coupling drive  
 for the conversion of switch to rear mounting switch  
 For use with  
 T0.../XZ  
 T3.../XZ  
 Information about equipment supplied  
 with axle shaft  
**Notes**  
 Spare part for T0.../Z, T3.../Z, P1.../Z

## Design verification as per IEC/EN 61439

Technical data for design verification  
 Rated operational current for specified heat dissipation [ $I_h$ ]  
 0 A  
 Heat dissipation per pole, current-dependent [ $P_{vid}$ ]  
 0 W  
 Equipment heat dissipation, current-dependent [ $P_{vid}$ ]  
 0 W  
 Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
 0 W  
 Heat dissipation capacity [ $P_{diss}$ ]  
 0 W  
 Operating ambient temperature min.  
 -25 °C  
 Operating ambient temperature max.  
 +50 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Door coupling handle for switchgear (EG000230)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Hand drive for switch devices (ecl@ss10.0.1-27-37-04-15 [AKF013014])

With axis extension

No

With door interlock

No

Lockable

No

With handle red/yellow

No

## Approvals





North America Certification

UL/CSA certification not required

## 3D drawing

- [115I029](#)  
Line drawing  
Coupling drive

## Product photo

-   
[115A038](#)  
Photo  
Coupling drive
-   
[y7-93487\\_bk](#)  
Photo
- [y7-93487\\_bk1](#)  
Photo
-   
[y7-93487\\_c](#)  
Photo
- [y7-93487\\_c1](#)  
Photo
-   
[y7-93487\\_l](#)  
Photo
-

y7-93487\_pkg  
Photo



y7-93487\_pkgo  
Photo



y7-93487\_r  
Photo

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH