Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norw egian Bokmål

Worldwide English



FS-ALU980-P3 - Front plate, For use with T5B, T5, P3, 84 x 84 (for frame 88 x 88) mm, Blank, can be engraved



266906 FS-ALU980-P3 Overview Specifications Resources ♪ ♪ ↓



266906 FS-ALU980-P3

Front plate, For use with T5B, T5, P3, 84 x 84 (for frame 88 x 88) mm, Blank, can be engraved EL-Nummer (Norway) 1456582 Front plate, Blank plate, Dimensions (W x H): 84 x 84 (for frame 88 x 88) mm, Name: Blank, can be engraved, For use with: T5B, T5, P3

• Delivery program

 Design verification as per IEC/EN 61439

- Technical data ETIM 7.0
- Approvals

Delivery program

Basic function Front plates Function Blank plate For use with T5B, T5, P3 Dimensions (W x H) 84 x 84 (for frame 88 x 88) mm Name Blank, can be engraved

Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [I_n] 0 A Heat dissipation per pole, current-dependent [P_{id}] 0 W Equipment heat dissipation, current-dependent [P_{id}] 0 W Static heat dissipation, non-current-dependent [P_{vs}] 0 W Heat dissipation capacity [P_{diss}] 0 W Operating ambient temperature min.

-25 °C Operating ambient temperature max. +50 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2 Strength of materials and parts 10.2.6 Mechanical impact Does not apply, since the entire switchgear needs to be evaluated. 10.2 Strength of materials and parts10.2.7 Inscriptions Meets the product standard's requirements. 10.3 Degree of protection of ASSEVBLIES Does not apply, since the entire switchgear needs to be evaluated. 10.4 Clearances and creepage distances Meets the product standard's requirements. 10.5 Protection against electric shock Does not apply, since the entire switchgear needs to be evaluated. 10.6 Incorporation of switching devices and components Does not apply, since the entire switchgear needs to be evaluated. 10.7 Internal electrical circuits and connections Is the panel builder's responsibility. 10.8 Connections for external conductors Is the panel builder's responsibility. 10.9 Insulation properties 10.9.2 Pow er-frequency electric strength Is the panel builder's responsibility. 10.9 Insulation properties 10.9.3 Impulse withstand voltage Is the panel builder's responsibility. 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material Is the panel builder's responsibility. 10.10 Temperature rise Not applicable. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498) Bectric engineering, automation, process control engineering / Low-voltage switch technology / Component for lowvoltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013]) Type of accessory Other

Approvals

North America Certification UL/CSA certification not required

Product photo



1150PIC-1136 Photo Blank front plate

3D drawing



Download-Center

- Download-Center (this item)
 Eaton EVEA Download-Center download data for this item
 Download Center
- Dow nload-Center
 Eaton EVEA Dow nload-Center

ß

Generate data sheet in PDF format

x

Generate data sheet in Excel format

Write a comment Imprint Privacy Policy Legal Disclaimer Terms and Conditions © 2021 by Eaton Industries GmbH