



214781
T6-3-8212/E/HI12

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Dimensions

DELIVERY PROGRAM

Product range
Control switches

Part group reference
T6


Basic function
Changeover switches

with black thumb grip and front plate

Contacts
9

Degree of Protection
Front IP65

Design
flush mounting



Contact sequence




Switching angle
60 °

Switching performance
maintained
With 0 (Off) position

Design number
8212

Front plate no.



FS 684

front plate
1-0-2

Motor rating AC-23A, 50 - 60 Hz [P]

400 V [P]
75 kW

Rated uninterrupted current [I_u]
150 A

Note on rated uninterrupted current I_u
Rated uninterrupted current I_u is specified for max.
cross-section.

Number of contact units
3 contact unit(s)

TECHNICAL DATA

General

Standards

IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature

Open

-25 - +50 °C

Ambient temperature

Enclosed

-25 - +40 °C

Overvoltage category/pollution degree

III/3

Rated impulse withstand voltage [U_{imp}]

6000 V AC

Mounting position

As required

Contacts

Electrical characteristics

Rated operational voltage [U_e]

690 V AC

Electrical characteristics

Rated uninterrupted current [I_u]

150 A

Electrical characteristics

Note on rated uninterrupted current I_u

Rated uninterrupted current I_u is specified for max. cross-section.

Load rating with intermittent operation, class 12

AB 25 % DF
 $2 \times I_e$

Load rating with intermittent operation, class 12
AB 40 % DF
 $1.6 \times I_e$

Load rating with intermittent operation, class 12
AB 60 % DF
 $1.3 \times I_e$

Short-circuit rating
Fuse
200 A gG/gL

Rated short-time withstand current (1 s current)
[I_{cw}]
 $2000 A_{rms}$

Note on rated short-time withstand current I_{cw}
Current for a time of 1 second

Rated conditional short-circuit current [I_q]
5 kA

Switching capacity

$\cos \phi$ rated making capacity as per IEC 60947-3
1600 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3
230 V
1280 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3
400/415 V
900 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3
500 V
880 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3
690 V
340 A

Safe isolation to EN61140
between the contacts
440 V AC

Safe isolation to EN61140
Current heat loss per contact at I_e
11 W

Safe isolation to EN61140
Current heat loss per auxiliary circuit at I_e (AC-
15/230 V)
0.2 W

Lifespan, mechanical [Operations]
> 0.1×10^6

Maximum operating frequency [Operations/h]
50

AC
AC-3
Rating, motor load switch [P]
220 V 230 V [P]
22 kW

AC
AC-3
Rating, motor load switch [P]
230 V Star-delta [P]
22 kW

AC
AC-3
Rating, motor load switch [P]
400 V 415 V [P]
37 kW

AC
AC-3
Rating, motor load switch [P]
400 V Star-delta [P]
37 kW

AC
AC-3
Rating, motor load switch [P]
500 V [P]
37 kW

AC

AC-3
Rating, motor load switch [P]
500 V Star-delta [P]
37 kW

AC
AC-3
Rating, motor load switch [P]
690 V [P]
30 kW

AC
AC-3
Rating, motor load switch [P]
690 V Star-delta [P]
30 kW

AC
AC-3
Rated operational current motor load switch
230 V [I_e]
75 A

AC
AC-3
Rated operational current motor load switch
230 V star-delta [I_e]
75 A

AC
AC-3
Rated operational current motor load switch
400V 415 V [I_e]
72.5 A

AC
AC-3
Rated operational current motor load switch
400 V star-delta [I_e]
72.5 A

AC
AC-3
Rated operational current motor load switch
500 V [I_e]
53 A

AC
AC-3
Rated operational current motor load switch
500 V star-delta [I_e]
53 A

AC
AC-3
Rated operational current motor load switch
690 V [I_e]
34 A

AC
AC-3
Rated operational current motor load switch
690 V star-delta [I_e]
34 A

AC
AC-23A
Motor rating AC-23A, 50 - 60 Hz [P]
230 V [P]
37 kW

AC
AC-23A
Motor rating AC-23A, 50 - 60 Hz [P]
400 V 415 V [P]
75 kW

AC
AC-23A
Motor rating AC-23A, 50 - 60 Hz [P]
500 V [P]
90 kW

AC
AC-23A
Motor rating AC-23A, 50 - 60 Hz [P]
690 V [P]
55 kW

AC
AC-23A
Rated operational current motor load switch
230 V [I_e]
126 A

AC
AC-23A
Rated operational current motor load switch
400 V 415 V [I_e]
138 A

AC
AC-23A
Rated operational current motor load switch
500 V [I_e]

128 A

AC
AC-23A
Rated operational current motor load switch
690 V [I_e]
60 A

DC
DC-1, Load-break switches L/R = 1 ms
Rated operational current [I_e]
125 A

DC
DC-1, Load-break switches L/R = 1 ms
Voltage per contact pair in series
42 V

DC
DC-23A, motor load switch L/R = 15 ms
24 V
Rated operational current [I_e]
125 A

DC
DC-23A, motor load switch L/R = 15 ms
24 V
Contacts
1 Quantity

DC
DC-23A, motor load switch L/R = 15 ms
48 V
Rated operational current [I_e]
125 A

DC
DC-23A, motor load switch L/R = 15 ms
48 V
Contacts
2 Quantity

DC
DC-23A, motor load switch L/R = 15 ms
60 V
Rated operational current [I_e]
125 A

DC
DC-23A, motor load switch L/R = 15 ms
60 V
Contacts

3 Quantity

DC
DC-23A, motor load switch L/R = 15 ms
120 V
Rated operational current [I_e]
50 A

DC
DC-23A, motor load switch L/R = 15 ms
120 V
Contacts
3 Quantity

DC
DC-13, Control switches L/R = 50 ms
Rated operational current [I_e]
125 A

DC
DC-13, Control switches L/R = 50 ms
Voltage per contact pair in series
24 V

Control circuit reliability at 24 V DC, 10 mA [Fault probability]
< 10^{-5} , < 1 failure in 100,000 switching operations
H₁

Terminal capacities

Solid or stranded
1 x 70
2 x 25 mm²

Flexible with ferrules to DIN 46228
1 x 50
2 x 16 mm²

Terminal screw
M6

Tightening torque for terminal screw
4.5 Nm

Technical safety parameters:

Notes

B10_d values as per EN ISO 13849-1, table C1

Rating data for approved types

Terminal capacity
Terminal screw
M6

Terminal capacity
Tightening torque
40 lb-in

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]
160 A

Heat dissipation per pole, current-dependent [P_{vid}]
11 W

Equipment heat dissipation, current-dependent
[P_{vid}]
0 W

Static heat dissipation, non-current-dependent [P_{vs}]
0 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+50 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
UV resistance only in connection with protective shield.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs

to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Off-load switch (E0001105)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Changeover switch (ecl@ss10.0.1-27-37-14-05 [AKF062013])

Model
Reverser

Number of poles
3

With 0 (off) position
Yes

With retraction in 0-position
No

Rated permanent current I_u
125 A

Rated operation current I_e at AC-3, 400 V
72.5 A

Rated operation power at AC-3, 400 V
37 kW

Degree of protection (IP), front side
IP65

Degree of protection (NEMA), front side
Other

Number of auxiliary contacts as normally closed
contact
0

Number of auxiliary contacts as normally open
contact
0

Number of auxiliary contacts as change-over
contact

0

Suitable for ground mounting
No

Suitable for front mounting 4-hole
Yes

Suitable for distribution board installation
No

Suitable for intermediate mounting
No

Complete device in housing
No

Material housing
Plastic

Type of control element
Toggle

Type of electrical connection of main circuit
Screw connection

DIMENSIONS



