



092378

T5B-3-8222/E

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Dimensions

DELIVERY PROGRAM

Product range
Control switches

Part group reference
T5B


Basic function
Changeover switches

with black thumb grip and front plate


Contacts
6

Degree of Protection
Front IP65

Design
flush mounting



Contact sequence




Switching angle
90°

Switching performance
maintained
Without 0 (Off) position

Design number
8222

Front plate no.



FS 943

front plate
1-2

Motor rating AC-23A, 50 - 60 Hz [P]

400 V [P]
30 kW

Rated uninterrupted current [I_u]
63 A

Note on rated uninterrupted current I_u
Rated uninterrupted current I_u is specified for max.
cross-section.

Number of contact units
3 contact unit(s)

TECHNICAL DATA

General

Standards

IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL
Switch-disconnector according to IEC/EN 60947-3

Climatic proofing

Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature

Open
-25 - +50 °C

Ambient temperature

Enclosed
-25 - +40 °C

Overvoltage category/pollution degree

III/3

Rated impulse withstand voltage [U_{imp}]

6000 V AC

Mechanical shock resistance

15 g

Mounting position

As required

Contacts

Electrical characteristics

Rated operational voltage [U_e]
690 V AC

Electrical characteristics

Rated uninterrupted current [I_u]
63 A

Electrical characteristics

Note on rated uninterrupted current I_u
Rated uninterrupted current I_u is specified for max.

cross-section.

Load rating with intermittent operation, class 12
AB 25 % DF
 $2 \times I_e$

Load rating with intermittent operation, class 12
AB 40 % DF
 $1.6 \times I_e$

Load rating with intermittent operation, class 12
AB 60 % DF
 $1.3 \times I_e$

Short-circuit rating
Fuse
80 A gG/gL

Rated short-time withstand current (1 s current)
 $[I_{cw}]$
 $1300 A_{rms}$

Note on rated short-time withstand current I_{cw}
Current for a time of 1 second

Rated conditional short-circuit current $[I_k]$
2 kA

Switching capacity

$\cos \phi$ rated making capacity as per IEC 60947-3
800 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3
230 V
520 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3
400/415 V
600 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3
500 V
480 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3

690 V
340 A

Safe isolation to EN61140
between the contacts
440 V AC

Safe isolation to EN61140
Current heat loss per contact at I_e
4.5 W

Safe isolation to EN61140
Current heat loss per auxiliary circuit at I_e (AC-
15/230 V)
4.5 W

Lifespan, mechanical [Operations]
> 0.5 x 10⁶

Maximum operating frequency [Operations/h]
1200

AC
AC-3
Rating, motor load switch [P]
220 V 230 V [P]
15 kW

AC
AC-3
Rating, motor load switch [P]
230 V Star-delta [P]
18.5 kW

AC
AC-3
Rating, motor load switch [P]
400 V 415 V [P]
22 kW

AC
AC-3
Rating, motor load switch [P]
400 V Star-delta [P]
30 kW

AC
AC-3
Rating, motor load switch [P]
500 V [P]

22 kW

AC
AC-3
Rating, motor load switch [P]
500 V Star-delta [P]
37 kW

AC
AC-3
Rating, motor load switch [P]
690 V [P]
15 kW

AC
AC-3
Rating, motor load switch [P]
690 V Star-delta [P]
22 kW

AC
AC-3
Rated operational current motor load switch
230 V [I_e]
51 A

AC
AC-3
Rated operational current motor load switch
230 V star-delta [I_e]
63 A

AC
AC-3
Rated operational current motor load switch
400V 415 V [I_e]
41 A

AC
AC-3
Rated operational current motor load switch
400 V star-delta [I_e]
63 A

AC
AC-3
Rated operational current motor load switch
500 V [I_e]
33 A

AC
AC-3

Rated operational current motor load switch
500 V star-delta [I_e]
57.2 A

AC
AC-3
Rated operational current motor load switch
690 V [I_e]
17 A

AC
AC-3
Rated operational current motor load switch
690 V star-delta [I_e]
29.4 A

AC
AC-23A
MOTOR rating AC-23A, 50 - 60 Hz [P]
230 V [P]
18.5 kW

AC
AC-23A
MOTOR rating AC-23A, 50 - 60 Hz [P]
400 V 415 V [P]
30 kW

AC
AC-23A
MOTOR rating AC-23A, 50 - 60 Hz [P]
500 V [P]
22 kW

AC
AC-23A
MOTOR rating AC-23A, 50 - 60 Hz [P]
690 V [P]
22 kW

AC
AC-23A
Rated operational current motor load switch
230 V [I_e]
63 A

AC
AC-23A
Rated operational current motor load switch
400 V 415 V [I_e]
63 A

AC
AC-23A
Rated operational current motor load switch
500 V [I_e]
33 A

AC
AC-23A
Rated operational current motor load switch
690 V [I_e]
23.8 A

DC
DC-1, Load-break switches L/R = 1 ms
Rated operational current [I_e]
63 A

DC
DC-1, Load-break switches L/R = 1 ms
Voltage per contact pair in series
60 V

DC
DC-23A, motor load switch L/R = 15 ms
24 V
Rated operational current [I_e]
50 A

DC
DC-23A, motor load switch L/R = 15 ms
24 V
Contacts
1 Quantity

DC
DC-23A, motor load switch L/R = 15 ms
48 V
Rated operational current [I_e]
50 A

DC
DC-23A, motor load switch L/R = 15 ms
48 V
Contacts
2 Quantity

DC
DC-23A, motor load switch L/R = 15 ms
60 V
Rated operational current [I_e]
50 A

DC
DC-23A, motor load switch L/R = 15 ms
60 V
Contacts
3 Quantity

DC
DC-23A, motor load switch L/R = 15 ms
120 V
Rated operational current [I_e]
25 A

DC
DC-23A, motor load switch L/R = 15 ms
120 V
Contacts
3 Quantity

DC
DC-23A, motor load switch L/R = 15 ms
240 V
Rated operational current [I_e]
20 A

DC
DC-23A, motor load switch L/R = 15 ms
240 V
Contacts
6 Quantity

DC
DC-13, Control switches L/R = 50 ms
Rated operational current [I_e]
25 A

DC
DC-13, Control switches L/R = 50 ms
Voltage per contact pair in series
24 V

Control circuit reliability at 24 V DC, 10 mA [Fault probability]
< 10^{-5} , < 1 failure in 100,000 switching operations
H_F

Terminal capacities

Solid or stranded
1 x (2,5 - 35)
2 x (2,5 - 16) mm²

Flexible with ferrules to DIN 46228
1 x (1 - 25)
2 x (1.5 - 10) mm²

Terminal screw
M6

Tightening torque for terminal screw
4 Nm

Technical safety parameters:

Notes

B10_d values as per EN ISO 13849-1, table C1

Rating data for approved types

Contacts
Rated operational voltage [U_e]
600 V AC

Contacts
Rated uninterrupted current max.
Main conducting paths
General use
63 A

Switching capacity
Maximum motor rating
Single-phase
120 V AC
3 HP

Switching capacity
Maximum motor rating
Single-phase
200 V AC
7.5 HP

Switching capacity
Maximum motor rating
Single-phase
240 V AC
10 HP

Switching capacity
Maximum motor rating
Three-phase

200 V AC
15 HP

Switching capacity
Maximum motor rating
Three-phase
240 V AC
15 HP

Switching capacity
Maximum motor rating
Three-phase
480 V AC
40 HP

Switching capacity
Maximum motor rating
Three-phase
600 V AC
40 HP

Short Circuit Current Rating
High fault rating
10 kA

Short Circuit Current Rating
max. Fuse
100, Class J A

Terminal capacity
Solid or flexible conductor with ferrule
12 - 4 AWG

Terminal capacity
Terminal screw
M6

Terminal capacity
Tightening torque
35.4 lb-in

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat

dissipation [I_r]
63 A

Heat dissipation per pole, current-dependent [P_{vid}]
4.5 W

Equipment heat dissipation, current-dependent
[P_{vid}]
0 W

Static heat dissipation, non-current-dependent [P_{vs}]
0 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+50 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of
enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating
materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating
materials to abnormal heat and fire due to internal
electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
UV resistance only in connection with protective

shield.

10.2 Strength of materials and parts

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Off-load switch (EC001105)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Changeover switch (ecl@ss10.0.1-27-37-14-05 [AKF062013])

Model
Reverser

Number of poles
3

With 0 (off) position
No

With retraction in 0-position
No

Rated permanent current I_u

63 A

Rated operation current I_e at AC-3, 400 V
41 A

Rated operation power at AC-3, 400 V
22 kW

Degree of protection (IP), front side
IP65

Degree of protection (NEMA), front side
12

Number of auxiliary contacts as normally closed
contact
0

Number of auxiliary contacts as normally open
contact
0

Number of auxiliary contacts as change-over
contact
0

Suitable for ground mounting
No

Suitable for front mounting 4-hole
Yes

Suitable for distribution board installation
No

Suitable for intermediate mounting
No

Complete device in housing
No

Material housing
Plastic

Type of control element
Toggle

Type of electrical connection of main circuit
Screw connection

APPROVALS

Product Standards
UL 60947-4-1; CSA - C22.2 No. 60947-4-1-14;
CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking

UL File No.
E36332

UL Category Control No.
NLRV

CSA File No.
12528


CSA Class No.
3211-05

North America Certification
UL listed, CSA certified

Suitable for
Branch circuits, suitable as motor disconnect

Degree of Protection
IEC: IP65; UL/CSA Type 1, 12

DIMENSIONS



- ZFS... Label mount not included as standard
 - Drilling dimensions door
- Cam switches T5B and T5 are same size, only their contacts are different



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)