

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



CI-K5-T5-2 - Insulated enclosure, HxWxD=280x200x125mm for T5-2



207441 CI-K5-T5-2

[Overview](#) [Specifications](#) [Resources](#)



207441 CI-K5-T5-2

Insulated enclosure, HxWxD=280x200x125mm for T5-2

EL-Nummer (Norway)

1456993

Small enclosure, degree of protection IP65, glass-fibre reinforced polycarbonate, enclosure base RAL 9005, black/operator only RAL 7035, light gray, metric cable entry knockouts top, bottom and in the back plate, hard metric cable entry knockouts, control cable entry, indicator light L-. can be mounted in base knock-out M20/M25, for T5-../Z switch, 1-2 contact units

- [Delivery program](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Approvals](#)
- [Dimensions](#)

Delivery program

Basic function
insulated enclosure
with metric knock-outs
For use with
T5-../Z
For use with
1 - 2 contact units
Information about equipment supplied
with an additional PE clamp
Degree of Protection
IP65

Notes

1 contact unit = 2 contacts

Design verification as per IEC/EN 61439

Technical data for design verification
Rated operational current for specified heat dissipation [I_n]
0 A
Heat dissipation per pole, current-dependent [P_{vid}]
0 W
Equipment heat dissipation, current-dependent [P_{vid}]
0 W
Static heat dissipation, non-current-dependent [P_{vs}]
0 W

Heat dissipation capacity [P_{diss}]

35 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+40 °C

Max. radiated heat dissipation with separate mounting, ambient air temperature +20 °C

35 W

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss10.0.1-27-37-13-01 [AKN343014])

Material housing

Plastic

Width

200 mm

Height

280 mm

Depth

125 mm

With transparent cover

No

Suitable for emergency stop
No
Model
Surface mounting
Degree of protection (IP)
IP65
Degree of protection (NEVA)
Other

Approvals

Product Standards
UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking
UL File No.
E54120
UL Category Control No.
MTW2
CSA File No.
12528
CSA Class No.
3211-07
North America Certification
UL listed, CSA certified
Degree of Protection
IEC: IP65; UL/CSA Type 1, 12

Dimensions



CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-bauform16_n](#)
File
(Web)

edz files

- [DA-CE-ETN.C-K5-T5-2](#)
File
(Web)

Step files


- [DA-CS-bauform16_n](#)
File
(Web)

Product photo



[1210PIC-337](#)
Photo

3D drawing



1151079

Line drawing
Insulated enclosures

Dimensions single product



1150DIM-203

Line drawing

Instruction Leaflet

- [Cam switch: switch-disconnector \(IL03801009Z\)](#)
Asset
former AWA1150-1982
(PDF, 06/2021, multilingual)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



Generate data sheet in PDF format



Generate data sheet in Excel format



Write a comment

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH