




**Main switch, 240/415 V AC, 63A, 1-pole**

**Part no.** IS-63/1  
**Catalog No.** 276274  
**Alternate Catalog No.** IS-63/1  
**EL-Nummer (Norway)** 1460851

Similar to illustration

### Delivery program

Basic function			Main load disconnecter switch
Number of poles			1 pole
Application			Switchgear for industrial and advanced commercial applications
Rated current	$I_n$	A	63
Product range			IS
Contact sequence			

### Technical data

#### Electrical

Standards			EN 45545-2; IEC 61373
-----------	--	--	-----------------------

### Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	63

Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	1.9
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	1.8
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	0
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

## Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss10.0.1-27-14-23-01 [AFZ813014])

Switching function			Other
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of poles			1
Rated current		A	63
Rated voltage		V	240
Min. rated voltage		V	240
Rated switching capacity		kA	12.5
Short-circuit breaking capacity (I <sub>cw</sub> )		kA	2
Voltage type			AC
With signal lamp			No
Colour calotte			Other
Lamp type			Other
Lamp socket			Other
Max. lamp power		W	0
Width in number of modular spacings			1
Built-in depth		mm	69.5
Degree of protection (IP)			IP40
Imprint/indication			Symbol "arrows"
Forced segregation (according to DIN VDE 0113)			No

## Dimensions

