



**C22G32**  
**CYLINDRICAL FUSE 22 x 58 32A GG 690V AC**

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data ETIM7.0](#)

## DELIVERY PROGRAM

Product range  
Fuse

Basic function  
Fuse-link

Field of application  
low voltage

Rated current [I]  
32 A

Rated voltage  
AC 690 V

Size  
22 x 58 mm

Utilization category  
gL/gG

Breaking Capacity  
80 kA

usable for size/applications  
for industrial applications  
for general purpose use

Standard/Approval  
IEC

Shape  
cylindrical

Standards/Regulations  
IEC 60269-2

## TECHNICAL DATA ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])

Size  
22x58 mm

Rated voltage  
690 - 690 V

Rated voltage  
Other

Voltage type  
AC

Utilization category  
gL/gG (cable protection/equipment protection)

Rated operating frequency  
45 - 62 Hz

Nominal current  
32 A

With striker  
No

Release characteristic  
Other

Breaking capacity  
80 kA

