



**Fuse-link, LV, 125 A, AC 500 V, NH2, gL/gG, IEC, dual indicator, live gripping lugs, weather resistant**

**Part no. NH 125A 500V gG SIZE 2 WEATHER RESISTANT**  
**Catalog No. 125NHG2BWP**

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	125
Rated voltage			AC 500 V
Construction size			NH2
Utilization category			gL/gG
Status indicator			dual (combination) indicator system
Description			live gripping lugs weather resistant
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with knife blade contacts

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			NH2
Rated current		A	125
Rated voltage		V	500
Voltage type			AC
Rated switching capacity		kA	120
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No