



355NHG2BWP NH 355A 500V gG SIZE 2 WEATHER RESISTANT

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data ETIM7.0](#)

DELIVERY PROGRAM

Product range
Fuse

Basic function
Fuse-link

Field of application
low voltage

Rated current [I]
355 A

Rated voltage
AC 500 V

Construction size
NH2

Utilization category
gL/gG

Status indicator
dual indicator

Description
live gripping lugs
weather resistant

Breaking Capacity
120 kA

usable for size/applications
industrial

Standard/Approval
IEC

Shape
square body with knife blade contacts

TECHNICAL DATA ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss 10.0.1-27-14-20-05 [AFZ800015])

Construction size
NH2

Rated current
355 A

Rated voltage
500 V

Voltage type
AC

Rated switching capacity
120 kA

Utilization category
gL/gG (cable protection/equipment protection)

Type of fuse status indicator
Combination fuse status indicator

Insulated metal gripping lugs (IMGL)
No

