#### Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norw egian Bokmål

### Worldwide English



PLS6-O6-DC-MW - Miniature circuit breaker (MOB), 6 A, 1p, characteristic: C, DC



## 243119 PLS6-06-DC-MW Overview Specifications Resources



- Delivery program
- Technical data

Design verification as per IEC/EN 61439

• Technical data ETIM 7.0

# 243119 PLS6-C6-DC-MW

Mniature circuit breaker (MCB), 6 A, 1p, characteristic: C, DC EL-Nummer (Norway) 1609276 Mniature circuit breaker (MCB), PLS6, 1-pole, tripping characteristic: C, rated current In: 6 A, rated switching capacity acc. to IEC/EN 60947-2: 6 kA, Switchgear for DC applications

### Delivery program

Basic function Mniature circuit-breakers Number of poles 1 pole Tripping characteristic C

Application Switchgear for DC applications Rated current [l<sub>n</sub>] 6 A Rated switching capacity acc. to IEC/EN 60947-2 [l<sub>cu</sub>] 6 kA Product range PLS6

### Technical data

Electrical Rated switching capacity acc. to IEC/EN 60947-2  $[I_{\rm cu}]$  6 kA

### Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation  $\left[I_n\right]$ 

6A Heat dissipation per pole, current-dependent [P<sub>vid</sub>] 0 W Equipment heat dissipation, current-dependent [P<sub>vid</sub>] 1.8 W Static heat dissipation, non-current-dependent [P<sub>vs</sub>] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +75 °C linear, per +1 °C, results in a 0.5% reduction of current carrying capacity IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2 Strength of materials and parts 10.2.6 Mechanical impact Does not apply, since the entire switchgear needs to be evaluated. 10.2 Strength of materials and parts10.2.7 Inscriptions Meets the product standard's requirements. 10.3 Degree of protection of ASSEVBLIES Does not apply, since the entire switchgear needs to be evaluated. 10.4 Clearances and creepage distances Meets the product standard's requirements. 10.5 Protection against electric shock Does not apply, since the entire switchgear needs to be evaluated. 10.6 Incorporation of switching devices and components Does not apply, since the entire switchgear needs to be evaluated. 10.7 Internal electrical circuits and connections Is the panel builder's responsibility. 10.8 Connections for external conductors Is the panel builder's responsibility. 10.9 Insulation properties 10.9.2 Pow er-frequency electric strength Is the panel builder's responsibility. 10.9 Insulation properties 10.9.3 Impulse withstand voltage Is the panel builder's responsibility. 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material Is the panel builder's responsibility. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. Technical data ETIM 7.0

### Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042) Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss10.0.1-27-14-19-01 [AAB905014]) Release characteristic C Number of poles (total) 1

Number of protected poles 1 Rated current 6A Rated voltage 220 V Rated insulation voltage Ui 440 V Rated impulse withstand voltage Ump 4 kV Rated short-circuit breaking capacity Icn EN 60898 at 230 V 0 kA Rated short-circuit breaking capacity Icn EN 60898 at 400 V 0 kA Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V 10 kA Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V 10 kA Voltage type DC Frequency 0-0Hz **Ourrent limiting class** 3 Suitable for flush-mounted installation No Concurrently switching N-neutral No Over voltage category 3 Pollution degree 2 Additional equipment possible Yes Width in number of modular spacings 1 Built-in depth 70.5 mm Degree of protection (IP) IP20 Ambient temperature during operating -25 - 75 °C Connectable conductor cross section multi-wired  $1 - 25 \, \text{mm}^2$ Connectable conductor cross section solid-core  $1 - 25 \, \text{mm}^2$ 

## CAD data

• 3D Preview (Web)

### DWG files

• DA-CD-pls\_1p File (Web)

### edz files

• DA-CE-ETN.PLS6-C6-DC-MW File (Web)

## Step files

• DA-CS-pls\_1p File (Web)

# Product photo



# Instruction Leaflet

Oircuit Breakers (IL019140ZU)
 Asset
 MA180503264
 (PDF, 10/2019, Language independent)

# **Declaration of Conformity**

EU

• DA-DC-03\_PLS\_200416 Asset (PDF)

# Download-Center

- Dow nload-Center (this item)
  Eaton EVEA Dow nload-Center dow nload data for this item
- Dow nload-Center
  Eaton EVEA Dow nload-Center

ß

Generate data sheet in PDF format

x

Generate data sheet in Excel format

 $\square$ 

Write a comment

Imprint Privacy Policy Legal Disclaimer Terms and Conditions © 2021 by Eaton Industries GmbH