Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norw egian Bokmål

Worldwide English



PLS6-C6/2-DC-MW - Mniature circuit breaker (MCB), 6 A, 2p, characteristic: C, DC



243132 PLS6-06/2-DC-MW

Overview Specifications Resources



243132 PLS6-C6/2-DC-MW

Mniature circuit breaker (MCB), 6 A, 2p, characteristic: C, DC EL-Nummer (Norway) 1609287

Mniature circuit breaker (MCB), PLS6, 2-pole, tripping characteristic: C, rated current In: 6 A, rated switching capacity acc. to IEC/EN 60947-2: 6 kA, Switchgear for DC applications

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0

Delivery program

Basic function

Miniature circuit-breakers

Number of poles

2 pole

Tripping characteristic

C.

Application

Switchgear for DC applications

Rated current [In]

6 A

Rated switching capacity acc. to IEC/EN 60947-2 [lcu]

6 kA

Product range

PLS6

Technical data

Bectrical

Rated switching capacity acc. to IEC/EN 60947-2 [lau]

6 kA

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [1,]

6 A

Heat dissipation per pole, current-dependent [P_{id}]

0 W

Equipment heat dissipation, current-dependent [P_{id}]

1.8 W

Static heat dissipation, non-current-dependent [P_s]

0 W

Heat dissipation capacity [P_{diss}]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+75 °C

linear, per +1 °C, results in a 0.5% reduction of current carrying capacity

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEVBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Mniature circuit breaker (MCB) (EC000042)

Bectric engineering, automation, process control engineering / Bectrical installation, device / Miniature circuit breaker system (MOB) / Miniature circuit breaker (MOB) (ecl@ss10.0.1-27-14-19-01 [AAB905014])

Release characteristic

С

Number of poles (total)

2

Number of protected poles

2

Rated current

6 A

Rated voltage

220 V

Rated insulation voltage Ui

440 V

Rated impulse withstand voltage Ump

4 kV

Rated short-circuit breaking capacity Icn EN 60898 at 230 V

0 kA

Rated short-circuit breaking capacity Icn \pm N 60898 at 400 V

0 kA

Rated short-circuit breaking capacity lcu IEC 60947-2 at 230 $\rm V$

10 kA

Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V

10 kA

Voltage type

DC

Frequency

0-0Hz

Current limiting class

S

Suitable for flush-mounted installation

No

Concurrently switching N-neutral

No

Over voltage category

3

Pollution degree

2

Additional equipment possible

V۵

Width in number of modular spacings

2

Built-in depth

 $70.5\,mm$

Degree of protection (IP)

IP20

Ambient temperature during operating

-25 - 75 °C

Connectable conductor cross section multi-wired

1 - 25 mm²

Connectable conductor cross section solid-core

1 - 25 mm²

CAD data

• 3D Preview (Web)

DWG files

DA-CD-pls_2pFile(Web)

edz files

DA-OE-ETN.PLS6-O6_2-DC-MW File (Web)

Step files

DA-CS-pls_2pFile(Web)

Product photo



System Sy

Miniature circuit breaker (MCB)

Instruction Leaflet

Circuit Breakers (IL019140ZU)
 Asset
 MA180503264
 (PDF, 10/2019, Language independent)

Declaration of Conformity

EU

DA-DC-03_PLS_200416
 Asset
 (PDF)

Download-Center

Download-Center (this item)
 Eaton EVEA Download-Center - download data for this item

Download-Center
 Eaton EVEA Download-Center

ല Generate data sheet in PDF format

Generate data sheet in Excel format

□ Write a comment

Imprint Privacy Policy Legal Disclaimer Terms and Conditions

© 2021 by Eaton Industries GmbH