



Surge arrester plug-in unit, 460VAC, 20 kA

Part no. SPCT2-460
Catalog No. 167607
Alternate Catalog No. SPCT2-460
No.
EL-Nummer (Norway) 0001609762

Similar to illustration

Delivery program

Products		Surge arresters
Application field		Residential buildings Utility buildings Open areas

Technical data ETIM 7.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)		
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss10.0.1-27-13-08-05 [ACN278011])		
System configuration DC		No
System configuration IT		No
System configuration TN		Yes
System configuration TN-C		No
System configuration TN-C-S		No
System configuration TN-S		No
System configuration TT		No
System configuration other		Yes
Number of conductors (without earthing)		0
Nominal discharge surge current (8/20)	kA	20
Nominal voltage AC	V	460
Nominal voltage DC	V	0
Short-circuit breaking capacity (Isc cr)	kA	0
Max. continuous voltage AC	V	460
Max. discharge surge current (8/20)	kA	40
Max. continuous voltage DC	V	0
Mounting method		On basic element
Construction size		1 modular spacing
Max. PV-voltage	V	0
Voltage protection level	kV	2.2
Max. conductor cross section solid (solid, stranded)	mm ²	0
Max. conductor cross section flexible (fine-strand)	mm ²	0
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
With remote signalling contact		No
Integrated backup fuse		No
Signalling at the device		Optic
Category type 2		Yes
Degree of protection (IP)		IP20