



RCD/RCB combination, 20 A, 30 mA, MCB trip characteristic: B, 2p, RCD trip characteristic: F



Part no. NmRBM-20/2/B/003-F-0L
Catalog No. MB-300119
Alternate Catalog 300119
No.
EL-Nummer 1611904
(Norway)

Technical data

Electrical

Characteristic			B
----------------	--	--	---

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Earth leakage circuit breaker (EC000905)			
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / MCB/RCCB combination (ecl@ss10.0.1-27-14-22-07 [AFZ810015])			
Number of poles (total)			2
Number of protected poles			2
Rated voltage		V	230
Rated insulation voltage Ui		V	250
Rated impulse withstand voltage Uimp		kV	4
Rated current		A	20
Rated fault current		A	0.03
Leakage current type			F
Current limiting class			3
Rated short-circuit breaking capacity according to EN 61009		kA	10
Rated short-circuit breaking capacity according to IEC 60947-2		kA	0
Rated short-circuit breaking capacity Icn according to EN 61009-1		kA	10
Disconnection characteristic			Short-time delayed
Surge current capacity		kA	3
Voltage type			AC
Frequency			50 Hz
Release characteristic			B
Concurrently switching neutral conductor			No
With interlocking device			No
Over voltage category			3
Pollution degree			2
Ambient temperature during operating		°C	-25 - 40
Width in number of modular spacings			2
Built-in depth		mm	70
Flush-mounted installation			No
Anti- nuisance tripping version			No
Degree of protection (IP)			IP20
Connectable conductor cross section solid-core		mm ²	1 - 25
Connectable conductor cross section multi-wired		mm ²	1 - 25