



RCD/RCB combination, 6 A, 30 mA, MCB trip characteristic: C, 2p, RCD trip characteristic: F

Part no. NMRBM-6/2/C/003-F
Catalog No. MB-300014
Alternate Catalog No. 300014
EL-Nummer (Norway) 1611908

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Earth leakage circuit breaker (EC000905)		
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / MCB/RCCB combination (ecl@ss10.0.1-27-14-22-07 [AFZ810015])		
Number of poles (total)		2
Number of protected poles		2
Rated voltage	V	230
Rated insulation voltage Ui	V	250
Rated impulse withstand voltage Uimp	kV	4
Rated current	A	6
Rated fault current	A	0.03
Leakage current type		F
Current limiting class		3
Rated short-circuit breaking capacity according to EN 61009	kA	10
Rated short-circuit breaking capacity according to IEC 60947-2	kA	0
Rated short-circuit breaking capacity Icn according to EN 61009-1	kA	10
Disconnection characteristic		Short-time delayed
Surge current capacity	kA	3
Voltage type		AC
Frequency		50 Hz
Release characteristic		C
Concurrently switching neutral conductor		No
With interlocking device		No
Over voltage category		3
Pollution degree		2
Ambient temperature during operating	°C	-25 - 40
Width in number of modular spacings		2
Built-in depth	mm	70
Flush-mounted installation		No
Anti- nuisance tripping version		No
Degree of protection (IP)		IP20
Connectable conductor cross section solid-core	mm ²	1 - 25
Connectable conductor cross section multi-wired	mm ²	1 - 25