



RCD/RCB combination, 40 A, 30 mA, MCB trip characteristic: C, 2p, RCD trip characteristic: F

Part no. NmRB6-40/2/C/003-F
Catalog No. MB-300070
Alternate Catalog 300070
No.
EL-Nummer 1611916
(Norway)

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Earth leakage circuit breaker (EC000905)			
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / MCB/RCCB combination (ecl@ss10.0.1-27-14-22-07 [AFZ810015])			
Number of poles (total)			2
Number of protected poles			2
Rated voltage	V		230
Rated insulation voltage Ui	V		250
Rated impulse withstand voltage Uimp	kV		4
Rated current	A		40
Rated fault current	A		0.03
Leakage current type			F
Current limiting class			3
Rated short-circuit breaking capacity according to EN 61009	kA		6
Rated short-circuit breaking capacity according to IEC 60947-2	kA		0
Rated short-circuit breaking capacity Icn according to EN 61009-1	kA		6
Disconnection characteristic			Short-time delayed
Surge current capacity	kA		3
Voltage type			AC
Frequency			50 Hz
Release characteristic			C
Concurrently switching neutral conductor			No
With interlocking device			No
Over voltage category			3
Pollution degree			2
Ambient temperature during operating	°C		-25 - 40
Width in number of modular spacings			2
Built-in depth	mm		70
Flush-mounted installation			No
Anti-nuisance tripping version			No
Degree of protection (IP)			IP20
Connectable conductor cross section solid-core	mm ²		1 - 25
Connectable conductor cross section multi-wired	mm ²		1 - 25