

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



XNH3-A630 - NH fuse-switch 3p flange connection M10 max. 300 mm<sup>2</sup>; mounting plate; NH3



183071 XNH3-A630

[Overview](#) [Specifications](#) [Resources](#)



## 183071 XNH3-A630

NH fuse-switch 3p flange connection M10 max. 300 mm<sup>2</sup>; mounting plate; NH3

EL-Nummer (Norway)

1624046

NH fuse switch-disconnector 3 pole with M10 flat terminal max. 300 mm<sup>2</sup>; mounting plate; for NH3 fuse-links; optionally lockable with XNH-XLOCK and padlock

- 



- 



- [Delivery program](#)

- [Technical data](#)

- [Design verification as per IEC/EN 61439](#)

- [Technical data ETIM 7.0](#)

- [Dimensions](#)

### Delivery program

Basic function  
Basic device  
Number of poles  
3 pole  
Mounting type  
DIN rails  
Mounting plate  
Size  
3  
Type of connection  
Flat connection  
Rated operational current [I<sub>b</sub>]  
630 A  
Front degree of protection (XNH installed)

IP20 (Operating status)  
IP2XC (Contact protection)  
IP10 (Handle cover open)  
Rated operational voltage [ $U_e$ ]  
690 V AC  
Rated operational voltage [ $U_e$ ]  
440 V DC  
Rated conditional short-circuit current  
120 (500 V)  
100 (690 V) kA  
Flammability characteristics  
Self-extinguishing as per UL 94  
Description  
Current paths of electrolytic copper, silver-plated  
Successor to  
026742  
284691

## Technical data

Electrical  
Standards  
IEC/EN 60947-3  
Rated operational voltage [ $U_e$ ]  
690 V AC  
Rated operational voltage [ $U_e$ ]  
440 V DC  
Rated operational current [ $I_e$ ]  
630 A  
Rated frequency [f]  
40 - 60 Hz  
Rated insulation voltage [U]  
800 V AC  
Total heat dissipation at  $I_{th}$  (without fuses) [ $P_d$ ]  
51 W  
Heat dissipation at 80% (without fuses) [ $P_d$ ]  
32.5 W  
Rated impulse withstand voltage [ $U_{imp}$ ]  
8 kV  
Utilization category AC-23B Rated operating voltage [ $U_e$ ]  
400 V AC  
Utilization category AC-23B Rated operating current [ $I_e$ ]  
630 A  
Utilization category AC22B Rated operating voltage [ $U_e$ ]  
500 V AC  
Utilization category AC22B Rated operating current [ $I_e$ ]  
630 A  
Utilization category AC-21B Rated operating voltage [ $U_e$ ]  
690 V AC  
Utilization category AC-21B Rated operating current [ $I_e$ ]  
630 A  
Utilization category DC-22B Rated operating voltage [ $U_e$ ]  
440 V DC  
Utilization category DC-22B Rated operating current [ $I_e$ ]  
630 A  
Utilization category DC21B Rated operating voltage [ $U_e$ ]  
250 V DC  
Utilization category DC21B Rated operating current [ $I_e$ ]  
630 A  
Rated conditional short-circuit current  
120 (500 V)  
100 (690 V) kA  
Rated short-time withstand current [ $I_{cw}$ ]  
10 kA  
Max. fuseSize according to DIN VDE 0636-2  
3 / 2  
Max. fuseMax. permitted power loss per fuse link [ $P_d$ ]  
48 W  
Lifespan, electrical [Operations]

200

Mechanical

Front degree of protection (XNH installed)

IP20 (Operating status)

IP2XC (Contact protection)

IP10 (Handle cover open)

Ambient temperature

-25 - +55 °C

Rated operating mode

Permanent operation

Activation

Dependent manual activation

Mounting position

Vertical, horizontal

Altitude

Max. 2000 m

Overvoltage category/pollution degree

III/3

RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)

Yes

Direction of incoming supply

as required

Lockable

Yes, optional

Sealable

Yes, Standard

Material characteristicsMaterial

Polyamide

Material characteristicsColour

Grey

Flammability characteristics

Self-extinguishing as per UL 94

Halogen-free

Yes

Voltage test

Yes, sliding inspection windows

Lifespan, mechanical [Operations]

800

Track resistance

CTI 600

Heat deflection temperature

125 °C

Terminal capacity

Flange connectionBolt diameter

M10

Flange connectionCable lug max. width

56 mm

Flange connectionFlat busbar

50 x 10 mm

Box terminalStranded

95 - 300 Cu/Al mm<sup>2</sup>

Box terminalCopper strip [Number of segments x width x thickness]

6 x 16 x 0,8 - 10 x 32 x 1 mm

Box terminalStranded

auf Anfrage mm<sup>2</sup>

Box terminalCopper band [Number of segments x width x thickness ]

11 x 21 x 1 mm

Clamp-type terminalStranded

120 - 300 Cu/Al mm<sup>2</sup>

Double clamp-type terminalStranded

2x (120 - 240) Cu/Al mm<sup>2</sup>

## Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [ $I_n$ ]

630 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]

7.3 W

Equipment heat dissipation, current-dependent [ $P_{\text{ed}}$ ]

22 W

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Is the panel builder's responsibility.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

$U_i = 800 \text{ V AC}$

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecl@ss 10.0.1-27-37-14-01 [AKF058013])

Version as main switch

No

Version as safety switch

No

Max. rated operation voltage  $U_e \text{ AC}$

690 V

Rated permanent current  $I_n$

630 A

Rated operation power at AC-23, 400 V

0 kW

Conditioned rated short-circuit current  $I_k$

120 kA

Rated short-time withstand current  $I_{cw}$


3 kA

Suitable for fuses

NH3

Number of poles  
3  
With error protection  
No  
Type of electrical connection of main circuit  
Screw connection  
Cable entry  
Other  
Equipped with connectors  
No  
Suitable for ground mounting  
Yes  
Suitable for front mounting 4-hole  
No  
Suitable for busbar mounting  
No  
Type of control element  
Cover grip  
Position control element  
Front side  
Motor drive optional  
No  
Motor drive integrated  
No  
Version as emergency stop installation  
No  
Degree of protection (IP), front side  
Other

## Dimensions



## Product photo



vt58315

Photo

Fuse switch-disconnectors



vt58415

Photo

Fuse switch-disconnectors




vt65315

Photo

Fuse switch-disconnectors

## Dimensions single product



1230DIM-357

Line drawing

# Instruction Leaflet

- [IL0131110ZU](#)  
Asset  
(PDF, Language independent)

# Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

