



**250NHG02B**  
**NH FUSE 250A 500V GG/GL SIZE 02**

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data ETIM7.0](#)

## DELIVERY PROGRAM

Product range  
Fuse

Basic function  
Fuse-link

Field of application  
low voltage

Rated current [I]  
250 A

Rated voltage  
AC 500 V

Construction size  
NH02

Utilization category  
gL/gG

Status indicator  
dual indicator

Description  
live gripping lugs

Breaking Capacity  
120 kA

Standard/Approval  
IEC

Shape  
square body with knife blade contacts

Standards/Regulations  
IEC 60269-2 fuse system A  
DIN 43620  
VDE 0636-2

## TECHNICAL DATA ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss 10.0.1-27-14-20-05 [AFZ800015])

Construction size  
Other

Rated current  
250 A

Rated voltage  
500 V

Voltage type  
AC

Rated switching capacity  
120 kA

Utilization category  
gL/gG (cable protection/equipment protection)

Type of fuse status indicator  
Combination fuse status indicator

Insulated metal gripping lugs (IMGL)  
No

