

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NH FUSE 20AMP 690V SIZE 000 GG MGL - Fuse-link, low voltage, 20 A, AC 690 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs



20NHG000B-690 NH FUSE 20AMP 690V SIZE 000 GG MGL

[Overview](#) [Specifications](#) [Resources](#)



# 20NHG000B-690 NH FUSE 20AMP 690V SIZE 000 GG MGL

Fuse-link, low voltage, 20 A, AC 690 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs  
 EL-Nummer (Norway) 1664100

Fuse, fuse-link, low voltage, 20 A, AC 690 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA



- 
- 

## Delivery program

Product range

Fuse  
Basic function  
Fuse-link  
Field of application  
low voltage  
Rated current [I]  
20 A  
Rated voltage  
AC 690 V  
Construction size  
NH000  
Utilization category  
gL/gG  
Status indicator  
dual indicator  
Description  
live gripping lugs  
Breaking Capacity  
120 kA  
usable for size/applications  
industrial  
Standard/Approval  
IEC  
Shape  
square body with knife blade contacts  
Standards/Regulations  
IEC 60269-2 fuse system A  
DIN 43620  
VDE 0636-2

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)  
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])  
Construction size  
NH000  
Rated current  
20 A  
Rated voltage  
690 V  
Voltage type  
AC  
Rated switching capacity  
120 kA  
Utilization category  
gL/gG (cable protection/equipment protection)  
Type of fuse status indicator  
Combination fuse status indicator  
Insulated metal gripping lugs (IMGL)  
No

## Product photo

- □ [100nhg000b\\_c](#)  
Photo



- [100nhg000b\\_l](#)  
Photo

- □ [100nhg000b\\_r](#)  
Photo



## Declaration of Conformity

### EU

- [Size 000, 690V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00003483\)](#)  
Asset  
(PDF)

### UK

- [Size 000, 690V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00004045\)](#)  
Asset  
(PDF)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH