



Cable gland, M50, RAL 7035, IP68\_x

Part no. V-M50  
Article no. 206913

## Delivery program

Product range		General switchboard accessories
Accessories		Cable management
Cable entry		M50
Hole diameter	mm	50,5
Outer cable diameter	mm	21 - 35
Example of application: NYM/NYY cable, 4-core	mm <sup>2</sup>	NYM 4 x 35/5 x 25
Description		Flammability classification V2 according to UL94 With lock nut and built-in strain relief
Material		Polyamide Halogen free
Surface finish		RAL 7035
Information about equipment supplied		With lock nut and built-in strain relief
Degree of Protection		IP68 up to 5 bar (30 min)

## Technical data

### General

Degree of Protection		IP68 up to 5 bar (30 min)
----------------------	--	---------------------------

### Material characteristics

Material		Polyamide Halogen free
Colour		Gray, RAL 7035
Temperature resistant		-20 °C - 100 °C, short-time up to approx. 120 °C
Chemical resistant		Resistant against : Acetone, petrol, paraffin, diesel, grease, oil, solvent for paints and varnishes
Danger of stress fracture		low
Flame retardant		Glow wire test 750 °C according to EN 60695-2-11
Flammability classification according to UL94		V2

## Dimensions

