



## Diaphragm grommet, M25

**Part no.** KT-M25

**Article no.** 207603



Powering Business Worldwide™

### Delivery program

Product range			General switchboard accessories
Accessories			Cable management
Accessories			Cable grommets Metric diaphragm grommets
Degree of Protection			up to IP66
Description			With integral push-through diaphragm
Material			PE and thermoplastic elastomer Halogen free
Surface finish			RAL 7035
Cable entry			M25
Hole diameter		mm	25,5
Outer cable diameter		mm	1 - 18
Example of application: NYM/NYY cable, 4-core		mm <sup>2</sup>	H03VV-F3 x 0.75, NYM 4 x 10

### Technical data

#### General

Overvoltage category/pollution degree			III/3
Degree of Protection			up to IP66

#### Contacts

Overvoltage category/pollution degree			III/3
---------------------------------------	--	--	-------

#### Material characteristics

Material			PE and thermoplastic elastomer Halogen free
Colour			Gray, RAL 7035
Temperature resistant			-40 °C - 80 °C, short-time up to approx. 100 °C
Chemical resistant			Resistant against: Alcohol, animal and plant fat, brine, light acids, water
Danger of stress fracture			Relative high

#### Mechanical variables

Overvoltage category/pollution degree			III/3
---------------------------------------	--	--	-------

### Approvals

Specially designed for North America			No
--------------------------------------	--	--	----

## Dimensions

