



Diaphragm grommet, M32

Part no. KT-M32
Article no. 207604

Delivery program

Product range			General switchboard accessories
Accessories			Cable management
Accessories			Cable grommets Metric diaphragm grommets
Degree of Protection			up to IP66
Description			With integral push-through diaphragm
Material			PE and thermoplastic elastomer Halogen free
Surface finish			RAL 7035
Cable entry			M32
Hole diameter		mm	32,5
Outer cable diameter		mm	1 - 25
Example of application: NYM/NYY cable, 4-core		mm ²	H03VV-F3 x 0.75, NYM 4 x 16/5 x 10

Technical data

General

Overvoltage category/pollution degree			III/3
Degree of Protection			up to IP66

Contacts

Overvoltage category/pollution degree			III/3
---------------------------------------	--	--	-------

Material characteristics

Material			PE and thermoplastic elastomer Halogen free
Colour			Gray, RAL 7035
Temperature resistant			-40 °C - 80 °C, short-time up to approx. 100 °C
Chemical resistant			Resistant against: Alcohol, animal and plant fat, brine, light acids, water
Danger of stress fracture			Relative high

Mechanical variables

Overvoltage category/pollution degree			III/3
---------------------------------------	--	--	-------

Approvals

Specially designed for North America			No
--------------------------------------	--	--	----

Dimensions

