



F3A-2K - Flange plate 2-component-plastic, up to IP55, Ø 3-70 mm

**Part no. F3A-2K-D70/3
EP-501499**

Product name	Eaton xEnergy Basic LV systems Low voltage switchgear
Part no.	F3A-2K-D70/3
EAN	9010653053187
Product Length/Depth	140 millimetre
Product height	17.5 millimetre
Product width	230 millimetre
Product weight	0.2 kilogram
Compliances	RoHS conform
Product Tradename	xEnergy Basic
Product Type	LV systems
Product Sub Type	Low voltage switchgear
Globally Marketable	Yes

Type	Accessory xEnergy series Accessory CS Accessory exterior fitting
Model	Membrane
Accessory/spare part type	Flanges

Shape	Straight
Surface finishing	RAL 7035, light gray RAL 7001, silver gray
Surface protection	Untreated
Material	Plastic
Degree of protection	IP55 Other
Number of connector holes	12
Thread type	None
Suitable for nominal thread (PG) - min	3
Suitable for nominal thread (PG) - max	70

Features	Pre-stamping
Special features	Membrane flange (push-through cable entry), RAL 7035 / RAL 7001, compound of polyamide (PA) and thermoplastic elastomer (TPE)
Used with	Accessory CS Accessory exterior fitting

Technical data ETIM 8.0

Distribution boards (EG000023) / Gland plate for enclosure/cabinet (EC000211)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Gland plate for small distribution boards/switchgear cabinets (ecl@ss10.0.1-27-14-24-21 [ADI315007])

Model	Membrane
Type	Straight
Width	mm 230
Height	mm 17.5
Depth	mm 140
Material	Plastic
Surface protection	Untreated
Degree of protection (NEMA)	Other
Pre-stamping	Yes
Number of connector holes	12

Thread type		None
Suitable for nominal thread metric/PG		3 - 70