



**F3A-2K - Flange plate 2-component-plastic, up to IP66, metrical entries**

**Part no. F3A-2K-M50/16-1  
EP-501502**

Product name	Eaton xEnergy Basic LV systems Low voltage switchgear
Part no.	F3A-2K-M50/16-1
EAN	9010653053217
Product Length/Depth	140 millimetre
Product height	17.5 millimetre
Product width	230 millimetre
Product weight	0.2 kilogram
Compliances	RoHS conform
Product Tradename	xEnergy Basic
Product Type	LV systems
Product Sub Type	Low voltage switchgear
Globally Marketable	Yes

Type	Accessory xEnergy series Accessory CS Accessory exterior fitting
Model	Cable screw gland
Accessory/spare part type	Flanges

Shape	Straight
Surface finishing	RAL 7035, light gray
Surface protection	Untreated
Material	Plastic
Degree of protection	IP66 Other
Number of connector holes	15
Thread type	Metric
Suitable for nominal thread (PG) - min	16
Suitable for nominal thread (PG) - max	50

Features	Pre-stamping
Special features	Blind flange with knock-outs, RAL 7035, compound of polyamide (PA) and thermoplastic elastomer (TPE)
Used with	Accessory CS Accessory exterior fitting

**Technical data ETIM 8.0**

Distribution boards (EG000023) / Gland plate for enclosure/cabinet (EC000211)	
Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Gland plate for small distribution boards/switchgear cabinets (ecl@ss10.0.1-27-14-24-21 [ADI315007])	
Model	Cable screw gland
Type	Straight
Width	mm 230
Height	mm 17.5
Depth	mm 140
Material	Plastic
Surface protection	Untreated
Degree of protection (NEMA)	Other
Pre-stamping	Yes
Number of connector holes	15

Thread type		Metric
Suitable for nominal thread metric/PG		16 - 50