DATASHEET - F3A-2K-0

EATON Powering Business Worldwide^{*}



F3A-2K - Flange plate 2-component-plastic, up to IP66, blind version

Part no.

F3A-2K-0 EP-501496

Product name	E	aton xEnergy Basic LV systems Low voltage switchgear
Part no.	E	3A-2K-0
EAN	90	010653053163
Product Length/Depth	14	40 millimetre
Product height	17	7.5 millimetre
Product width	23	30 millimetre
Product weight	0.	.25 kilogram
Compliances	R	oHS conform
Product Tradename	x	Energy Basic
Product Type	L	V systems
Product Sub Type	Lo	ow voltage switchgear
Globally Marketable	Ye	es
Туре	A	ccessory xEnergy series ccessory CS ccessory exterior fitting
Model	В	lind
Accessory/spare part type	FI	langes
Shape	Si	traight
Surface finishing	R	AL 7035, light gray
Surface protection	U	Intreated
Material	P	lastic
Degree of protection		266 ther
Number of connector holes	0	
Thread type	N	lone
Suitable for nominal thread (PG) - min	0	
Suitable for nominal thread (PG) - max	0	
Features		lone re-stamping
Special features	В	lind flange without knock-outs, RAL 7035, compound of polyamide (PA) and nermoplastic elastomer (TPE)
Used with	A	ccessory CS ccessory exterior fitting

Technical data ETIM 8.0

Distribution boards (EG000023) / Gland plate for enclosure/cabinet (EC000211)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Gland plate for small distribution boards/switchgear cabinets (ecl@ss10.0.1-27-14-24-21 [ADI315007])

Model		Blind
Туре		Straight
Width	mm	n 230
Height	mm	n 17.5
Depth	mm	n 140
Material		Plastic
Surface protection		Untreated
Degree of protection (NEMA)		Other
Pre-stamping		Yes
Number of connector holes		0

Thread type	None	
Suitable for nominal thread metric/PG	0 - 0	