



Busbar support, 1p, profile up to 720mm²

Part no. BBS-1/PR
Article no. 107165



Powering Business Worldwide™

Delivery program

Product range			60 mm system 185 mm system
Basic function			System for profile busbars
Subrange			Busbar supports Double T profile busbar carrier
Material			Thermoplast, silicon free, chlorine free
Halogen free			yes
Self-extinguishing			to UL 94
Colour			RAL 7035
Track resistance			CTI 200
Temperature resistant			to 120°C
Description			Suitable for assembly of PE or N bar With screw block inside
Pole			1
Rated operational current	I_e	A	1600
For use with			Double T profile

Technical data

General

Interval between busbar centres		mm	60 185
---------------------------------	--	----	-----------

Contacts

Interval between busbar centres		mm	60 185
---------------------------------	--	----	-----------

Electrical data

Rated operational current	I_e	A	1600
---------------------------	-------	---	------

Material characteristics

Material			Thermoplast, silicon free, chlorine free
Colour			RAL 7035
Track resistance			CTI 200
Temperature resistant			to 120°C

Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

Dimensions

