



Busbar shroud section, 12-30x5, B=1m




Powering Business Worldwide™

Part no. **BBC-FL5**

Catalog No. **107173**

EL-Nummer
(Norway) **2465011**

Delivery program

			
Product range			60 mm system Compact system
Subrange			Bar covers
Material			Silicon free, chlorine free
Self-extinguishing			to UL 94
Temperature resistant			to 110°C
Length		mm	1000
For use with			12 x 5 15 x 5 20 x 5 25 x 5 30 x 5
For use with			All 5 mm thick flat busbars

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Accessories for busbars (EC002270)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar (accessories) (ecl@ss10.0.1-27-40-06-36 [AC0563011])			
Type of accessory			Contact protection rail

Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E300273
UL Category Control No.			NMTR, NMTR7
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL listed, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits