





**Terminal plate, 6-50mm<sup>2</sup>, 54 mm**


**Part no. BBA-TP3/50**  
**Article no. 107183**

## Delivery program

Product range			60 mm system
Basic function			Connections
Subrange			Clamp plate
Material			Silicon free, chlorine free
Self-extinguishing			to UL 94
Track resistance			CTI 200
Temperature resistant			to 120°C
Description			The terminal can be removed for the connection of uncut conductors Looping is not possible
Terminal area W x H		mm	10 x 15
Width		mm	54
Pole			3
Rated operational current	I <sub>e</sub>	A	300
Copper strip		mm	6 - 50 mm <sup>2</sup> AWG 10 - AWG 2/0.    6 x 9 x 0.8
Cu factor		kg	0,03
For use with			12 x 5/10 15 x 5/10 20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile

### Notes

 round conductor, solid


 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Section conductor, solid

Sector conductor, stranded

 CU band

 CU busbar

## Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E300273
UL Category Control No.			NMTR, NMTR7
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL listed, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits

## Dimensions

