






Terminal plate, 3p, 95-300mm², 560A





Part no. BBA-TP3/300
Catalog No. 107185

EL-Nummer (Norway) 2465023

Delivery program

Product range			60 mm system
Basic function			Connections
Subrange			Connection kit
Material			Silicon free, chlorine free
Self-extinguishing			to UL 94
Track resistance			CTI 200
Temperature resistant			to 120°C
Description			Pole pitch adjustable Fixing direct over busbar terminals Including shroud with adjustable width Looping is possible
Width		mm	180 - 240
Pole			3
Rated operational current conductor	I _e	A	560
			95 - 300 mm ² MCM300 - MCM600. directly terminated:   
Cu factor		kg	0,00
For use with			20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile

Notes

-  round conductor, solid
-  Flexible, round conductor with correctly crimped ferrule
- Round conductor, stranded
-  Section conductor, solid
- Sector conductor, stranded
- # CU band
-  CU busbar

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])			
Busbar thickness		mm	5 - 10
Busbar width		mm	12 - 30
Suitable for			Flat rail
Width clamp		mm	240
Max. conductor cross section		mm ²	300
Max. rated operation current I _e		A	560
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			Yes
Suitable for strip conductor connection			Yes

Dimensions

