



Terminal plate, 3p, copper band up to 32x20 mm, 800A

Part no. **BBA-TP3/CU-BAND**  
 Catalog No. **107186**

EL-Nummer **2465024**  
 (Norway)

**Delivery program**

Product range			60 mm system
Basic function			Connections
Subrange			Connection kit
Material			Silicon free, chlorine free
Self-extinguishing			to UL 94
Track resistance			CTI 200
Temperature resistant			to 120°C
Description			Pole pitch adjustable Fixing direct over busbar terminals Including shroud with adjustable width Looping is possible
Terminal area W x H		mm	32 x 25
Width		mm	180 - 240
Pole			3
Rated operational current conductor	$I_e$	A	800
Cu factor		kg	0,00
For use with			20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile

**Notes**

- round conductor, solid
- ⊗ Flexible, round conductor with correctly crimped ferrule
- Round conductor, stranded
- ⊙ Section conductor, solid
- Sector conductor, stranded
- # CU band
- CU busbar

**Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])			
Busbar thickness		mm	5 - 10
Busbar width		mm	20 - 30
Suitable for			Flat rail
Width clamp		mm	240
Max. conductor cross section		mm <sup>2</sup>	750
Max. rated operation current Ie		A	800
Suitable for round conductor connection			No
Suitable for sector conductor connection			No
Suitable for strip conductor connection			Yes

## Dimensions

