

Eaton 101455

Catalog Number: 101455

Eaton Moeller® series BBA Busbar adapter, 45 mm, 16 A, DIN rail:
2



General specifications

Product Name	Catalog Number
Eaton Moeller® series BBA Accessory Busbar adapter	101455
	Model Code
	BBA0C-16
EAN	Product Length/Depth
4015081013753	200 mm
Product Height	Product Width
63 mm	45 mm
Product Weight	Certifications
0.28 kg	CE
	IEC60439-1
	CSA-C22.2 No. 14
	UL File No.: E300273
	UL 508A
	Certified by UL for use in Canada
	UL Category Control No.: NMTR;
	NMTR7
	UL
	UL 508

Catalog Notes

This item can only be ordered until
December 31, 2023 with a maximum
delivery date of May 31, 2024.

Product specifications

Nominal current

16 A

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Number of DIN rails

2

Busbar thickness - min

5 mm

Equipment heat dissipation, current-dependent P_{vid}

0.8 W

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Voltage rating at AC

690 V

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Mounting rail armament

2 mounting rails

Rail width

35 mm

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Resources

Brochures

[eaton-xeffect-sasy60i-customer-success-story-css-wagner-mueller-en-us.pdf](#)

Catalogs

Product Range Catalog Switching and protecting motors

[eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf](#)

Certification reports

[DA-DC-00004244.pdf](#)

[DA-DC-00004109.pdf](#)

[DA-DC-00004108.pdf](#)

[DA-DC-00004554.pdf](#)

[DA-DC-00004245.pdf](#)

[eaton-xeffect-sasy-60i-declaration-of-conformity.pdf](#)

[DA-DC-00004624.pdf](#)

[DA-DC-00004637.pdf](#)

[DA-DC-00004246.pdf](#)

Declarations of conformity

[DA-DC-00004945.pdf](#)

[DA-DC-00004892.pdf](#)

[DA-DC-00004890.pdf](#)

[DA-DC-00004886.pdf](#)

[DA-DC-00004878.pdf](#)

[DA-DC-00004910.pdf](#)

[DA-DC-00004915.pdf](#)

[DA-DC-00004962.pdf](#)

[DA-DC-00004944.pdf](#)

[DA-DC-00004937.pdf](#)

[DA-DC-00004920.pdf](#)

[DA-DC-00004891.pdf](#)

[DA-DC-00004950.pdf](#)

[DA-DC-00004921.pdf](#)

Drawings

[eaton-manual-motor-starters-bba-busbar-adapter-dimensions-002.eps](#)

[eaton-manual-motor-starters-bba-busbar-adapter-3-d-drawing.eps](#)

eCAD model

[ETN.BBA0C-16](#)

Special features

Terminal capacity: 2.5 mm² (AWG 14)

Rated operation current (I_e)

16 A

Ambient operating temperature - max

55 °C

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Static heat dissipation, non-current-dependent P_{vs}

0 W

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Voltage rating (UL CSA 13)

600 V AC, UL/CSA

Ambient operating temperature - min

-25 °C

Busbar thickness - max

10 mm

Type

Busbar adapter

SASY Busbar system 60

mm

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Installation instructions

IL03402015Z

mCAD model

bba0_32.stp

eaton-bba0c-16-drawing.dwg

bba0_32

eaton-bba0c-16-3d-model.stp

bba0_25

bba0_25.stp

Busbar distance

60 mm

Electric connection type

Round conductor

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Heat dissipation per pole, current-dependent P_{vid}

0 W

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Adapter width

45 mm



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)