Select your language

- German
- English
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norw egian Bokmål

Worldwide English



Powering Business Worldwide

EMS2-XBR-T-3 - Three-phase current connector with plug, Pole 3, Devices 3, For use with EMS2-D..., EMS2-D..., EMS2-R..., EMS2-R..., EMS2-R..., EMS2-R...



197177 EVS2-XBR-T-3

Overview Specifications Resources



197177 EMS2-XBR-T-3

Three-phase current connector with plug, Pole 3, Devices 3, For use with EVS2-D..., EVS2-D..., EVS2-D..., EVS2-R..., EVS2-R...

Alternate Catalog No.

EVS2-XBR-T-3

Three-phase current connector, Product range: Electronic motor starter, Accessories, Description: Three-phase current connector with plug, Pole: 3, Devices: 3, For use with: EVS2-D..., EVS2-D..., EVS2-R..., EVS2-R..., EVS2-R..., EVS2-R..., EVS2-R..., EVS2-R..., EVS2-R..., EVS2-R..., EVS2-R...

- Delivery program
- Technical data

Design verification as per IEC/EN 61439

- Technical data ETIM 7.0
- Approvals

Delivery program

Product range

Bectronic motor starter

Basic function

Accessories

Description

Three-phase current connector with plug

Pole

3

Devices

3 Number

For use with

∃VS2-D...

EVS2-D...-SWD...

EMS-R...

EVS2-R...-SWD...

Conductor cross-section

2.5 mm²

Technical data

General

Ambient temperature

-25 - +70

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [In]

25 A

Static heat dissipation, non-current-dependent $[P_{vs}]$

0 W

Heat dissipation capacity [Pdiss]

0 W

Operating ambient temperature min.

-25°C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat Weets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEVBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for electronic motor control and protection device (EC002615)

Bectric engineering, automation, process control engineering / Low-voltage switch technology / Bectronic motor control and motor protection device / Bectronic motor control and motor protection unit (accessories) (ecl@ss10.0.1-27-37-08-92 [ACC035011])

Type of accessory

Connecting cable

Approvals

Product Standards

UL 60947-4-1; CSA C22.2 No. 60947-4-1-14; CE marking

UL File No.

E338590

UL Category Control No.

NLDX, NLDX7

CSA File No.

UL report applies to both US and Canada North America Certification UL listed, certified by UL for use in Canada Specially designed for North America No

CAD data

- Product-specific CAD data (Web)
- 3D Preview (Web)
- DA-CD-ems2_xbr_t_3
 CAD data
 DWG files
 (Web)
- DA-CE-ETN.EVS2-XBR-T-3
 CAD data
 edz files
 (Web)
- DA-CS-ems2_xbr_t_3
 CAD data
 Step files
 (Web)

Product photo



3D drawing



Instruction Leaflet

- BVS2 Electronic Motorstarter (IL034064ZU) Instruction Leaflet (PDF, 07/2019, Language independent)
 Elektronic Motorstarter EVS2, SWD type (IL120004ZU)
- Elektronic Motorstarter EVS2, SWD type (IL120004ZU Instruction Leaflet (PDF, 07/2019, Language independent)

Declaration of Conformity

- DA-DC-00003279
 Declaration of Conformity (PDF)
- DA-DC-00003280
 Declaration of Conformity (PDF)

Download-Center

- Download-Center (this item)
 Eaton EVEA Download-Center download data for this item
- Dow nload-Center

Eaton EVEA Download-Center

Generate data sheet in PDF format X Generate data sheet in Excel format

Write a comment

Imprint Privacy Policy Legal Disclaimer Terms and Conditions
© 2020 by Eaton Industries GmbH