



**197903**  
**DILH600/22(RDC48)**

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per IEC/EN 61439](#)

[Technical data ETIM8.0](#)

[Approvals](#)

[Characteristics](#)

[Dimensions](#)

## DELIVERY PROGRAM

Product range  
Contactors

Application  
Mains contactors for resistive loads from 1000 A

Subrange  
AC-1 contactors greater than 1000 A

Utilization category  
AC-1: Non-inductive or slightly inductive loads, resistance furnaces

Connection technique  
Screw connection

### Rated operational current

AC-1  
Conventional free air thermal current, 3 pole, 50 - 60 Hz

Open  
at 40 °C [ $I_{th}=I_e$ ]  
850 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
600 A

AC-1  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]  
1738 A

Contact sequence



For use with  
DILH800-XH1...


Actuating voltage  
RDC 48: 24 - 48 V DC

Voltage AC/DC  
DC operation

## Auxiliary contacts

possible variants at auxiliary contact module fitting  
options  
sidewise: 2 x DILH800-XH11(V)-SI; 2 x DILH800-  
XH11-SA

Side mounting auxiliary contacts



## Instructions

Interlocked opposing contacts according to IEC/EN  
60947-5-1 Appendix L, inside the auxiliary contact  
module

Auxiliary contacts used as mirror contacts  
according to IEC/EN 60947-4-1 Appendix F (not  
NC late open)

integrated suppressor circuit in actuating electronics  
660 V, 690 V or 1000 V: not directly reversing

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947, VDE 0660, UL, CSA, CCC

Lifespan, mechanical  
AC operated [Operations]  
 $3 \times 10^6$

Lifespan, mechanical  
DC operated [Operations]  
 $3 \times 10^6$

Operating frequency, mechanical  
AC operated [Operations/h]  
1000


Operating frequency, mechanical  
DC operated [Operations/h]  
1000

Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Open  
 $-40 - +70 \text{ } ^\circ\text{C}$

Ambient temperature  
Storage  
 $-40 - +80 \text{ } ^\circ\text{C}$

Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Main contacts  
N/O contact  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/O contact  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/C contact  
8 g

Degree of Protection  
IP00

Altitude  
Max. 2000 m

Weight  
9.5 kg

Terminal capacity main cable  
Flexible with cable lug  
50 - 240 mm<sup>2</sup>

Terminal capacity main cable  
Stranded with cable lug  
70 - 240 mm<sup>2</sup>

Terminal capacity main cable  
Busbar [Width]  
50 mm

Main cable connection screw/bolt  
M10

Tightening torque  
24 Nm

Terminal capacity control circuit cables  
Solid

1 x (0.75 - 2.5)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Terminal capacity control circuit cables  
Flexible with ferrule  
1 x (0.75 - 2.5)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Terminal capacity control circuit cables  
Solid or stranded  
18 - 14 AWG

Stripping length  
10 mm

Control circuit cable connection screw/bolt  
M3.5

Tightening torque  
1.2 Nm

Tool  
Main cable  
Width across flats  
16 mm

Tool  
Control circuit cables  
Pozidriv screwdriver  
2 Size

Tool  
Control circuit cables  
Standard screw driver  
0.8 x 5.5/1 x 6 mm

## Main conducting paths

Rated impulse withstand voltage [ $U_{imp}$ ]  
12000 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [ $U_i$ ]  
1000 V AC

Rated operational voltage [U<sub>e</sub>]  
1000 V AC

Safe isolation to EN 61140  
between coil and contacts  
1000 V AC

Safe isolation to EN 61140  
between the contacts  
1000 V AC

Making capacity (p.f. to IEC/EN 60947)  
6000 A

Breaking capacity  
220 V 230 V  
4800 A

Breaking capacity  
380 V 400 V  
4800 A

Breaking capacity  
500 V  
4800 A

Breaking capacity  
660 V 690 V  
2000 A

Breaking capacity  
1000 V  
1575 A

Short-circuit rating  
Short-circuit protection maximum fuse  
AC-1  
400 V [aR 500 V]  
1260 (2 x 630) A

Short-circuit rating  
Short-circuit protection maximum fuse  
AC-1  
690 V [aR 690 V]  
1260 (2 x 630) A

Short-circuit rating

Short-circuit protection maximum fuse  
AC-1  
1000 V [aR 1000 V]  
1260 (2 x 630) A

## AC

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [ $I_{th} = I_e$ ]  
850 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 50 °C [ $I_{th} = I_e$ ]  
760 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 55 °C [ $I_{th} = I_e$ ]  
725 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 60 °C [ $I_{th} = I_e$ ]  
695 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
600 A

AC-1  
Rated operational current  
Conventional free air thermal current, 1 pole  
Note  
at maximum permissible ambient air temperature

AC-1

Rated operational current  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]  
1738 A

### Current heat loss

3 pole, at  $I_{th}$  (60°)  
37.3 W

Current heat loss at  $I_e$  to AC-3/400 V  
0.026 W

### Magnet systems

Voltage tolerance  
 $U_S$   
24 - 48 V DC

Voltage tolerance  
DC operated [Flick-up]  
 $0.7 \times U_{S \min} - 1.15 \times U_{S \max}$

Voltage tolerance  
DC operated [Drop-out]  
 $0.2 \times U_{S \max} - 0.6 \times U_{S \min}$

Power consumption of the coil in a cold state and  
 $1.0 \times U_S$   
Note on power consumption  
Control transformer with  $u_k \leq 7\%$

Power consumption of the coil in a cold state and  
 $1.0 \times U_S$   
Pull-in power [Flick-up]  
480 W

Power consumption of the coil in a cold state and  
 $1.0 \times U_S$   
Sealing power [Sealing]  
6.4 W

Duty factor  
100 % DF

Changeover time at 100 %  $U_S$  (recommended  
value)



Main contacts  
Closing delay  
80 ms

Changeover time at 100 %  $U_S$  (recommended value)  
Main contacts  
Opening delay  
110 ms

Behaviour in marginal and transitional conditions  
Sealing  
Voltage interruptions  
(0 ... 0.2 x  $U_{c,min}$ )  $\square$  10 ms  
Time is bridged specifically

Behaviour in marginal and transitional conditions  
Sealing  
Voltage interruptions  
(0 ... 0.2 x  $U_{c,min}$ ) > 10 ms  
Contactor drop-out

Behaviour in marginal and transitional conditions  
Sealing  
Voltage drops  
(0.2 ... 0.6 x  $U_{c,min}$ )  $\square$  12 ms  
Time is bridged specifically

Behaviour in marginal and transitional conditions  
Sealing  
Voltage drops  
(0.2 ... 0.6 x  $U_{c,min}$ ) > 12 ms  
Contactor drop-out

Behaviour in marginal and transitional conditions  
Sealing  
Voltage drops  
(0.6 ... 0.7 x  $U_{c,min}$ )  
Contactor remains switched on

Behaviour in marginal and transitional conditions  
Sealing  
Excess voltage  
(1.15 ... 1.3 x  $U_{c,max}$ )  
Contactor remains switched on

Behaviour in marginal and transitional conditions  
Sealing  
Flick-up phase  
(0 ... 0.7 x  $U_{c,min}$ )  
Contactor does not switch on

Behaviour in marginal and transitional conditions

Sealing

Pick-up phase

$(0.7 \times U_{c\min} \dots 1.15 \times U_{c\max})$

Contactors switches on properly

Admissible transitional contact resistance (of the external control circuit device when actuating A11)

□ 500 mΩ

PLC signal level (A3 - A4) to IEC/EN 61131-2 (type 2)

High

15 V

PLC signal level (A3 - A4) to IEC/EN 61131-2 (type 2)

Low

5 V

## Electromagnetic compatibility (EMC)

Electromagnetic compatibility

This product has been designed for use in the industrial sector (Environment A). Use in the residential area (Environment B) can produce radio interference, therefore additional interference suppression measures must be provided.

## Rating data for approved types

Auxiliary contacts

Flot Duty

AC operated

A600

Auxiliary contacts

Flot Duty

DC operated

P300

Auxiliary contacts

General Use

AC

600 V

Auxiliary contacts

General Use

AC

6 A

Auxiliary contacts  
General Use  
DC  
250 V

Auxiliary contacts  
General Use  
DC  
1 A

Special Purpose Ratings  
Resistance Air Heating  
480V 60Hz 3phase, 277V 60Hz 1phase  
700 A

Special Purpose Ratings  
Resistance Air Heating  
600V 60Hz 3phase, 347V 60Hz 1phase  
700 A

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_n$ ]  
650 A

Equipment heat dissipation, current-dependent  
[ $P_{id}$ ]  
0 W

Static heat dissipation, non-current-dependent [ $P_{is}$ ]  
6.4 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-40 °C

Operating ambient temperature max.

+70 °C

## IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

# TECHNICAL DATA ETIM 8.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage  $U_s$  at AC 50HZ  
0 - 0 V

Rated control supply voltage  $U_s$  at AC 60HZ  
0 - 0 V

Rated control supply voltage  $U_s$  at DC  
24 - 48 V

Voltage type for actuating  
DC

Rated operation current  $I_e$  at AC-1, 400 V  
850 A

Rated operation current  $I_e$  at AC-3, 400 V  
0 A

Rated operation power at AC-3, 400 V  
0 kW

Rated operation current  $I_e$  at AC-4, 400 V  
0 A

Rated operation power at AC-4, 400 V  
0 kW

Rated operation power NEVA  
0 kW

Modular version  
No

Number of auxiliary contacts as normally open contact  
2

Number of auxiliary contacts as normally closed contact  
2

Type of electrical connection of main circuit  
Rail connection

Number of normally closed contacts as main contact  
0

Number of normally open contacts as main contact  
3

## APPROVALS

Product Standards  
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No. 60947-4-1-14; CE marking

UL File No.  
E29096

UL Category Control No.  
NLDX

CSA File No.  
012528


CSA Class No.  
3211-04

North America Certification  
UL listed, CSA certified

Specially designed for North America  
No

## CHARACTERISTICS

### Side mounting auxiliary contacts



possible variants at auxiliary contact module fitting options


sidewise: 2 x DILH800-XH11(V)-S; 2 x DILH800-XH11-SA

### Characteristic curve



Electrical lifespan AC-1

### Characteristic curve



Short-time loading, 3-pole

Time interval between two loading cycles: 15 minutes

## DIMENSIONS





[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)