



276399

DILA-22(230V50HZ,240V60HZ)

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Characteristics

Dimensions

## DELIVERY PROGRAM

Product range  
DILA relays

Application  
Contactor relays

Description  
Basic devices with positive operation contacts

Connection technique  
Screw terminals

### Rated operational current

AC-15  
220 V 230 V 240 V [I<sub>e</sub>]  
4 A


AC-15  
380 V 400 V 415 V [I<sub>e</sub>]  
4 A

## Contacts

NO = Normally open  
2 NO

NC = Normally closed  
2 NC

Contact sequence



## Instructions

Contact numbers to EN 50011  
Coil terminal markings to EN 50005

## Code number and version of combination

Distinctive number  
22E

Can be combined with auxiliary contact module  
DILA-XHI(V)...

Actuating voltage  
230 V 50 Hz, 240 V 60 Hz

Voltage AC/DC  
AC operation

Connection to SmartWire-DT  
no

## Instructions

Contact numbers to EN 50011  
Coil terminal markings to EN 50005

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

Lifespan, mechanical  
AC operated [Operations]  
 $20 \times 10^6$

Maximum operating frequency [Operations/h]  
9000


Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Open  
-25 - +60 °C

Ambient temperature  
Enclosed  
- 25 - 40 °C

Ambient temperature  
Ambient temperature, storage  
- 40 - 80 °C

Mounting position  
Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Basic unit with auxiliary contact module  
N/O contact  
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Basic unit with auxiliary contact module  
N/C contact  
5 g

Degree of Protection  
IP20

Protection against direct contact when actuated  
from front (EN 50274)  
Finger and back-of-hand proof

Altitude  
Max. 2000 m

Weight  
AC operated  
0.24 kg

Terminal capacities  
Screw terminals  
Solid  
1 x (0,75 - 4)  
2 x (0,75 - 2,5) mm<sup>2</sup>

Terminal capacities  
Screw terminals  
Flexible with ferrule  
1 x (0.75 - 2.5)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Terminal capacities  
Screw terminals  
Solid or stranded  
18 - 14 AWG

Terminal capacities  
Screw terminals  
Stripping length  
10 mm

Terminal capacities  
Screw terminals  
Terminal screw  
M3.5

Terminal capacities  
Screw terminals  
Poizidriv screw driver  
2 Size

Terminal capacities  
Screw terminals  
Standard screw driver  
0.8 x 5.5  
1 x 6 mm

Terminal capacities  
Screw terminals  
Max. tightening torque  
1.2 Nm

Terminal capacities  
Spring-loaded terminals  
Stripping length  
10 mm

## Contacts

Positive operating contacts to ZH 1/457, including  
auxiliary contact module  
Yes

Rated impulse withstand voltage [ $U_{imp}$ ]  
6000 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [ $U_i$ ]  
690 V AC

Rated operational voltage [ $U_e$ ]  
690 V AC

Safe isolation to EN 61140  
between coil and auxiliary contacts  
400 V AC

Safe isolation to EN 61140  
between the auxiliary contacts  
400 V AC

Rated operational current  
Conventional free air thermal current, 1 pole  
Open  
at 60 °C [ $I_{th} = I_e$ ]  
16 A

Rated operational current  
AC-15  
220 V 230 V 240 V [ $I_e$ ]  
4 A

Rated operational current  
AC-15  
380 V 400 V 415 V [I<sub>e</sub>]  
4 A

Rated operational current  
AC-15  
500 V [I<sub>e</sub>]  
1.5 A

Rated operational current  
DC current  
Notes  
Switch-on and switch-off conditions based on  
DC-13, time constant as specified.

Rated operational current  
DC current  
DC L/R □ 15 ms  
Contacts in series:  
1 [24 V]  
10 A

Rated operational current  
DC current  
DC L/R □ 15 ms  
Contacts in series:  
1 [60 V]  
6 A

Rated operational current  
DC current  
DC L/R □ 15 ms  
Contacts in series:  
2 [60 V]  
10 A

Rated operational current  
DC current  
DC L/R □ 15 ms  
Contacts in series:  
1 [110 V]  
3 A

Rated operational current  
DC current  
DC L/R □ 15 ms  
Contacts in series:  
3 [110 V]  
6 A

Rated operational current

DC current  
DC L/R  $\square$  15 ms  
Contacts in series:  
1 [220 V]  
1 A

Rated operational current  
DC current  
DC L/R  $\square$  15 ms  
Contacts in series:  
3 [220 V]  
5 A

Rated operational current  
DC current  
DC L/R  $\square$  50 ms  
Contacts in series:  
3 [24 V]  
4 A

Rated operational current  
DC current  
DC L/R  $\square$  50 ms  
Contacts in series:  
3 [60 V]  
4 A

Rated operational current  
DC current  
DC L/R  $\square$  50 ms  
Contacts in series:  
3 [110 V]  
2 A

Rated operational current  
DC current  
DC L/R  $\square$  50 ms  
Contacts in series:  
3 [220 V]  
1 A

Rated operational current  
Control circuit reliability [Failure rate]  
 $<10^{-8}$ , < one failure at 100 million operations  
(at  $U_e = 24$  V DC,  $U_{min} = 17$  V,  $I_{min} = 5.4$  mA)  $\lambda$

Short-circuit rating without welding  
Maximum overcurrent protective device  
220 V 230 V 240 V  
4 FKZM0

Short-circuit rating without welding  
Maximum overcurrent protective device

380 V 400 V 415 V  
4 FKZMD

Short-circuit rating without welding  
Short-circuit protection maximum fuse  
500 V  
10 A gG/gL

Current heat loss at  $I_{th}$   
AC operated  
0.53 W

## Magnet systems

Voltage tolerance  
AC operated  
Single-voltage coil 50 Hz and dual-voltage coil 50  
Hz, 60 Hz [Pick-up]  
0.8 - 1.1 x  $U_c$

Power consumption  
AC operation  
Single-voltage coil 50 Hz and dual-voltage coil 50  
Hz, 60 Hz [Pick-up]  
24 VA

Power consumption  
AC operation  
Single-voltage coil 50 Hz and dual-voltage coil 50  
Hz, 60 Hz [Sealing]  
3.4 VA

Power consumption  
AC operation  
Single-voltage coil 50 Hz and dual-voltage coil 50  
Hz, 60 Hz [Sealing]  
1.4 W

duty factor  
100 % DF

Changeover time at 100 %  $U_S$  (recommended  
value)  
AC operated closing delay  
15 - 21 ms

Changeover time at 100 %  $U_S$  (recommended  
value)  
AC operated NO contact opening delay  
9 - 18 ms



## Rating data for approved types

Auxiliary contacts  
Pilot Duty  
AC operated  
A600

Auxiliary contacts  
Pilot Duty  
DC operated  
P300

Auxiliary contacts  
General Use  
AC  
600 V

Auxiliary contacts  
General Use  
AC  
15 A

Auxiliary contacts  
General Use  
DC  
250 V

Auxiliary contacts  
General Use  
DC  
1 A

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_r$ ]  
15.5 A

Heat dissipation per pole, current-dependent [ $P_{rd}$ ]  
0.5 W

Equipment heat dissipation, current-dependent

[P<sub>vid</sub>]  
0 W

Static heat dissipation, non-current-dependent [P<sub>vs</sub>]  
1.4 W

Heat dissipation capacity [P<sub>diss</sub>]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+60 °C

### IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2 Strength of materials and parts

##### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9 Insulation properties

##### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9 Insulation properties

##### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9 Insulation properties

##### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Contactor relay (EC000196)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Contactor relay (ecl@ss10.0.1-27-37-10-01 [AAB716014])

Rated control supply voltage  $U_s$  at AC 50HZ  
230 - 230 V

Rated control supply voltage  $U_s$  at AC 60HZ  
240 - 240 V

Rated control supply voltage  $U_s$  at DC  
0 - 0 V

Voltage type for actuating  
AC

Rated operation current  $I_e$ , 400 V  
4 A

Connection type auxiliary circuit  
Screw connection

Mounting method  
DIN-rail/screw

Interface  
No

Number of auxiliary contacts as normally closed  
contact  
2

Number of auxiliary contacts as normally open  
contact  
2

Number of auxiliary contacts as normally closed  
contact, delayed switching  
0

Number of auxiliary contacts as normally open  
contact, leading  
0

With LED indication  
No

Number of auxiliary contacts as change-over  
contact  
0

Manual operation possible  
No

## APPROVALS

Product Standards  
IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05;  
CE marking

UL File No.  
E29184

UL Category Control No.  
NKCR


CSA File No.  
012528

CSA Class No.  
3211-03

North America Certification  
UL listed, CSA certified

Specially designed for North America  
No


## CHARACTERISTICS



Accessories


- 1: Suppressor
- 2: Auxiliary contact module

Characteristic curve



Component lifespan (operations)  
 $I_b$  = rated operational current

Characteristic curve



Component lifespan (operations)  
 $I_b$  = rated operational current  
Three contacts in series

## DIMENSIONS

Contactor with auxiliary contact module

