

**DILE MINI CONTACTOR RELAY**  
**051778**



Overview



Specifications



Resources

How to buy




Photo is representative




Photo is representative

051778

Eaton Moeller® series DILER Contactor relay, 380V  
Normally open: 2 N/O, N/C = Normally closed: 2 N/C  
operation

How to buy




Photo is representative




Photo is representative



## GENERAL SPECIFICATIONS

General specifications



**PRODUCT NAME**

Eaton Moeller® series DILER Control Relay

**CATALOG NUMBER**

051778

Product specifications



**MODEL CODE**

DILER-22(380V50HZ,440V60HZ)

**EAN**

4015080517788

**PRODUCT LENGTH/DEPTH**

52 mm

**PRODUCT HEIGHT**

58 mm

**PRODUCT WIDTH**

45 mm

<b>PRODUCT WEIGHT</b>	0.17 kg
<b>CERTIFICATIONS</b>	CE UL File No.: E29184 CSA-C22.2 No. 14-05 EN 60947-5-1 UL 508 CSA CSA File No.: 012528 UL Category Control No.: NKCR CSA Class No.: 3211-03 IEC/EN 60947 IEC/EN 60947-4-1 UL VDE 0660

## PRODUCT SPECIFICATIONS

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	6 A
<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	1 x (0.75 - 1.5) mm <sup>2</sup> 2 x (0.75 - 1.5) mm <sup>2</sup>
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications must be observed.
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN</b>	380 V
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>MOUNTING METHOD</b>	DIN-rail/screw
<b>OPERATING VOLTAGE AT DC - MAX</b>	220 VDC
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>FITTED WITH:</b>	Interlocked opposing contacts
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX</b>	380 V
<b>OPERATING VOLTAGE AT DC - MIN</b>	24 VDC
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	50 °C
<b>FEATURES</b>	Positive operating contacts to EN 60947-5-1 appendix auxiliary contact module
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to

<b>APPLICATION</b>	Contactor relays
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V</b>	3 A
<b>OPERATING FREQUENCY</b>	9000 Operations/h
<b>VOLTAGE TYPE</b>	AC
<b>PRODUCT CATEGORY</b>	DILER Mini-contactors
<b>POWER CONSUMPTION, PICK-UP, 50 HZ</b>	25 VA, AC, Single-frequency coil 50 Hz and Dual-f Hz
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>CONNECTION TYPE (AUXILIARY CIRCUIT)</b>	Screw connection
<b>SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING</b>	6 A gG/gL, 500 V, Max. Fuse, Contacts
<b>SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MIN</b>	8 ms
<b>OPERATING VOLTAGE AT AC, 60 HZ - MAX</b>	500 V
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	18 - 14 2 x (18 - 14) 1 x (18 - 14)
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>DEGREE OF PROTECTION</b>	IP20
<b>OVERVOLTAGE CATEGORY</b>	III
<b>SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX</b>	18 ms
<b>VOLTAGE TYPE OF OPERATING VOLTAGE</b>	AC/DC
<b>POLLUTION DEGREE</b>	3
<b>POWER CONSUMPTION, PICK-UP, 60 HZ</b>	25 VA, AC, Single-frequency coil 50 Hz and Dual-f Hz
<b>SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX</b>	21 ms
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	6000 V AC
<b>OPERATING VOLTAGE AT AC, 60 HZ - MIN</b>	17 V
<b>TIGHTENING TORQUE</b>	1.2 Nm, Screw terminals
<b>SWITCHING TIME (AC OPERATED, N/O, WITH AUXILIARY CONTACT MODULE, CLOSING DELAY)</b>	45 ms
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.

<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	2
<b>SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MIN</b>	14 ms
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>	2
<b>SHOCK RESISTANCE</b>	8 g, N/C auxiliary contact, Basic unit with auxiliary Mechanical, according to IEC/EN 60068-2-27, Half ms 10 g, N/O auxiliary contact, Basic unit with auxiliary Mechanical, according to IEC/EN 60068-2-27, Half ms
<b>POWER CONSUMPTION, SEALING, 60 HZ</b>	1.3 W, AC, Single-frequency coil 50 Hz and Dual-f Hz
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	25 °C
<b>OPERATING VOLTAGE AT AC, 50 HZ - MAX</b>	500 V
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications must be observed.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS, DELAYED SWITCHING)</b>	0
<b>STRIPPING LENGTH (MAIN CABLE)</b>	8 mm
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN</b>	0 V
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>SCREW SIZE</b>	M3.5, Terminal screw
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS, LEADING)</b>	0
<b>PROTECTION</b>	Finger and back-of-hand proof Protection against dirt actuated from front (EN 50274)
<b>POWER CONSUMPTION, SEALING, 50 HZ</b>	4.6 VA, AC, Single-frequency coil 50 Hz and Dual-f Hz 1.3 W, AC, Single-frequency coil 50 Hz and Dual-f Hz
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>CODE NUMBER</b>	22E
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	1.8 W
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V</b>	1.5 A

<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX</b>	0 V
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be grounded.
<b>SAFE ISOLATION</b>	300 V AC, Between auxiliary contacts, According to IEC 60439-1 300 V AC, Between coil and auxiliary contacts, According to IEC 60439-1
<b>OPERATING VOLTAGE AT AC, 50 HZ - MIN</b>	17 V
<b>MOUNTING POSITION</b>	As required (except vertical with terminals A1/A2 at the top)
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V</b>	6 A
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the instructions in the instruction leaflet (IL) is observed.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	2
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0.4 W
<b>ACTUATING VOLTAGE</b>	380 V 50 Hz, 440 V 60 Hz
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)</b>	10 A, 600 V AC, (UL/CSA) 0.5 A, 250 V DC, (UL/CSA)
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>RATED SWITCH CURRENT</b>	10 A
<b>RATED OPERATIONAL CURRENT (IE)</b>	2.5 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in parallel) 1.5 A at 110 V, DC L/R ≤ 15 ms (with 3 contacts in parallel) 2.5 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in parallel) 0.5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in parallel) 10 A
<b>PICK-UP VOLTAGE</b>	0.85 - 1.1 V AC x U <sub>c</sub> (voltage tolerance - dual frequency) 0.8 - 1.1 V AC x U <sub>c</sub> (voltage tolerance - single-voltage) dual-voltage coil 50 Hz, 60 Hz
<b>TERMINAL CAPACITY (SOLID)</b>	1 x (0.75 - 2.5) mm <sup>2</sup> 2 x (0.75 - 2.5) mm <sup>2</sup>
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b>	2
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>LIFESPAN, MECHANICAL</b>	10,000,000 Operations (AC operated)

<b>CONTROL CIRCUIT RELIABILITY</b>	< 2 λ, < 1 failure at 100,000,000 Operations (at U <sub>e</sub> = 17 V, I <sub>min</sub> = 5.4 mA)
<b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	600 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN</b>	440 V
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature. Eaton will provide heat dissipation data for the device.
<b>CONVENTIONAL THERMAL CURRENT ITH AT 50°C (3-POLE, OPEN)</b>	10 A
<b>SCREWDRIVER SIZE</b>	0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
<b>DUTY FACTOR</b>	100 %
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX</b>	440 V
<b>SHORT-CIRCUIT PROTECTION RATING</b>	10 A fast, 500V, Maximum fuse, Short-circuit rating for Contacts
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)</b>	P300, DC operated (UL/CSA) A600, AC operated (UL/CSA)
<b>RATED INSULATION VOLTAGE (UI)</b>	690 V

Catalogs

Characteristic curve

Declarations of conformity

Drawings

eCAD model

Installation instructions

mCAD model

---

## System overview

---

## Wiring diagrams

---

051778



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.