

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



VGDILE415 - Varistor suppressor, 415VAC, for DILE, screw connection



010463 VGDILE415

[Overview](#) [Specifications](#) [Resources](#)



010463 VGDILE415

Varistor suppressor, 415VAC, for DILE, screw connection

Alternate Catalog No.

XTMCXV/SN

EL-Nummer (Norway)

4130399

Varistor suppressor circuit, Accessories: Suppressor circuit, Description: Varistor suppressor, Actuating voltage: U_s 380 - 415 AC V, For use with: DILE..

- Delivery program
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Approvals
- Dimensions

Delivery program

Accessories

Suppressor circuit


Description

Varistor suppressor

Actuating voltage [U_s]

380 - 415 AC V

Contact sequence



For use with

DILE..

Instructions

For AC operation contactors 50 - 60 Hz.

The suppressor is fitted as standard in DC operated contactor relays.

Note drop-out delay

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_r]

0 A

Heat dissipation per pole, current-dependent [P_{id}]

0 W
Equipment heat dissipation, current-dependent [P_{id}]
0 W
Static heat dissipation, non-current-dependent [P_{s}]
0 W
Heat dissipation capacity [P_{diss}]
0 W
Operating ambient temperature min.
-25 °C
Operating ambient temperature max.
+50 °C
IEC/EN 61439 design verification
10.2 Strength of materials and parts 10.2.2 Corrosion resistance
Meets the product standard's requirements.
10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.
10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.
10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.
10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.
10.2 Strength of materials and parts 10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.
10.2 Strength of materials and parts 10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.
10.2 Strength of materials and parts 10.2.7 Inscriptions
Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances
Meets the product standard's requirements.
10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.
10.8 Connections for external conductors
Is the panel builder's responsibility.
10.9 Insulation properties 10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.
10.9 Insulation properties 10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.
10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.
10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Surge protection module (EC000683)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) /
Component for protective circuit (ecl@ss10.0.1-27-37-10-10 [AKF019013])
Function
Varistor (voltage-sensitive resistor)
Rated control supply voltage U_s at AC 50Hz
380 - 415 V
Rated control supply voltage U_s at AC 60Hz
380 - 415 V
Rated control supply voltage U_s at DC

0 - 0 V
Voltage type for actuating
AC
With LED indication
No

Approvals

Product Standards
IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking
UL File No.
E29096
UL Category Control No.
NLDX
CSA File No.
012528
CSA Class No.
3211-03
North America Certification
UL listed, CSA certified
Specially designed for North America
No

Dimensions



DILE-... + VGDILE..

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-rcdfile](#)
File
(Web)


edz files

- [DA-CE-ETN.VGDILE415](#)
File
(Web)

Step files

- [DA-CS-rcdfile](#)
File
(Web)

Wiring diagram



250S023

Line drawing
Varistor suppressor

3D drawing



2501008

Line drawing

Varistor suppression element

Dimensions single product



210X048

Line drawing

Suppressor

Product photo



210A165

Photo

RC suppressor, varistor suppressor

Declaration of Conformity

UK

- [DILE \(DA-DC-00003709\)](#)
Asset
(PDF)

EU

- [DILE EA \(DA-DC-00004065\)](#)
Asset
(PDF)
- [DILE \(DA-DC-00004068\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH