

[United States](#) [Select your location](#)

[Sign in](#)

We make what matters work*

[Products](#) [Digital Services](#) [Markets](#) [Support](#) [Company](#)

Search

[Products](#)

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)

- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)

- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)

- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

[Digital](#)

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

[Services](#)

Close Search

[Markets](#)

Close Search

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)

- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)

- [Vehicles](#)

[Support](#)

Close Search

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

[Company](#)

Close Search

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)

- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)

- [Selling to Eaton](#)

[MyEaton](#)

Close Search

Quick links



DIL contactors
109855

[Overview](#) [Specifications](#) [Resources](#)

How to buy

[Back to search](#)

[Download](#) [Zoom](#)

Download [Zoom](#)

109855

Eaton Moeller® series DILMP Contactor, 4 pole, 63 A, 230 V 50 Hz, 240 V 60 Hz, AC operation

[Add a free sample to the cart](#)

- [WIN-WIN with Push-in Terminals](#)
- [How to improve wiring](#)

×



Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

Keep My Cart

Create a New Cart

×



Item is already in the cart.

Okay

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

- [277950](#)

277950
Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170
- [277946](#)

277946
Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170
- [278425](#)

278425

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM40 - DILM225A, -SI

- [277949](#)

277949

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 3 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [281206](#)

281206

Eaton Moeller® series DILM RC suppressor circuit, 110 - 240 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200

- [083094](#)

083094

Eaton Moeller® series Amplifier module, for separate mounting

- [278427](#)

278427

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM40 - DILM225A

- [281218](#)

281218

Eaton Moeller® series DILM Varistor suppressor circuit, 130 - 240 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200 DILM95-XSPV240

- [283464](#)

283464

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170, XHIA

- [281198](#)

281198

Eaton Moeller® series DILM Interlock, mechanical, for DILM40-65

- [281207](#)

281207

Eaton Moeller® series DILM RC suppressor circuit, 240 - 500 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200

- [207517](#)

207517

Eaton Moeller® series Sheet of labels

- [277948](#)

277948

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 4 N/O, Front fixing, Screw terminals, DILM40 - DILM170

- [277945](#)

277945

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, DILM40 - DILM170

- [277951](#)

277951

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 1 N/O, 3 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [283463](#)

283463

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170, XHIA

- [277952](#)

277952

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 4 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [281192](#)

281192

Eaton Moeller® series DILM Star-point bridge, For use with DILM40 - DILM72, DILMF40 - DILMF65

- [281205](#)

281205

Eaton Moeller® series DILM RC suppressor circuit, 24 - 48 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200

- [281216](#)

281216

Eaton Moeller® series DILM Varistor suppressor circuit, 24 - 48 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200 DILM95-XSPV48

[Go to Previous Item](#)

[Go to Next Item](#)

- [277950](#)

277950

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [277946](#)

277946

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [278425](#)

278425

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM40 - DILM225A, -SI

- [277949](#)

277949

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 3 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [281206](#)

281206

Eaton Moeller® series DILM RC suppressor circuit, 110 - 240 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200

- [083094](#)

083094

Eaton Moeller® series Amplifier module, for separate mounting

- [278427](#)

278427

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM40 - DILM225A

- [281218](#)

281218

Eaton Moeller® series DILM Varistor suppressor circuit, 130 - 240 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200 DILM95-XSPV240

- [283464](#)

283464

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170, XHIA

- [281198](#)

281198

Eaton Moeller® series DILM Interlock, mechanical, for DILM40-65

- [281207](#)

281207

Eaton Moeller® series DILM RC suppressor circuit, 240 - 500 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200

- [207517](#)

207517

Eaton Moeller® series Sheet of labels

- [277948](#)

277948

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 4 N/O, Front fixing, Screw terminals, DILM40 - DILM170

- [277945](#)

277945

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, DILM40 - DILM170

- [277951](#)

277951

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 1 N/O, 3 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [283463](#)

283463

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170, XHIA

- [277952](#)

277952

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 4 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [281192](#)

281192

Eaton Moeller® series DILM Star-point bridge, For use with DILM40 - DILM72, DILMF40 - DILMF65

- [281205](#)

281205

Eaton Moeller® series DILM RC suppressor circuit, 24 - 48 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200

- [281216](#)

281216

Eaton Moeller® series DILM Varistor suppressor circuit, 24 - 48 AC V, For use with: DILM40 - DILM95, DILK33 - DILK50, DILMP63 - DILMP200 DILM95-XSPV48

[View more](#) [View less](#)

-
-

General specifications

Product Name

Eaton Moeller® series DILMP 4-pole contactor

Catalog Number

109855
Model Code
DILMP63(230V50HZ,240V60HZ)
EAN
4015081094233
Product Length/Depth
132 mm
Product Height
115 mm
Product Width
74 mm
Product Weight
1.04 kg
Certifications
CE
UL 60947-4-1
UL Category Control No.: NLDX
CSA File No.: 012528
IEC/EN 60947
CSA-C22.2 No. 60947-4-1-14
UL File No.: E29096
CSA Class No.: 2411-03, 3211-04
CSA
VDE 0660
UL
IEC/EN 60947-4-1
Catalog Notes
Contacts according to EN 50012

Product specifications

Terminal capacity (flexible with ferrule)
1 x (0.75 - 1.5) mm²
2 x (0.75 - 1.5) mm²
Rated operational current for specified heat dissipation (In)
63 A
10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.
Rated operational power at AC-1, 380/400 V, 50 Hz
39 kW
Rated operational power at AC-3, 380/400 V, 50 Hz
18.5 kW
Conventional thermal current ith (3-pole, enclosed)
50 A
Rated operational power at AC-4, 380/400 V, 50 Hz
12 kW
Terminal capacity (copper band)
2 x (6 x 9 x 0.8) mm (Number of segments x width x thickness), Main cables
Rated control supply voltage (Us) at AC, 50 Hz - min
230 V
Conventional thermal current ith at 60°C (3-pole, open)
54 A
10.4 Clearances and creepage distances
Meets the product standard's requirements.
Number of contacts (normally closed) as main contact
0
Short-circuit current rating (high fault at 480 V)
250/150 A, Class J, max Fuse, SCCR (UL/CSA)
30/100 kA, Fuse, SCCR (UL/CSA)
100 A, max. CB, SCCR (UL/CSA)
65 kA, CB, SCCR (UL/CSA)
Conventional thermal current ith at 55°C (3-pole, open)
58 A
Rated operational power (NEMA)
22 kW

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Ambient storage temperature - min

40 °C

Rated breaking capacity at 380/400 V

400 A

Short-circuit current rating (basic rating)

10 kA, SCCR (UL/CSA)

250 A, max. Fuse, SCCR (UL/CSA)

250 A, max. CB, SCCR (UL/CSA)

Rated control supply voltage (Us) at AC, 50 Hz - max

230 V

Rated breaking capacity at 660/690 V

250 A

Rated operational current (Ie) at DC-1, 220 V

63 A

Special purpose rating of elevator control

7.5 HP, 200 V 60 Hz 3-ph, (UL/CSA)

34 A, 480 V 60 Hz 3-ph, (UL/CSA)

25 HP, 480 V 60 Hz 3-ph, (UL/CSA)

32 A, 600 V 60 Hz 3-ph, (UL/CSA)

30 HP, 600 V 60 Hz 3-ph, (UL/CSA)

10 HP, 240 V 60 Hz 3-ph, (UL/CSA)

25.3 A, 200 V 60 Hz 3-ph, (UL/CSA)

28 A, 240 V 60 Hz 3-ph, (UL/CSA)

Ambient operating temperature - max

60 °C

Assigned motor power at 115/120 V, 60 Hz, 1-phase

3 HP

Electrical connection type of main circuit

Screw connection

Number Of Poles

Four-pole

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

Terminal capacity (flexible)

1 x (0.75 - 2.5) mm²

2 x (0.75 - 2.5) mm²

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Application

Contactors for 4 pole electric consumers

Operating frequency

5000 mechanical Operations/h (AC operated)

5000 mechanical Operations/h (DC operated)

Voltage type

AC

Short-circuit protection rating (type 1 coordination) at 400 V

125 A gG/gL

Product category

Contactors

Rated operational power at AC-1, 500 V, 50 Hz

52 kW

Rated operational power at AC-3, 690 V, 50 Hz

23 kW

Power consumption, pick-up, 50 Hz

150 VA, Dual-frequency coil in a cold state and 1.0 x Us

Heat dissipation capacity Pdiss

0 W

Assigned motor power at 460/480 V, 60 Hz, 3-phase

30 HP

Special purpose rating of tungsten incandescent lamps
74 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
74 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
Switching time (AC operated, make contacts, opening delay) - min
8 ms
Rated operational power at AC-3, 240 V, 50 Hz
13.5 kW
Operating voltage at AC, 60 Hz - max
690 V
Terminal capacity (solid/stranded AWG)
18 - 14, Control circuit cables
12 - 2, Main Cables
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.
Degree of protection
IP00
Overvoltage category
III
Rated operational power at AC-1, 440 V, 50 Hz
46 kW
Switching time (AC operated, make contacts, opening delay) - max
13 ms
Ambient storage temperature - max
80 °C
Pollution degree
3
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V
63 A
Power consumption, pick-up, 60 Hz
150 VA, Dual-frequency coil in a cold state and 1.0 x Us
95 W, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz
Switching time (AC operated, make contacts, closing delay) - max
18 ms
Rated impulse withstand voltage (Uimp)
8000 V AC
Connection
Screw terminals
Operating voltage at AC, 60 Hz - min
230 V
Tightening torque
3.3 Nm, Screw terminals, Main cables
1.2 Nm, Screw terminals, Control circuit cables
Conventional thermal current Ith (1-pole, enclosed)
146 A
Rated operational current (Ie) at AC-3, 660 V, 690 V
25 A
10.2.2 Corrosion resistance
Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.
10.2.7 Inscriptions
Meets the product standard's requirements.
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V
40 A
Switching time (AC operated, make contacts, closing delay) - min
12 ms
Short-circuit protection rating (type 2 coordination) at 400 V
63 A gG/gL
Special purpose rating of ballast electrical discharge lamps
79 A (600V 60Hz 3phase, 347V 60Hz 1phase)
79 A (480V 60Hz 3phase, 277V 60Hz 1phase)
Number of auxiliary contacts (normally open contacts)
0
Rated operational power at AC-3, 500 V, 50 Hz
28 kW

Shock resistance

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Rated operational current (Ie) at DC-1, 110 V

63 A

Assigned motor power at 230/240 V, 60 Hz, 3-phase

15 HP

Drop-out voltage

AC operated: 0.6 - 0.4 x UC, AC operated

Power consumption, sealing, 60 Hz

4.1 W, Dual-frequency coil in a cold state and 1.0 x Us

16 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Resistance per pole

1.9 mΩ

Ambient operating temperature (enclosed) - min

25 °C

Stripping length (control circuit cable)

10 mm

Operating voltage at AC, 50 Hz - max

690 V

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Stripping length (main cable)

10 mm

Ambient operating temperature (enclosed) - max

40 °C

Special purpose rating of resistance air heating

79 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

79 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

Rated control supply voltage (Us) at DC - min

0 V

Short-circuit current rating (high fault at 600 V)

30 kA, CB, SCCR (UL/CSA)

250 A, max. CB, SCCR (UL/CSA)

30/100 kA, Fuse, SCCR (UL/CSA)

250/150 A, Class J, max. Fuse, SCCR (UL/CSA)

10.8 Connections for external conductors

Is the panel builder's responsibility.

Number of main contacts (normally open contact)

4

Rated breaking capacity at 220/230 V

400 A

Screw size

M6, Terminal screw, Main cables

M3.5, Terminal screw, Control circuit cables

Rated operational current (Ie) at AC-4, 400 V

25 A

Short-circuit protection rating (type 2 coordination) at 690 V

50 A gG/gL

Assigned motor power at 575/600 V, 60 Hz, 3-phase

40 HP

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Power consumption, sealing, 50 Hz

4.1 W, Dual-frequency coil in a cold state and 1.0 x Us

Rated operational power at AC-3, 440 V, 50 Hz

25 kW

Terminal capacity (stranded)

2 x (16 - 35) mm², Main cables

1 x (16 - 50) mm², Main cables

Rated breaking capacity at 500 V

400 A

Rated operational power at AC-1, 415 V, 50 Hz
43 kW

Rated operational power at AC-3, 415 V, 50 Hz
24 kW

Climatic proofing

Damp heat, constant, to IEC 60068-2-3

Damp heat, cyclic, to IEC 60068-2-30

Connection to SmartWire-DT

No

Static heat dissipation, non-current-dependent Pvs

4.1 W

Rated control supply voltage (Us) at DC - max

0 V

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Utilization category

AC-3: Normal AC induction motors: starting, switch off during running

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

Rated operational current (Ie) at AC-3, 440 V

40 A

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Safe isolation

440 V AC, Between the contacts, According to EN 61140

440 V AC, Between coil and contacts, According to EN 61140

Operating voltage at AC, 50 Hz - min

230 V

Rated operational power at AC-1, 220/230 V, 50 Hz

23 kW

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Heat dissipation per pole, current-dependent Pvid

5.5 W

Actuating voltage

230 V 50 Hz, 240 V 60 Hz

Residual current

1 mA (with actuation of A1 - A2 by the electronics with "0" signal)

Equipment heat dissipation, current-dependent Pvid

16.5 W

Assigned motor power at 200/208 V, 60 Hz, 3-phase

10 HP

Pick-up voltage

0.8 - 1.1 V AC x Uc

0.85 - 1.1 V AC/DC x Us

Conventional thermal current Ith at 40°C (3-pole, open)

63 A

Terminal capacity (solid)

2 x (0.75 - 4) mm², Control circuit cables

2 x (2.5 - 16) mm², Main cables

1 x (0.75 - 4) mm², Control circuit cables

1 x (2.5 - 16) mm², Main cables

1 x (0.75 - 2.5) mm²

Number of auxiliary contacts (normally closed contacts)

0

Rated operational power at AC-1, 240 V, 50 Hz

25 kW

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Lifespan, mechanical

10,000,000 Operations (DC operated)

10,000,000 Operations (AC operated)

Short-circuit protection rating (type 1 coordination) at 690 V
80 A gG/gL
Rated making capacity up to 690 V (cos phi to IEC/EN 60947)
560 A
Rated operational current (Ie) at DC-1, 60 V
63 A
Rated operational voltage (Ue) at AC - max
690 V
Rated control supply voltage (Us) at AC, 60 Hz - min
240 V

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Switching capacity (main contacts, general use)
63 A, Maximum motor rating (UL/CSA)
Conventional thermal current Ith at 50°C (3-pole, open)
60 A
Rated operational current (Ie) at AC-3, 500 V
40 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase
7.5 HP

Screwdriver size
0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver
2, Terminal screw, Pozidriv screwdriver

Duty factor
100 %
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V
40 A


Conventional thermal current Ith of main contacts (1-pole, open)
162 A
Rated control supply voltage (Us) at AC, 60 Hz - max
240 V

Rated operational power at AC-1, 690 V, 50 Hz
68 kW

Rated insulation voltage (Ui)
690 V

Altitude
Max. 2000 m

Serial Number Verified :

Authenticated: 

The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

Catalogs

- [Switching and protecting motors - catalog](#)
- [SmartWire-DT Catalog](#)
- [Product Range Catalog Switching and protecting motors](#)

Characteristic curve

- [eaton-contactors-characteristic-curve-2110dia-3.eps](#)
- [eaton-contactors-switching-dilmp-characteristic-curve.eps](#)

[Download all files](#)

Drawings

- [eaton-contactors-mounting-dilm-dimensions-002.eps](#)
- [eaton-contactors-dilmp-dimensions-002.eps](#)
- [eaton-contactors-mounting-dilm-dimensions.eps](#)
- [eaton-contactors-dilmp-dimensions.eps](#)

[Download all files](#)

eCAD model

- [DA-CE-ETN.DILMP63\(230V50HZ,240V60HZ\)](#)

Installation instructions

- [IL03407049Z](#)

Installation videos

- [WIN-WIN with push-in technology](#)

mCAD model

- [DA-CS-dil_mp63_80](#)
- [DA-CD-dil_mp63_80](#)

Download all files

PEP Eco-passport

- [EATO-00018-V01.01-EN](#)

Wiring diagrams

- [eaton-contactors-contact-dilem-wiring-diagram.eps](#)

Export product specification

-

x



Enter your city, state, or zip code or [Locate me](#)

City, state

Search

Show locations that offer:

- Product pickup
- Order online and ship product

- 109855

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)
- [Policies and statements](#)

- [Terms and conditions](#)
- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

Let's talk big ideas

-
-
-
-

[View all social media](#)

- [Sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

© 2023 Eaton. All Rights Reserved.

[Back to top of the page](#)

Are you sure?

[Cancel](#) [Sign out](#)

Are you sure?

[Cancel](#) [Sign out](#)

[×](#)

[×](#)