

[United States](#) [Select your location](#)

[Sign in](#)

We make what matters work*

[Products](#) [Digital Services](#) [Markets](#) [Support](#) [Company](#)

Search

[Products](#)

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)

- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)

- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)

- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

[Digital](#)

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

[Services](#)

Close Search

[Markets](#)

Close Search

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)

- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)

- [Vehicles](#)

[Support](#)

Close Search

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

[Company](#)

Close Search

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)

- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)

- [Selling to Eaton](#)

[MyEaton](#)

Close Search

Quick links



DIL contactors
109910

[Overview](#) [Specifications](#) [Resources](#)

How to buy

[Back to search](#)

[Download](#) Zoom

Download Zoom

109910

Eaton Moeller® series DILMP Contactor, 4 pole, 125 A, RDC 24: 24 - 27 VDC, DC operation

[Add a free sample to the cart](#)

- [WIN-WIN with Push-in Terminals](#)
- [How to improve wiring](#)

×



Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

Keep My Cart

Create a New Cart

×



Item is already in the cart.

Okay

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

- [277950](#)

277950

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [277946](#)

277946

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [278425](#)

278425

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM40 - DILM225A, -SI

- [277949](#)

277949

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 3 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [240081](#)

240081

Eaton Moeller® series DILM Interlock, mechanical, for DILM80-150 DILM150-XMV

- [083094](#)

083094

Eaton Moeller® series Amplifier module, for separate mounting

- [278427](#)

278427

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM40 - DILM225A

- [284768](#)

284768

Eaton Moeller® series DILM Star-point bridge, For use with DILM80 - DILM170, DILMF80 - DILMF150

- [283464](#)

283464

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170, XHIA

- [207517](#)

207517

Eaton Moeller® series Sheet of labels

- [277948](#)

277948

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 4 N/O, Front fixing, Screw terminals, DILM40 - DILM170

- [277945](#)

277945

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, DILM40 - DILM170

- [277951](#)

277951

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 1 N/O, 3 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [230112](#)

230112

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RAC 240: 190 - 240 V 50/60 Hz, AC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200

- [283463](#)

283463

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170, XHIA

- [277952](#)

277952

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 4 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [277947](#)

277947

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [277953](#)

277953

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 1 N/O, 1 N/OE, 1 NC, 1 NCL, Front fixing, Screw terminals, DILM40 - DILM170

- [230113](#)

230113

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RAC 440: 380 - 440 V 50/60 Hz, AC, For use with: DILM115, DILM150, DILM170

- [230115](#)

230115

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RDC 24: 24 - 27 VDC, DC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200

[Go to Previous Item](#)

[Go to Next Item](#)

- [277950](#)

277950

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [277946](#)

277946

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [278425](#)

278425
Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM40 - DILM225A, -SI
- [277949](#)

277949
Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 3 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170
- [240081](#)

240081
Eaton Moeller® series DILM Interlock, mechanical, for DILM80-150 DILM150-XMV
- [083094](#)

083094
Eaton Moeller® series Amplifier module, for separate mounting
- [278427](#)

278427
Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM40 - DILM225A
- [284768](#)

284768
Eaton Moeller® series DILM Star-point bridge, For use with DILM80 - DILM170, DILMF80 - DILMF150
- [283464](#)

283464
Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170, XHIA
- [207517](#)

207517
Eaton Moeller® series Sheet of labels
- [277948](#)

277948
Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 4 N/O, Front fixing, Screw terminals, DILM40 - DILM170
- [277945](#)

277945
Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 2 N/O, Front fixing, Screw terminals, DILM40 - DILM170
- [277951](#)

277951

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 1 N/O, 3 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [230112](#)

230112

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RAC 240: 190 - 240 V 50/60 Hz, AC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200

- [283463](#)

283463

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILM40 - DILM170, XHIA

- [277952](#)

277952

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 4 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [277947](#)

277947

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 16 A, 2 NC, Front fixing, Screw terminals, DILM40 - DILM170

- [277953](#)

277953

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 1 N/O, 1 N/OE, 1 NC, 1 NCL, Front fixing, Screw terminals, DILM40 - DILM170

- [230113](#)

230113

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RAC 440: 380 - 440 V 50/60 Hz, AC, For use with: DILM115, DILM150, DILM170

- [230115](#)

230115

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RDC 24: 24 - 27 VDC, DC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200

[View more](#) [View less](#)

- [General specifications](#)
- [Product specifications](#)

General specifications

Product Name

Eaton Moeller® series DILMP 4-pole contactor

Catalog Number

109910
Model Code
DILMP125(RDC24)
EAN
4015081094769
Product Length/Depth
160 mm
Product Height
170 mm
Product Width
122 mm
Product Weight
2.73 kg
Certifications
CSA Class No.: 2411-03, 3211-04
VDE 0660
UL
UL File No.: E29096
CE
CSA
IEC/EN 60947-4-1
CSA-C22.2 No. 60947-4-1-14
IEC/EN 60947
UL 60947-4-1
UL Category Control No.: NLDX
CSA File No.: 012528
Catalog Notes
Also tested according to AC-3e.

Product specifications

Terminal capacity (flexible with ferrule)
1 x (0.75 - 1.5) mm²
2 x (0.75 - 1.5) mm²
Rated operational current for specified heat dissipation (In)
125 A
10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.
Rated operational power at AC-1, 380/400 V, 50 Hz
78 kW
Rated operational power at AC-3, 380/400 V, 50 Hz
37 kW
Conventional thermal current ith (3-pole, enclosed)
100 A
Rated operational power at AC-4, 380/400 V, 50 Hz
28 kW
Terminal capacity (copper band)
2 x (6 x 16 x 0.8) mm (Number of segments x width x thickness), Main cables
Rated control supply voltage (Us) at AC, 50 Hz - min
0 V
Conventional thermal current ith at 60°C (3-pole, open)
108 A
10.4 Clearances and creepage distances
Meets the product standard's requirements.
Number of contacts (normally closed) as main contact
0
Short-circuit current rating (high fault at 480 V)
65 kA, CB, SCCR (UL/CSA)
300/300 A, Class J, max Fuse, SCCR (UL/CSA)
250 A, max. CB, SCCR (UL/CSA)
30/100 kA, Fuse, SCCR (UL/CSA)
Conventional thermal current ith at 55°C (3-pole, open)
110 A
Rated operational power (NEMA)
44.7 kW

Operating voltage at DC - max

27 V

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Ambient storage temperature - min

40 °C

Fitted with:

Suppressor circuit in actuating electronics

Rated breaking capacity at 380/400 V

800 A

Short-circuit current rating (basic rating)

600 A, max. CB, SCCR (UL/CSA)

600 A, max. Fuse, SCCR (UL/CSA)

10 kA, SCCR (UL/CSA)

Rated supply voltage (Us) at AC, 50 Hz - max

0 V

Rated breaking capacity at 660/690 V

650 A

Rated operational current (Ie) at DC-1, 220 V

125 A

Special purpose rating of elevator control

60 HP, 600 V 60 Hz 3-ph, (UL/CSA)

68 A, 240 V 60 Hz 3-ph, (UL/CSA)

25 HP, 240 V 60 Hz 3-ph, (UL/CSA)

65 A, 480 V 60 Hz 3-ph, (UL/CSA)

20 HP, 200 V 60 Hz 3-ph, (UL/CSA)

62.1 A, 200 V 60 Hz 3-ph, (UL/CSA)

50 HP, 480 V 60 Hz 3-ph, (UL/CSA)

62 A, 600 V 60 Hz 3-ph, (UL/CSA)

Operating voltage at DC - min

24 V

Ambient operating temperature - max

60 °C

Assigned motor power at 115/120 V, 60 Hz, 1-phase

7.5 HP

Electrical connection type of main circuit

Screw connection

Power consumption (sealing) at DC

1.9 W

Number Of Poles

Four-pole

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

Terminal capacity (flexible)

1 x (0.75 - 2.5) mm²

2 x (0.75 - 2.5) mm²

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Application

Contactors for 4 pole electric consumers

Operating frequency

3600 mechanical Operations/h (AC operated)

3600 mechanical Operations/h (DC operated)

Voltage type

DC

Short-circuit protection rating (type 1 coordination) at 400 V

250 A gG/gL

Product category

Contactors

Rated operational power at AC-1, 500 V, 50 Hz

103 kW

Rated operational power at AC-3, 690 V, 50 Hz
63 kW

Heat dissipation capacity P_{diss}
0 W

Assigned motor power at 460/480 V, 60 Hz, 3-phase
60 HP

Special purpose rating of tungsten incandescent lamps
100 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
100 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

Rated operational power at AC-3, 240 V, 50 Hz
27.5 kW

Operating voltage at AC, 60 Hz - max
690 V

Terminal capacity (solid/stranded AWG)
18 - 14, Control circuit cables
8 - 3/0, Main cables

10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

Degree of protection
IP00

Overvoltage category
III

Rated operational power at AC-1, 440 V, 50 Hz
90 kW

Ambient storage temperature - max
80 °C

Pollution degree
3

Rated operational current (I_e) at AC-1, 380 V, 400 V, 415 V
125 A

Rated impulse withstand voltage (U_{imp})
8000 V AC

Connection
Screw terminals
Operating voltage at AC, 60 Hz - min
230 V

Tightening torque
14 Nm, Screw terminals, Main cables
1.2 Nm, Screw terminals, Control circuit cables

Conventional thermal current I_{th} (1-pole, enclosed)
292 A

Rated operational current (I_e) at AC-3, 660 V, 690 V
65 A

10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2.7 Inscriptions
Meets the product standard's requirements.

Rated operational current (I_e) at AC-3, 380 V, 400 V, 415 V
80 A

Short-circuit protection rating (type 2 coordination) at 400 V
160 A gG/gL

Special purpose rating of ballast electrical discharge lamps
100 A (480V 60Hz 3phase, 277V 60Hz 1phase)
100 A (600V 60Hz 3phase, 347V 60Hz 1phase)

Number of auxiliary contacts (normally open contacts)
0

Rated operational power at AC-3, 500 V, 50 Hz
58 kW

Shock resistance
5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Rated operational current (I_e) at DC-1, 110 V

125 A
Assigned motor power at 230/240 V, 60 Hz, 3-phase
30 HP
Drop-out voltage
0.2 - 0.6 x UC, DC operated
Resistance per pole
0.6 mΩ
Ambient operating temperature (enclosed) - min
25 °C
Stripping length (control circuit cable)
10 mm
Operating voltage at AC, 50 Hz - max
690 V

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Special purpose rating of refrigeration control (CSA only)

420 A, LRA 600 V 60 Hz 3phase; (CSA)

90 A, FLA 480 V 60 Hz 3phase; (CSA)

540 A, LRA 480 V 60 Hz 3phase; (CSA)

70 A, FLA 600 V 60 Hz 3phase; (CSA)

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Stripping length (main cable)

15 mm

Ambient operating temperature (enclosed) - max

40 °C

Special purpose rating of resistance air heating

100 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

110 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

Rated control supply voltage (Us) at DC - min

24 V

Short-circuit current rating (high fault at 600 V)

30 kA, CB, SCCR (UL/CSA)

30/100 kA, Fuse, SCCR (UL/CSA)

300/300 A, Class J, max. Fuse, SCCR (UL/CSA)

350 A, max. CB, SCCR (UL/CSA)

10.8 Connections for external conductors

Is the panel builder's responsibility.

Number of main contacts (normally open contact)

4

Rated breaking capacity at 220/230 V

800 A

Screw size

M10, Terminal screw, Main cables

5 mm AF, Hexagon socket-head spanner, Terminal screw, Main cables

M3.5, Terminal screw, Control circuit cables

Rated operational current (Ie) at AC-4, 400 V

115 A

Short-circuit protection rating (type 2 coordination) at 690 V

160 A gG/gL

Assigned motor power at 575/600 V, 60 Hz, 3-phase

75 HP

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated operational power at AC-3, 440 V, 50 Hz

51 kW

Terminal capacity (stranded)

1 x (16 - 120) mm², Main cables

2 x (16 - 95) mm², Main cables

Rated breaking capacity at 500 V

800 A

Rated operational power at AC-1, 415 V, 50 Hz

85 kW

Rated operational power at AC-3, 415 V, 50 Hz

48 kW

Climatic proofing
Damp heat, constant, to IEC 60068-2-3
Damp heat, cyclic, to IEC 60068-2-30
Connection to SmartWire-DT
No
Static heat dissipation, non-current-dependent Pvs
1.9 W
Rated control supply voltage (Us) at DC - max
27 V
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.
Utilization category
AC-3: Normal AC induction motors: starting, switch off during running
AC-1: Non-inductive or slightly inductive loads, resistance furnaces
Rated operational current (Ie) at AC-3, 440 V
80 A
10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.
Safe isolation
440 V AC, Between coil and contacts, According to EN 61140
440 V AC, Between the contacts, According to EN 61140
Operating voltage at AC, 50 Hz - min
230 V
Rated operational power at AC-1, 220/230 V, 50 Hz
45 kW
10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.
Heat dissipation per pole, current-dependent Pvid
7.4 W
Actuating voltage
RDC 24: 24 - 27 VDC
Switching time (DC operated, make contacts, opening delay) - max
30 ms
Switching time (DC operated, make contacts, closing delay) - max
35 ms
Residual current
1 mA (with actuation of A1 - A2 by the electronics with "0" signal)
Equipment heat dissipation, current-dependent Pvid
22.2 W
Assigned motor power at 200/208 V, 60 Hz, 3-phase
25 HP
Pick-up voltage
0.7 - 1.2 VDC x Uc
0.8 - 1.1 V AC/DC x Us
Conventional thermal current Ith at 40°C (3-pole, open)
125 A
Terminal capacity (solid)
2 x (0.75 - 4) mm², Control circuit cables
1 x (0.75 - 4) mm², Control circuit cables
1 x (0.75 - 2.5) mm²
Number of auxiliary contacts (normally closed contacts)
0
Rated operational power at AC-1, 240 V, 50 Hz
49 kW
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects
Meets the product standard's requirements.
Lifespan, mechanical
10,000,000 Operations (DC operated)
10,000,000 Operations (AC operated)
Short-circuit protection rating (type 1 coordination) at 690 V
200 A gG/gL

Rated making capacity up to 690 V (cos phi to IEC/EN 60947)

1120 A

Rated operational current (Ie) at DC-1, 60 V

125 A

Rated operational voltage (Ue) at AC - max

690 V

Rated control supply voltage (Us) at AC, 60 Hz - min

0 V

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Power consumption (pick-up) at DC

149 W

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Switching capacity (main contacts, general use)

125 A, Maximum motor rating (UL/CSA)

Conventional thermal current Ith at 50°C (3-pole, open)

116 A

Rated operational current (Ie) at AC-3, 500 V

80 A

Assigned motor power at 230/240 V, 60 Hz, 1-phase

15 HP

Screwdriver size

0.8 x 5.5/1 x 6 mm, Terminal screw, Control circuit cables, Standard screwdriver

2, Terminal screw, Control circuit cables, Pozidriv screwdriver

Duty factor

100 %

Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V

80 A

Conventional thermal current Ith of main contacts (1-pole, open)

325 A

Rated control supply voltage (Us) at AC, 60 Hz - max

0 V

Arcing time

15 ms

Rated operational power at AC-1, 690 V, 50 Hz

136 kW


Rated insulation voltage (Ui)

690 V

Altitude

Max. 2000 m

Serial Number Verified :

Authenticated: 

The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

Catalogs

- [Switching and protecting motors - catalog](#)
- [SmartWire-DT Catalog](#)
- [Product Range Catalog Switching and protecting motors](#)

Characteristic curve

- [eaton-contactors-characteristic-curve-2110dia-3.eps](#)
- [eaton-contactors-switching-dilmp-characteristic-curve.eps](#)

Declarations of conformity

- [DA-DC-00004818.pdf](#)
- [DA-DC-00004781.pdf](#)

Drawings

- [eaton-contactors-mounting-dilm-dimensions.eps](#)
- [eaton-contactors-dilmp-dimensions-004.eps](#)
- [eaton-contactors-dilmp-dimensions-003.eps](#)
- [eaton-contactors-mounting-dilm-dimensions-002.eps](#)

Download all files

eCAD model

- [DA-CE-ETN.DILMP125\(RDC24\)](#)

Installation instructions

- [IL03407049Z](#)

Installation videos

- [WIN-WIN with push-in technology](#)

mCAD model

- [DA-CS-dil_mp125_200](#)
- [DA-CD-dil_mp125_200](#)

Download all files

Wiring diagrams

- [eaton-contactors-contact-dilem-wiring-diagram.eps](#)

Export product specification

-

x



Enter your city, state, or zip code or [Locate me](#)

City, state

Search

Show locations that offer:

- Product pickup
- Order online and ship product

- 109910

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)
- [Policies and statements](#)
- [Terms and conditions](#)
- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

Let's talk big ideas

-
-
-
-

[View all social media](#)

- [Sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

© 2023 Eaton. All Rights Reserved.

[Back to top of the page](#)

Are you sure?

[Cancel](#) [Sign out](#)

Are you sure?

[Cancel](#) [Sign out](#)

[×](#)

[×](#)