



**107671**  
**DILM72(RDC24)**

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per IEC/EN 61439](#)

[Technical data ETIM7.0](#)

[Approvals](#)

[Characteristics](#)

[Dimensions](#)

## DELIVERY PROGRAM

Product range  
Contactors

Application  
Contactors for Motors

Subrange  
Contactors up to 170 A, 3 pole

Utilization category  
AC-1: Non-inductive or slightly inductive loads, resistance furnaces  
NAC-3: Normal AC induction motors: starting, switch off during running  
AC-4: Normal AC induction motors: starting, plugging, reversing, inching

Notes  
Not suitable for motors with efficiency class IE3.

Connection technique  
Screw terminals

Number of poles  
3 pole

### Rated operational current

AC-3  
Notes  
At maximum permissible ambient temperature  
(open.)

AC-3  
380 V 400 V [I<sub>e</sub>]  
72 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [I<sub>th</sub> = I<sub>e</sub>]  
98 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [I<sub>th</sub>]  
72 A

AC-1  
Conventional free air thermal current, 1 pole  
open [I<sub>th</sub>]  
200 A

AC-1  
Conventional free air thermal current, 1 pole  
enclosed [I<sub>th</sub>]  
180 A

### Max. rating for three-phase motors, 50 - 60 Hz

AC-3  
220 V 230 V [P]  
22 kW

AC-3  
380 V 400 V [P]  
37 kW

AC-3  
660 V 690 V [F]  
35 kW

AC-4  
220 V 230 V [F]  
7 kW

AC-4  
380 V 400 V [F]  
12 kW

AC-4  
660 V 690 V [F]  
17 kW

Contact sequence



### Instructions

Contacts to EN 50 012.  
integrated suppressor circuit in actuating  
electronics  
Observe electrical lifespan.

Can be combined with auxiliary contact  
DILM150-XH(V)...  
DILM1000-XH(V)...

Actuating voltage  
RDC 24: 24 - 27 V DC

Voltage AC/DC  
DC operation

Connection to SmartWire-DT  
no

Frame size  
3

## TECHNICAL DATA

## General

Standards  
IEC/EN 60947, VDE 0660, UL, CSA

Lifespan, mechanical  
DC operated [Operations]  
 $10 \times 10^6$

Operating frequency, mechanical  
DC operated [Operations/h]  
5000


Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Open  
-25 - +60 °C

Ambient temperature  
Enclosed  
- 25 - 40 °C

Ambient temperature  
Storage  
- 40 - 80 °C

### Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Main contacts  
N/O contact  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/O contact  
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/C contact  
5 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Main contacts  
N/O contact  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/O contact  
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/C contact  
5 g

Degree of Protection  
IP00

Protection against direct contact when actuated  
from front (EN 50274)  
Finger and back-of-hand proof

Altitude  
Max. 2000 m

Weight  
DC operated  
1.052 kg

Screw connector terminals  
Terminal capacity main cable  
Solid  
1 x (0.75 - 16)  
2 x (0.75 - 16) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity main cable  
Flexible with ferrule  
1 x (0.75 - 35)

2 x (0.75 - 25) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity main cable  
Stranded  
1 x (16 - 50)  
2 x (16 - 35) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity main cable  
Solid or stranded  
single 14 - 1, double 14 - 2 AWG

Screw connector terminals  
Terminal capacity main cable  
Flat conductor [Lamellenzahl x Breite x Dicke ]  
2 x (6 x 9 x 0.8) mm

Screw connector terminals  
Terminal capacity main cable  
Stripping length  
14 mm

Screw connector terminals  
Terminal capacity main cable  
Terminal screw  
M6

Screw connector terminals  
Terminal capacity main cable  
Tightening torque  
3.3 Nm

Screw connector terminals  
Terminal capacity main cable  
Tool  
Pozidriv screwdriver  
2 Size

Screw connector terminals  
Terminal capacity main cable  
Tool  
Standard screw driver  
0.8 x 5.5  
1 x 6 mm

Screw connector terminals  
Terminal capacity control circuit cables  
Solid  
1 x (0.75 - 4)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity control circuit cables  
Flexible with ferrule  
1 x (0.75 - 2.5)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity control circuit cables  
Solid or stranded  
18 - 14 AWG

Screw connector terminals  
Terminal capacity control circuit cables  
Stripping length  
10 mm

Screw connector terminals  
Terminal capacity control circuit cables  
Terminal screw  
M3.5

Screw connector terminals  
Terminal capacity control circuit cables  
Tightening torque  
1.2 Nm

Screw connector terminals  
Terminal capacity control circuit cables  
Tool  
Pozidriv screwdriver  
2 Size

Screw connector terminals  
Terminal capacity control circuit cables  
Tool  
Standard screw driver  
0.8 x 5.5  
1 x 6 mm

## Main conducting paths

Rated impulse withstand voltage [ $U_{imp}$ ]  
8000 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [ $U_i$ ]  
690 V AC

Rated operational voltage [ $U_e$ ]  
690 V AC

Safe isolation to EN 61140  
between coil and contacts  
440 V AC

Safe isolation to EN 61140  
between the contacts  
440 V AC

Making capacity (p.f. to IEC/EN 60947) [Up to 690  
V]  
910 A

Breaking capacity  
220 V 230 V  
650 A

Breaking capacity  
380 V 400 V  
650 A

Breaking capacity  
500 V  
650 A

Breaking capacity  
660 V 690 V  
370 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "2" coordination  
400 V [gG/gL 500 V]  
125 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "2" coordination  
690 V [gG/gL 690 V]  
80 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "1" coordination  
400 V [gG/gL 500 V]



250 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "1" coordination  
690 V [gG/gL 690 V]  
100 A

## AC

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [ $I_{th} = I_e$ ]  
98 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 50 °C [ $I_{th} = I_e$ ]  
88 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 55 °C [ $I_{th} = I_e$ ]  
83 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 60 °C [ $I_{th} = I_e$ ]  
80 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
72 A

AC-1  
Rated operational current  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]

200 A

AC-1

Rated operational current  
Conventional free air thermal current, 1 pole  
enclosed [ $I_{th}$ ]  
180 A

AC-3

Rated operational current  
Open, 3-pole: 50 – 60 Hz  
Notes  
At maximum permissible ambient temperature  
(open.)

AC-3

Rated operational current  
Open, 3-pole: 50 – 60 Hz  
220 V 230 V [ $I_e$ ]  
72 A

AC-3

Rated operational current  
Open, 3-pole: 50 – 60 Hz  
240 V [ $I_e$ ]  
72 A

AC-3

Rated operational current  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [ $I_e$ ]  
72 A

AC-3

Rated operational current  
Open, 3-pole: 50 – 60 Hz  
415 V [ $I_e$ ]  
72 A

AC-3

Rated operational current  
Open, 3-pole: 50 – 60 Hz  
440V [ $I_e$ ]  
72 A

AC-3

Rated operational current  
Open, 3-pole: 50 – 60 Hz  
500 V [ $I_e$ ]  
72 A

AC-3

Rated operational current  
Open, 3-pole: 50 – 60 Hz  
660 V 690 V [I<sub>e</sub>]  
37 A

AC-3  
MOTOR rating [P]  
220 V 230 V [P]  
22 kW

AC-3  
MOTOR rating [P]  
240V [P]  
25 kW

AC-3  
MOTOR rating [P]  
380 V 400 V [P]  
37 kW

AC-3  
MOTOR rating [P]  
415 V [P]  
41 kW

AC-3  
MOTOR rating [P]  
440 V [P]  
44 kW

AC-3  
MOTOR rating [P]  
500 V [P]  
50 kW

AC-3  
MOTOR rating [P]  
660 V 690 V [P]  
35 kW

AC-4  
Open, 3-pole: 50 – 60 Hz  
220 V 230 V [I<sub>e</sub>]  
25 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
240 V [I<sub>e</sub>]  
25 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [I<sub>e</sub>]  
25 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
415 V [I<sub>e</sub>]  
25 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
440 V [I<sub>e</sub>]  
25 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
500 V [I<sub>e</sub>]  
25 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
660 V 690 V [I<sub>e</sub>]  
20 A

AC-4  
MOTOR rating [P]  
220 V 230 V [P]  
7 kW

AC-4  
MOTOR rating [P]  
240 V [P]  
7.5 kW

AC-4  
MOTOR rating [P]  
380 V 400 V [P]  
12 kW

AC-4  
MOTOR rating [P]  
415 V [P]  
13 kW

AC-4  
MOTOR rating [P]  
440 V [P]  
14 kW

AC-4  
Motor rating [P]  
500 V [F]  
16 kW

AC-4  
Motor rating [P]  
660 V 690 V [F]  
17 kW

## DC

Rated operational current, open  
DC-1  
60 V [ $I_e$ ]  
72 A

Rated operational current, open  
DC-1  
110 V [ $I_e$ ]  
72 A

Rated operational current, open  
DC-1  
220 V [ $I_e$ ]  
65 A

## Current heat loss

3 pole, at  $I_{th}$  (60°)  
25.9 W

Current heat loss at  $I_e$  to AC-3/400 V  
21 W

Impedance per pole  
1.9 m $\Omega$

## Magnet systems

Voltage tolerance  
DC operated [Pick-up]  
0.7 - 1.2 x  $U_c$

Voltage tolerance  
Notes

RDC 24 ( $U_{\min}$  24 V DC/ $U_{\max}$  27 V DC)  
Example:  $U_S = 0.7 \times U_{\min} - 1.2 \times U_{\max} / U_S = 0.7 \times 24V - 1.2 \times 27V$  DC

Voltage tolerance  
DC operated [Drop-out]  
 $0.15 - 0.6 \times U_c$

Voltage tolerance  
Notes  
at least smoothed two-phase bridge rectifier or three-phase rectifier

Power consumption of the coil in a cold state and  
 $1.0 \times U_S$   
DC operated [Pick-up]  
24 W

Power consumption of the coil in a cold state and  
 $1.0 \times U_S$   
DC operated [Sealing]  
1 W

Duty factor  
100 % DF

Changeover time at 100 %  $U_S$  (recommended value)  
Main contacts  
DC operated  
Closing delay  
Closing delay  
54 ms

Changeover time at 100 %  $U_S$  (recommended value)  
Main contacts  
DC operated  
Opening delay  
Opening delay  
24 ms

Changeover time at 100 %  $U_S$  (recommended value)  
Arcing time  
10 ms

## Electromagnetic compatibility (EMC)

Emitted interference

to EN 60947-1

Interference immunity  
to EN 60947-1

### Rating data for approved types

Switching capacity  
Maximum motor rating  
Three-phase  
200 V  
208 V  
20 HP

Switching capacity  
Maximum motor rating  
Three-phase  
230 V  
240 V  
25 HP

Switching capacity  
Maximum motor rating  
Three-phase  
460 V  
480 V  
50 HP

Switching capacity  
Maximum motor rating  
Three-phase  
575 V  
600 V  
60 HP

Switching capacity  
Maximum motor rating  
Single-phase  
115 V  
120 V  
5 HP

Switching capacity  
Maximum motor rating  
Single-phase  
230 V  
240 V  
15 HP

Switching capacity  
General use  
88 A

Short Circuit Current Rating  
Basic Rating  
SCCR  
10 kA

Short Circuit Current Rating  
Basic Rating  
max. Fuse  
250 A

Short Circuit Current Rating  
Basic Rating  
max. CB  
250 A

Short Circuit Current Rating  
480 V High Fault  
SCCR (fuse)  
30/100 kA

Short Circuit Current Rating  
480 V High Fault  
max. Fuse  
250/150 Class J A

Short Circuit Current Rating  
480 V High Fault  
SCCR (CB)  
65 kA

Short Circuit Current Rating  
480 V High Fault  
max. CB  
100 A

Short Circuit Current Rating  
600 V High Fault  
SCCR (fuse)  
30/100 kA

Short Circuit Current Rating  
600 V High Fault  
max. Fuse  
250/150 Class J A

Short Circuit Current Rating  
600 V High Fault  
SCCR (CB)  
30 kA



Short Circuit Current Rating  
600 V High Fault  
max. CB  
250 A

Special Purpose Ratings  
Electrical Discharge Lamps (Ballast)  
480V 60Hz 3phase, 277V 60Hz 1phase  
88 A

Special Purpose Ratings  
Electrical Discharge Lamps (Ballast)  
600V 60Hz 3phase, 347V 60Hz 1phase  
88 A

Special Purpose Ratings  
Incandescent Lamps (Tungsten)  
480V 60Hz 3phase, 277V 60Hz 1phase  
88 A

Special Purpose Ratings  
Incandescent Lamps (Tungsten)  
600V 60Hz 3phase, 347V 60Hz 1phase  
88 A

Special Purpose Ratings  
Resistance Air Heating  
480V 60Hz 3phase, 277V 60Hz 1phase  
88 A

Special Purpose Ratings  
Resistance Air Heating  
600V 60Hz 3phase, 347V 60Hz 1phase  
88 A

Special Purpose Ratings  
Definite Purpose Ratings (100,000 cycles acc. to  
UL 1995)  
LRA 480V 60Hz 3phase  
432 A

Special Purpose Ratings  
Definite Purpose Ratings (100,000 cycles acc. to  
UL 1995)  
FLA 480V 60Hz 3phase  
72 A

Special Purpose Ratings  
Elevator Control

200V 60Hz 3phase  
10 HP

Special Purpose Ratings  
Elevator Control  
200V 60Hz 3phase  
32.2 A

Special Purpose Ratings  
Elevator Control  
240V 60Hz 3phase  
15 HP

Special Purpose Ratings  
Elevator Control  
240V 60Hz 3phase  
42 A

Special Purpose Ratings  
Elevator Control  
480V 60Hz 3phase  
30 HP

Special Purpose Ratings  
Elevator Control  
480V 60Hz 3phase  
40 A

Special Purpose Ratings  
Elevator Control  
600V 60Hz 3phase  
40 HP

Special Purpose Ratings  
Elevator Control  
600V 60Hz 3phase  
41 A

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [I<sub>n</sub>]  
72 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]  
7 W

Equipment heat dissipation, current-dependent  
[ $P_{vid}$ ]  
21 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
1 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+60 °C

## IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of  
enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating  
materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating  
materials to abnormal heat and fire due to internal  
electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2 Strength of materials and parts

##### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2 Strength of materials and parts

##### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9 Insulation properties

##### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9 Insulation properties

##### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9 Insulation properties

##### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage  $U_s$  at AC 50HZ  
0 - 0 V

Rated control supply voltage  $U_s$  at AC 60HZ  
0 - 0 V

Rated control supply voltage  $U_s$  at DC  
24 - 27 V

Voltage type for actuating  
DC

Rated operation current  $I_e$  at AC-1, 400 V  
98 A

Rated operation current  $I_e$  at AC-3, 400 V

72 A

Rated operation power at AC-3, 400 V  
37 kW

Rated operation current Ie at AC-4, 400 V  
25 A

Rated operation power at AC-4, 400 V  
12 kW

Rated operation power NEMA  
37 kW

Modular version  
No

Number of auxiliary contacts as normally open  
contact  
0

Number of auxiliary contacts as normally closed  
contact  
0

Type of electrical connection of main circuit  
Screw connection

Number of normally closed contacts as main  
contact  
0

Number of main contacts as normally open contact  
3

## APPROVALS

Product Standards  
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No.  
60947-4-1-14; CE marking

UL File No.  
E29096

UL Category Control No.  
NLDX


CSA File No.  
012528

CSA Class No.  
2411-03, 3211-04

North America Certification  
UL listed, CSA certified

Specially designed for North America  
No


## CHARACTERISTICS



### Accessories

- 1: Overload relay
- 2: Suppressor
- 3: Auxiliary contact modules


### Side mounting auxiliary contacts



possible variants at auxiliary contact module fitting  
options


- on the side: 2 x DILM1000-XHI(V)11-St; surface mounting: 1 x DILM150-XHIA11
- on the side: 2 x DILM1000-XHI(V)11-SA; surface mounting: 1 x DILM150-XHI (2 pole)
- on the side: 1 x DILM1000-XHI(V)11-St; surface mounting: 1 x DILM150-XHIA22
- on the side: 1 x DILM1000-XHI(V)11-SA; surface mounting: 1 x DILM150-XHI (4 pole)

### Characteristic curve



- Squirrel-cage motor
- Operating characteristics
- Starting: from rest
- Stopping: after attaining full running speed
- Electrical characteristics
- Make: up to 6 x rated motor current
- Break: up to 1 x rated motor current
- Utilization category
- 100 % AC-3
- Typical applications
- Compressors
- Lifts
- Mixers
- Pumps
- Escalators
- Agitators
- Fans
- Conveyor belts
- Centrifuges
- Hinged flaps
- Bucket-elevators
- Air conditioning system
- General drives in manufacturing and processing machines


### Characteristic curve



- Extreme switching duty
- Squirrel-cage motor
- Operating characteristics
- Inching, plugging, reversing
- Electrical characteristics
- Make: up to 6 x rated motor current
- Break: up to 6 x rated motor current
- Utilization category
- 100 % AC-4
- Typical applications
- Printing presses
- Wire-drawing machines
- Centrifuges
- Special drives for manufacturing and processing machines

### Characteristic curve





Switching conditions for non-motor consumers, 3 pole, 4 pole  
Operating characteristics  
Non inductive and slightly inductive loads  
Electrical characteristics  
Switch on: 1 x rated operational current  
Switch off: 1 x rated operational current  
Utilization category  
100 % AC-1  
Typical examples of application  
Electric heat

Characteristic curve



## DIMENSIONS



Contactor with auxiliary contact module



Lateral clearance to earthed parts: 6 mm

DILM40...DILM72  
DILMC40...DILMC65  
DILMF40...DILMF65



