



277262

DILM 32-10(400V50HZ,440V60HZ)

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per IEC/EN 61439](#)

[Technical data ETIM 7.0](#)

[Characteristics](#)

[Dimensions](#)

## DELIVERY PROGRAM

Product range  
Contactors

Application  
Contactors for Motors

Subrange  
Contactors up to 170 A, 3 pole

Utilization category  
AC-1: Non-inductive or slightly inductive loads, resistance furnaces  
AC-3/AC-3e: Normal AC induction motors: Starting, switching off while running  
AC-4: Normal AC induction motors: starting, plugging, reversing, inching



Notes

Also suitable for motors with efficiency class IE3.

Connection technique  
Screw terminals

Number of poles  
3 pole

### Rated operational current

AC-3  
Notes  
At maximum permissible ambient temperature  
(open.)  
Also tested according to AC-3e.

AC-3  
380 V 400 V [ $I_e$ ]  
32 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [ $I_{th} = I_e$ ]  
45 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
36 A

AC-1  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]  
100 A

AC-1  
Conventional free air thermal current, 1 pole  
enclosed [ $I_{th}$ ]  
90 A

### Max. rating for three-phase motors, 50 - 60 Hz

AC-3  
220 V 230 V [P]  
10 kW

AC-3  
380 V 400 V [F]  
15 kW

AC-3  
660 V 690 V [F]  
17 kW

AC-4  
220 V 230 V [F]  
4 kW

AC-4  
380 V 400 V [F]  
7 kW

AC-4  
660 V 690 V [F]  
10 kW

## Contacts

NO = Normally open  
1 NO

Contact sequence



## Instructions

Contacts to EN 50 012.

Can be combined with auxiliary contact  
DILM32-XH...  
DILA-XH(V)...

Actuating voltage  
400 V 50 Hz, 440 V 60 Hz

Voltage AC/DC  
AC operation

Connection to SmartWire-DT  
no

Frame size  
2

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947, VDE 0660, UL, CSA

Lifespan, mechanical  
AC operated [Operations]  
 $10 \times 10^6$

Operating frequency, mechanical  
AC operated [Operations/h]  
5000


Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Open  
-25 - +60 °C

Ambient temperature  
Enclosed  
- 25 - 40 °C

Ambient temperature  
Storage  
- 40 - 80 °C

Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Main contacts  
NO contact

10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/O contact  
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/C contact  
5 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Main contacts  
N/O contact  
6.9 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/O contact  
5.3 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/C contact  
3.5 g

Degree of Protection  
IP00

Protection against direct contact when actuated  
from front (EN 50274)  
Finger and back-of-hand proof

Altitude  
Max. 2000 m

Weight  
AC operated  
0.428 kg

Screw connector terminals

Terminal capacity main cable  
Solid  
1 x (0.75 - 16)  
2 x (0.75 - 10) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity main cable  
Flexible with ferrule  
1 x (0.75 - 16)  
2 x (0.75 - 10) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity main cable  
Stranded  
1 x 16 mm<sup>2</sup>

Screw connector terminals  
Terminal capacity main cable  
Solid or stranded  
single 18 - 6, double 18 - 8 AWG

Screw connector terminals  
Terminal capacity main cable  
Stripping length  
10 mm

Screw connector terminals  
Terminal capacity main cable  
Terminal screw  
M5

Screw connector terminals  
Terminal capacity main cable  
Tightening torque  
3.2 Nm

Screw connector terminals  
Terminal capacity main cable  
Tool  
Pozidriv screwdriver  
2 Size

Screw connector terminals  
Terminal capacity main cable  
Tool  
Standard screw driver  
0.8 x 5.5  
1 x 6 mm

Screw connector terminals  
Terminal capacity control circuit cables  
Solid

1 x (0.75 - 4)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity control circuit cables  
Flexible with ferrule  
1 x (0.75 - 2.5)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Screw connector terminals  
Terminal capacity control circuit cables  
Solid or stranded  
18 - 14 AWG

Screw connector terminals  
Terminal capacity control circuit cables  
Stripping length  
10 mm

Screw connector terminals  
Terminal capacity control circuit cables  
Terminal screw  
M3.5

Screw connector terminals  
Terminal capacity control circuit cables  
Tightening torque  
1.2 Nm

Screw connector terminals  
Terminal capacity control circuit cables  
Tool  
Pozidriv screwdriver  
2 Size

Screw connector terminals  
Terminal capacity control circuit cables  
Tool  
Standard screwdriver  
0.8 x 5.5  
1 x 6 mm

## Main conducting paths

Rated impulse withstand voltage [ $U_{imp}$ ]  
8000 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [U]  
690 V AC

Rated operational voltage [U<sub>e</sub>]  
690 V AC

Safe isolation to EN 61140  
between coil and contacts  
440 V AC

Safe isolation to EN 61140  
between the contacts  
440 V AC

Making capacity (p.f. to IEC/EN 60947) [Up to 690  
V]  
384 A

Breaking capacity  
220 V 230 V  
320 A

Breaking capacity  
380 V 400 V  
320 A

Breaking capacity  
500 V  
320 A

Breaking capacity  
660 V 690 V  
180 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "2" coordination  
400 V [gG/gL 500 V]  
63 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "2" coordination  
690 V [gG/gL 690 V]  
35 A

Short-circuit rating



Short-circuit protection maximum fuse  
Type "1" coordination  
400 V [gG/gL 500 V]  
125 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "1" coordination  
690 V [gG/gL 690 V]  
63 A

## AC

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [ $I_{th} = I_e$ ]  
45 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 50 °C [ $I_{th} = I_e$ ]  
43 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 55 °C [ $I_{th} = I_e$ ]  
42 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 60 °C [ $I_{th} = I_e$ ]  
40 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
36 A

AC-1

Rated operational current  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]  
100 A

AC-1  
Rated operational current  
Conventional free air thermal current, 1 pole  
enclosed [ $I_{th}$ ]  
90 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
Notes  
At maximum permissible ambient temperature  
(open.)  
Also tested according to AC-3e.

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
220 V 230 V [ $I_e$ ]  
32 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
240 V [ $I_e$ ]  
32 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [ $I_e$ ]  
32 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
415 V [ $I_e$ ]  
32 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
440V [ $I_e$ ]  
32 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
500 V [ $I_e$ ]

32 A

AC-3

Rated operational current

Open, 3-pole: 50 – 60 Hz

660 V 690 V [I<sub>e</sub>]

18 A

AC-3

Motor rating [P]

220 V 230 V [P]

10 kW

AC-3

Motor rating [P]

240V [P]

11 kW

AC-3

Motor rating [P]

380 V 400 V [P]

15 kW

AC-3

Motor rating [P]

415 V [P]

19 kW

AC-3

Motor rating [P]

440 V [P]

20 kW

AC-3

Motor rating [P]

500 V [P]

23 kW

AC-3

Motor rating [P]

660 V 690 V [P]

17 kW

AC-4

Open, 3-pole: 50 – 60 Hz

220 V 230 V [I<sub>e</sub>]

15 A

AC-4

Open, 3-pole: 50 – 60 Hz

240 V [I<sub>e</sub>]  
15 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [I<sub>e</sub>]  
15 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
415 V [I<sub>e</sub>]  
15 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
440 V [I<sub>e</sub>]  
15 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
500 V [I<sub>e</sub>]  
15 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
660 V 690 V [I<sub>e</sub>]  
12 A

AC-4  
MOTOR rating [F]  
220 V 230 V [F]  
4 kW

AC-4  
MOTOR rating [F]  
240 V [F]  
4.5 kW

AC-4  
MOTOR rating [F]  
380 V 400 V [F]  
7 kW

AC-4  
MOTOR rating [F]  
415 V [F]  
7.5 kW

AC-4  
MOTOR rating [F]

440 V [P]  
8 kW

AC-4  
Mtor rating [P]  
500 V [P]  
9 kW

AC-4  
Mtor rating [P]  
660 V 690 V [P]  
10 kW

## DC

Rated operational current, open  
DC-1  
60 V [ $I_e$ ]  
40 A

Rated operational current, open  
DC-1  
110 V [ $I_e$ ]  
40 A

Rated operational current, open  
DC-1  
220 V [ $I_e$ ]  
40 A

## Current heat loss

3 pole, at  $I_{th}$  (60°)  
10.3 W

Current heat loss at  $I_e$  to AC-3/400 V  
6.6 W

Impedance per pole  
2.7 m $\Omega$

## Magnet systems

Voltage tolerance  
AC operated [Pick-up]  
0.8 - 1.1 x  $U_c$

Voltage tolerance  
Drop-out voltage AC operated [Drop-out]  
 $0.3 - 0.6 \times U_c$

Power consumption of the coil in a cold state and  
 $1.0 \times U_s$   
50 Hz [Pick-up]  
52 VA

Power consumption of the coil in a cold state and  
 $1.0 \times U_s$   
50 Hz [Sealing]  
7.1 VA

Power consumption of the coil in a cold state and  
 $1.0 \times U_s$   
50 Hz [Sealing]  
2.1 W

Power consumption of the coil in a cold state and  
 $1.0 \times U_s$   
60 Hz [Pick-up]  
67 VA

Power consumption of the coil in a cold state and  
 $1.0 \times U_s$   
60 Hz [Sealing]  
8.7 VA

Power consumption of the coil in a cold state and  
 $1.0 \times U_s$   
60 Hz [Sealing]  
2.1 W

Duty factor  
100 % DF

Changeover time at 100 %  $U_s$  (recommended  
value)  
Main contacts  
AC operated  
Closing delay  
16 - 22 ms

Changeover time at 100 %  $U_s$  (recommended  
value)  
Main contacts  
AC operated  
Opening delay  
8 - 14 ms

Changeover time at 100 %  $U_N$  (recommended value)  
Arcing time  
10 ms

### Electromagnetic compatibility (EMC)

Emitted interference  
to EN 60947-1

Interference immunity  
to EN 60947-1

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat dissipation [ $I_r$ ]  
32 A

Heat dissipation per pole, current-dependent [ $P_{id}$ ]  
2.2 W

Equipment heat dissipation, current-dependent [ $P_{id}$ ]  
6.6 W

Static heat dissipation, non-current-dependent [ $P_{is}$ ]  
2.1 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+60 °C

### IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.



10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage  $U_s$  at AC 50HZ  
400 - 400 V

Rated control supply voltage  $U_s$  at AC 60HZ  
440 - 440 V

Rated control supply voltage  $U_s$  at DC  
0 - 0 V

Voltage type for actuating  
AC

Rated operation current  $I_e$  at AC-1, 400 V  
45 A

Rated operation current  $I_e$  at AC-3, 400 V  
32 A

Rated operation power at AC-3, 400 V  
15 kW

Rated operation current  $I_e$  at AC-4, 400 V  
15 A

Rated operation power at AC-4, 400 V  
7 kW

Rated operation power NEVA  
14.9 kW

Modular version  
No

Number of auxiliary contacts as normally open  
contact  
1

Number of auxiliary contacts as normally closed


contact  
0

Type of electrical connection of main circuit  
Screw connection

Number of normally closed contacts as main  
contact  
0

Number of main contacts as normally open contact  
3

## CHARACTERISTICS




Accessories

1: Overload relay

2: Suppressor

3: Auxiliary contact modules

Characteristic curve



Squirrel-cage motor

Operating characteristics

Starting:from rest

Stopping:after attaining full running speed

Electrical characteristics

Make: up to 6 x rated motor current

Break: up to 1 x rated motor current

Utilization category

100 % AC-3

Typical applications

Compressors

Lifts

Mixers

Pumps

Escalators

Agitators

Fans

Conveyor belts

Centrifuges

Hinged flaps

Bucket-elevators

Air conditioning system  
General drives in manufacturing and processing  
machines

Characteristic curve



Extreme switching duty  
Squirrel-cage motor  
Operating characteristics  
Inching, plugging, reversing  
Electrical characteristics  
Make: up to 6 x rated motor current  
Break: up to 6 x rated motor current  
Utilization category  
100 % AC-4  
Typical applications  
Printing presses  
Wire-drawing machines  
Centrifuges  
Special drives for manufacturing and processing  
machines

Characteristic curve



Switching conditions for non-motor consumers, 3  
pole, 4 pole  
Operating characteristics  
Non inductive and slightly inductive loads  
Electrical characteristics  
Switch on: 1 x rated operational current  
Switch off: 1 x rated operational current  
Utilization category  
100 % AC-1  
Typical examples of application  
Electric heat

## DIMENSIONS



Contactor with auxiliary contact module



distance at side to earthed parts: 6 mm



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)