



277753
DILM40(24V50HZ)

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per IEC/EN 61439](#)

[Technical data ETIM7.0](#)

[Approvals](#)

[Characteristics](#)

[Dimensions](#)

DELIVERY PROGRAM

Product range
Contactors

Application
Contactors for Motors

Subrange
Contactors up to 170 A, 3 pole

Utilization category
AC-1: Non-inductive or slightly inductive loads, resistance furnaces
AC-3/AC-3e: Normal AC induction motors: Starting, switching off while running
AC-4: Normal AC induction motors: starting, plugging, reversing, inching



Notes

Also suitable for motors with efficiency class IE3.

Connection technique
Screw terminals

Number of poles
3 pole

Rated operational current

AC-3
Notes
At maximum permissible ambient temperature
(open.)
Also tested according to AC-3e.

AC-3
380 V 400 V [I_e]
40 A

AC-1
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 40 °C [$I_{th} = I_e$]
60 A

AC-1
Conventional free air thermal current, 3 pole, 50 -
60 Hz
enclosed [I_{th}]
45 A

AC-1
Conventional free air thermal current, 1 pole
open [I_{th}]
125 A

AC-1
Conventional free air thermal current, 1 pole
enclosed [I_{th}]
112 A

Max. rating for three-phase motors, 50 - 60 Hz

AC-3
220 V 230 V [P]
12.5 kW

AC-3
380 V 400 V [F]
18.5 kW

AC-3
660 V 690 V [F]
23 kW

AC-4
220 V 230 V [F]
5 kW

AC-4
380 V 400 V [F]
9 kW

AC-4
660 V 690 V [F]
12 kW

Contact sequence



Instructions

Contacts to EN 50 012.

Can be combined with auxiliary contact
DILM150-XH(V)...
DILM1000-XH(V)...

Actuating voltage
24 V 50 Hz

Voltage AC/DC
AC operation

Connection to SmartWire-DT
no

Frame size
3

TECHNICAL DATA

General

Standards
IEC/EN 60947, VDE 0660, UL, CSA

Lifespan, mechanical
AC operated [Operations]
 10×10^6

Operating frequency, mechanical
AC operated [Operations/h]
5000


Climatic proofing
Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature
Open
-25 - +60 °C

Ambient temperature
Enclosed
- 25 - 40 °C

Ambient temperature
Storage
- 40 - 80 °C

Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Main contacts
N/O contact
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/O contact
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/C contact
5 g

Mechanical shock resistance (IEC/EN 60068-2-27)
when tabletop-mounted
Half-sinusoidal shock, 10 ms
Main contacts
N/O contact
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)
when tabletop-mounted
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/O contact
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)
when tabletop-mounted
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/C contact
5 g

Degree of Protection
IP00

Protection against direct contact when actuated
from front (EN 50274)
Finger and back-of-hand proof

Altitude
Max. 2000 m

Weight
AC operated
0.872 kg

Screw connector terminals
Terminal capacity main cable
Solid
1 x (0.75 - 16)
2 x (0.75 - 16) mm²

Screw connector terminals
Terminal capacity main cable

Flexible with ferrule
1 x (0.75 - 35)
2 x (0.75 - 25) mm²

Screw connector terminals
Terminal capacity main cable
Stranded
1 x (16 - 50)
2 x (16 - 35) mm²

Screw connector terminals
Terminal capacity main cable
Solid or stranded
single 14 - 1, double 14 - 2 AWG

Screw connector terminals
Terminal capacity main cable
Flat conductor [Lamellenzahl x Breite x Dicke]
2 x (6 x 9 x 0.8) mm

Screw connector terminals
Terminal capacity main cable
Stripping length
14 mm

Screw connector terminals
Terminal capacity main cable
Terminal screw
M6

Screw connector terminals
Terminal capacity main cable
Tightening torque
3.3 Nm

Screw connector terminals
Terminal capacity main cable
Tool
Poqidriv screwdriver
2 Size

Screw connector terminals
Terminal capacity main cable
Tool
Standard screw driver
0.8 x 5.5
1 x 6 mm

Screw connector terminals
Terminal capacity control circuit cables
Solid
1 x (0.75 - 4)

2 x (0.75 - 2.5) mm²

Screw connector terminals
Terminal capacity control circuit cables
Flexible with ferrule
1 x (0.75 - 2.5)
2 x (0.75 - 2.5) mm²

Screw connector terminals
Terminal capacity control circuit cables
Solid or stranded
18 - 14 AWG

Screw connector terminals
Terminal capacity control circuit cables
Stripping length
10 mm

Screw connector terminals
Terminal capacity control circuit cables
Terminal screw
M3.5

Screw connector terminals
Terminal capacity control circuit cables
Tightening torque
1.2 Nm

Screw connector terminals
Terminal capacity control circuit cables
Tool
Pozidriv screwdriver
2 Size

Screw connector terminals
Terminal capacity control circuit cables
Tool
Standard screwdriver
0.8 x 5.5
1 x 6 mm

Main conducting paths

Rated impulse withstand voltage [U_{imp}]
8000 V AC

Overvoltage category/pollution degree
III/3

Rated insulation voltage [U]
690 V AC

Rated operational voltage [U_e]
690 V AC

Safe isolation to EN 61140
between coil and contacts
440 V AC

Safe isolation to EN 61140
between the contacts
440 V AC

Making capacity (p.f. to IEC/EN 60947) [Up to 690
V]
560 A

Breaking capacity
220 V 230 V
400 A

Breaking capacity
380 V 400 V
400 A

Breaking capacity
500 V
400 A

Breaking capacity
660 V 690 V
250 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
400 V [gG/gL 500 V]
63 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
690 V [gG/gL 690 V]
50 A

Short-circuit rating
Short-circuit protection maximum fuse

Type "1" coordination
400 V [gG/gL 500 V]
125 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination
690 V [gG/gL 690 V]
80 A

AC

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 40 °C [$I_{th} = I_e$]
60 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 50 °C [$I_{th} = I_e$]
57 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 55 °C [$I_{th} = I_e$]
55 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 60 °C [$I_{th} = I_e$]
50 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
enclosed [I_{th}]
45 A

AC-1
Rated operational current

Conventional free air thermal current, 1 pole
open [I_{th}]
125 A

AC-1
Rated operational current
Conventional free air thermal current, 1 pole
enclosed [I_{th}]
112 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
Notes
At maximum permissible ambient temperature
(open.)
Also tested according to AC-3e.

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
220 V 230 V [I_e]
40 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
240 V [I_e]
40 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
40 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
415 V [I_e]
40 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
440V [I_e]
40 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
500 V [I_e]
40 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz
660 V 690 V [I_e]
25 A

AC-3
MOTOR rating [P]
220 V 230 V [P]
12.5 kW

AC-3
MOTOR rating [P]
240V [P]
13.5 kW

AC-3
MOTOR rating [P]
380 V 400 V [P]
18.5 kW

AC-3
MOTOR rating [P]
415 V [P]
24 kW

AC-3
MOTOR rating [P]
440 V [P]
25 kW

AC-3
MOTOR rating [P]
500 V [P]
28 kW

AC-3
MOTOR rating [P]
660 V 690 V [P]
23 kW

AC-4
Open, 3-pole: 50 – 60 Hz
220 V 230 V [I_e]
18 A

AC-4
Open, 3-pole: 50 – 60 Hz
240 V [I_e]

18 A

AC-4
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
18 A

AC-4
Open, 3-pole: 50 – 60 Hz
415 V [I_e]
18 A

AC-4
Open, 3-pole: 50 – 60 Hz
440 V [I_e]
18 A

AC-4
Open, 3-pole: 50 – 60 Hz
500 V [I_e]
18 A

AC-4
Open, 3-pole: 50 – 60 Hz
660 V 690 V [I_e]
14 A

AC-4
MOTOR rating [P]
220 V 230 V [P]
5 kW

AC-4
MOTOR rating [P]
240 V [P]
5.5 kW

AC-4
MOTOR rating [P]
380 V 400 V [P]
9 kW

AC-4
MOTOR rating [P]
415 V [P]
9.5 kW

AC-4
MOTOR rating [P]
440 V [P]

10 kW

AC-4
Mtor rating [P]
500 V [P]
11 kW

AC-4
Mtor rating [P]
660 V 690 V [P]
12 kW

DC

Rated operational current, open
DC-1
60 V [I_e]
50 A

Rated operational current, open
DC-1
110 V [I_e]
50 A

Rated operational current, open
DC-1
220 V [I_e]
45 A

Current heat loss

3 pole, at I_{th} (60°)
10.3 W

Current heat loss at I_e to AC-3/400 V
6.6 W

Impedance per pole
1.9 m Ω

Magnet systems

Voltage tolerance
AC operated [Pick-up]
0.8 - 1.1 x U_c

Voltage tolerance
Drop-out voltage AC operated [Drop-out]
 $0.3 - 0.6 \times U_c$

Power consumption of the coil in a cold state and
 $1.0 \times U_S$
50 Hz [Pick-up]
149 VA

Power consumption of the coil in a cold state and
 $1.0 \times U_S$
50 Hz [Sealing]
16 VA

Power consumption of the coil in a cold state and
 $1.0 \times U_S$
50 Hz [Sealing]
4.1 W

Power consumption of the coil in a cold state and
 $1.0 \times U_S$
60 Hz [Pick-up]
178 VA

Power consumption of the coil in a cold state and
 $1.0 \times U_S$
60 Hz [Sealing]
19 VA

Power consumption of the coil in a cold state and
 $1.0 \times U_S$
60 Hz [Sealing]
4.1 W

Duty factor
100 % DF

Changeover time at 100 % U_S (recommended
value)
Main contacts
AC operated
Closing delay
12 - 18 ms

Changeover time at 100 % U_S (recommended
value)
Main contacts
AC operated
Opening delay
8 - 13 ms

Changeover time at 100 % U_N (recommended value)
Arcing time
10 ms

Electromagnetic compatibility (EMC)

Emitted interference
to EN 60947-1

Interference immunity
to EN 60947-1

Rating data for approved types

Switching capacity
Maximum motor rating
Three-phase
200 V
208 V
10 HP

Switching capacity
Maximum motor rating
Three-phase
230 V
240 V
15 HP

Switching capacity
Maximum motor rating
Three-phase
460 V
480 V
30 HP

Switching capacity
Maximum motor rating
Three-phase
575 V
600 V
40 HP

Switching capacity
Maximum motor rating
Single-phase
115 V
120 V
3 HP

Switching capacity
Maximum motor rating
Single-phase
230 V
240 V
7.5 HP

Switching capacity
General use
63 A

Short Circuit Current Rating
Basic Rating
SCCR
10 kA

Short Circuit Current Rating
Basic Rating
max. Fuse
250 A

Short Circuit Current Rating
Basic Rating
max. CB
250 A

Short Circuit Current Rating
480 V High Fault
SCCR (fuse)
30/100 kA

Short Circuit Current Rating
480 V High Fault
max. Fuse
250/150 Class J A

Short Circuit Current Rating
480 V High Fault
SCCR (CB)
65 kA

Short Circuit Current Rating
480 V High Fault
max. CB
100 A

Short Circuit Current Rating
600 V High Fault
SCCR (fuse)
30/100 kA

Short Circuit Current Rating
600 V High Fault
max. Fuse
250/150 Class J A

Short Circuit Current Rating
600 V High Fault
SCCR (CB)
30 kA

Short Circuit Current Rating
600 V High Fault
max. CB
250 A

Special Purpose Ratings
Electrical Discharge Lamps (Ballast)
480V 60Hz 3phase, 277V 60Hz 1phase
79 A

Special Purpose Ratings
Electrical Discharge Lamps (Ballast)
600V 60Hz 3phase, 347V 60Hz 1phase
79 A

Special Purpose Ratings
Incandescent Lamps (Tungsten)
480V 60Hz 3phase, 277V 60Hz 1phase
74 A

Special Purpose Ratings
Incandescent Lamps (Tungsten)
600V 60Hz 3phase, 347V 60Hz 1phase
74 A

Special Purpose Ratings
Resistance Air Heating
480V 60Hz 3phase, 277V 60Hz 1phase
79 A

Special Purpose Ratings
Resistance Air Heating
600V 60Hz 3phase, 347V 60Hz 1phase
79 A

Special Purpose Ratings
Elevator Control
200V 60Hz 3phase
7.5 HP

Special Purpose Ratings
Elevator Control
200V 60Hz 3phase
25.3 A

Special Purpose Ratings
Elevator Control
240V 60Hz 3phase
10 HP

Special Purpose Ratings
Elevator Control
240V 60Hz 3phase
28 A

Special Purpose Ratings
Elevator Control
480V 60Hz 3phase
25 HP

Special Purpose Ratings
Elevator Control
480V 60Hz 3phase
34 A

Special Purpose Ratings
Elevator Control
600V 60Hz 3phase
30 HP

Special Purpose Ratings
Elevator Control
600V 60Hz 3phase
32 A

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]
40 A

Heat dissipation per pole, current-dependent [P_{vid}]
2.2 W

Equipment heat dissipation, current-dependent

[P_{icd}]

6.6 W

Static heat dissipation, non-current-dependent [P_{vs}]

4.1 W

Heat dissipation capacity [P_{diss}]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+60 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide

heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage U_s at AC 50HZ
24 - 24 V

Rated control supply voltage U_s at AC 60HZ
0 - 0 V

Rated control supply voltage U_s at DC
0 - 0 V

Voltage type for actuating
AC

Rated operation current I_e at AC-1, 400 V
60 A

Rated operation current I_e at AC-3, 400 V
40 A

Rated operation power at AC-3, 400 V

18.5 kW

Rated operation current I_e at AC-4, 400 V
18 A

Rated operation power at AC-4, 400 V
9 kW

Rated operation power NEMA
22 kW

Modular version
No

Number of auxiliary contacts as normally open
contact
0

Number of auxiliary contacts as normally closed
contact
0

Type of electrical connection of main circuit
Screw connection

Number of normally closed contacts as main
contact
0

Number of main contacts as normally open contact
3

APPROVALS

Product Standards
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No.
60947-4-1-14; CE marking

UL File No.
E29096

UL Category Control No.
NLDX

CSA File No.
012528

CSA Class No.
2411-03, 3211-04

North America Certification
UL listed, CSA certified

Specially designed for North America
No

CHARACTERISTICS



Accessories
1: Overload relay
2: Suppressor
3: Auxiliary contact modules

Side mounting auxiliary contacts



possible variants at auxiliary contact module fitting
options


on the side: 2 x DILM1000-XHI(V)11-SI; surface
mounting: 1 x DILM150-XHIA11

on the side: 2 x DILM1000-XHI(V)11-SA; surface
mounting: 1 x DILM150-XHI (2 pole)

on the side: 1 x DILM1000-XHI(V)11-SI; surface
mounting: 1 x DILM150-XHIA22

on the side: 1 x DILM1000-XHI(V)11-SA; surface
mounting: 1 x DILM150-XHI (4 pole)

Characteristic curve



Squirrel-cage motor
Operating characteristics
Starting: from rest
Stopping: after attaining full running speed
Electrical characteristics
Make: up to 6 x rated motor current

Break: up to 1 x rated motor current
Utilization category
100 % AC-3
Typical applications
Compressors
Lifts
Mixers
Pumps
Escalators
Agitators
Fans
Conveyor belts
Centrifuges
Hinged flaps
Bucket-elevators
Air conditioning system
General drives in manufacturing and processing machines

Characteristic curve



Extreme switching duty
Squirrel-cage motor
Operating characteristics
Inching, plugging, reversing
Electrical characteristics
Make: up to 6 x rated motor current
Break: up to 6 x rated motor current
Utilization category
100 % AC-4
Typical applications
Printing presses
Wire-drawing machines
Centrifuges
Special drives for manufacturing and processing machines

Characteristic curve



Switching conditions for non-motor consumers, 3 pole, 4 pole
Operating characteristics
Non inductive and slightly inductive loads
Electrical characteristics
Switch on: 1 x rated operational current
Switch off: 1 x rated operational current
Utilization category
100 % AC-1
Typical examples of application
Electric heat

DIMENSIONS



Contactor with auxiliary contact module



Lateral clearance to earthed parts: 6 mm

DILM40...DILM72
DILMC40...DILMC65
DILMF40...DILMF65



