



107012
DILM170(RAC120)

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per IEC/EN 61439](#)

[Technical data ETIM7.0](#)

[Approvals](#)

[Characteristics](#)

[Dimensions](#)

DELIVERY PROGRAM

Product range
Contactors

Application
Contactors for Motors

Subrange
Contactors up to 170 A, 3 pole

Utilization category
AC-1: Non-inductive or slightly inductive loads, resistance furnaces
NAC-3: Normal AC induction motors: starting, switch off during running
AC-4: Normal AC induction motors: starting, plugging, reversing, inching

Notes
Not suitable for motors with efficiency class IE3.

Connection technique
Screw terminals

Number of poles
3 pole

Rated operational current

AC-3
Notes
At maximum permissible ambient temperature
(open.)

AC-3
380 V 400 V [I_e]
170 A

AC-1
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 40 °C [I_{th} = I_e]
225 A

AC-1
Conventional free air thermal current, 3 pole, 50 -
60 Hz
enclosed [I_{th}]
166 A

AC-1
Conventional free air thermal current, 1 pole
open [I_{th}]
460 A

AC-1
Conventional free air thermal current, 1 pole
enclosed [I_{th}]
415 A

Max. rating for three-phase motors, 50 - 60 Hz

AC-3
220 V 230 V [P]
52 kW

AC-3
380 V 400 V [P]
90 kW

AC-3
660 V 690 V [F]
96 kW

AC-4
220 V 230 V [F]
20 kW

AC-4
380 V 400 V [F]
33 kW

AC-4
660 V 690 V [F]
48 kW

Contact sequence



Instructions

Contacts to EN 50 012.
integrated suppressor circuit in actuating
electronics
Observe electrical lifespan.

Can be combined with auxiliary contact
DILM150-XH(V)...
DILM1000-XH(V)...

Actuating voltage
RAC 120: 100 - 120 V 50/60 Hz

Voltage AC/DC
AC operation

Connection to SmartWire-DT
no

Frame size
4

TECHNICAL DATA

General

Standards
IEC/EN 60947, VDE 0660, UL, CSA

Lifespan, mechanical
AC operated [Operations]
 5.7×10^6

Operating frequency, mechanical
AC operated [Operations/h]
3000


Climatic proofing
Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature
Open
-25 - +60 °C

Ambient temperature
Enclosed
- 25 - 40 °C

Ambient temperature
Storage
- 40 - 80 °C

Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Main contacts
N/O contact
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/O contact
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/C contact
5 g

Mechanical shock resistance (IEC/EN 60068-2-27)
when tabletop-mounted
Half-sinusoidal shock, 10 ms
Main contacts
N/O contact
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)
when tabletop-mounted
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/O contact
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)
when tabletop-mounted
Half-sinusoidal shock, 10 ms
Auxiliary contacts
N/C contact
5 g

Degree of Protection
IP00

Protection against direct contact when actuated
from front (EN 50274)
Finger and back-of-hand proof

Altitude
Max. 2000 m

Weight
AC operated
2.25 kg

Screw connector terminals
Terminal capacity main cable
Flexible with ferrule
1 x (10 - 95)
2 x (10 - 70) mm²

Screw connector terminals
Terminal capacity main cable
Stranded
1 x (16 - 95)

2 x (16 - 70) mm²

Screw connector terminals
Terminal capacity main cable
Solid or stranded
single 8...3/0, double 8...2/0 AWG

Screw connector terminals
Terminal capacity main cable
Flat conductor [Lamellenzahl x Breite x Dicke]
2 x (6 x 16 x 0.8) mm

Screw connector terminals
Terminal capacity main cable
Stripping length
24 mm

Screw connector terminals
Terminal capacity main cable
Terminal screw
M10

Screw connector terminals
Terminal capacity main cable
Tightening torque
14 Nm

Screw connector terminals
Terminal capacity main cable
Tool
Hexagon socket-head spanner [SW]
5 mm

Screw connector terminals
Terminal capacity control circuit cables
Solid
1 x (0.75 - 4)
2 x (0.75 - 2.5) mm²

Screw connector terminals
Terminal capacity control circuit cables
Flexible with ferrule
1 x (0.75 - 2.5)
2 x (0.75 - 2.5) mm²

Screw connector terminals
Terminal capacity control circuit cables
Solid or stranded
18 - 14 AWG

Screw connector terminals
Terminal capacity control circuit cables
Stripping length
10 mm

Screw connector terminals
Terminal capacity control circuit cables
Terminal screw
M3.5

Screw connector terminals
Terminal capacity control circuit cables
Tightening torque
1.2 Nm

Screw connector terminals
Terminal capacity control circuit cables
Tool
Pozidriv screw driver
2 Size

Screw connector terminals
Terminal capacity control circuit cables
Tool
Standard screw driver
0.8 x 5.5
1 x 6 mm

Main conducting paths

Rated impulse withstand voltage [U_{imp}]
8000 V AC

Overvoltage category/pollution degree
III/3

Rated insulation voltage [U_i]
690 V AC

Rated operational voltage [U_e]
690 V AC

Safe isolation to EN 61140
between coil and contacts
690 V AC

Safe isolation to EN 61140

between the contacts
690 V AC

Making capacity (p.f. to IEC/EN 60947) [Up to 690 V]
2100 A

Breaking capacity
220 V 230 V
1500 A

Breaking capacity
380 V 400 V
1500 A

Breaking capacity
500 V
1500 A

Breaking capacity
660 V 690 V
1320 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
400 V [gG/gL 500 V]
250 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "2" coordination
690 V [gG/gL 690 V]
250 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination
400 V [gG/gL 500 V]
250 A

Short-circuit rating
Short-circuit protection maximum fuse
Type "1" coordination
690 V [gG/gL 690 V]
250 A

AC

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 40 °C [$I_{th} = I_e$]
225 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 50 °C [$I_{th} = I_e$]
200 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 55 °C [$I_{th} = I_e$]
190 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
Open
at 60 °C [$I_{th} = I_e$]
185 A

AC-1
Rated operational current
Conventional free air thermal current, 3 pole, 50 -
60 Hz
enclosed [I_{th}]
166 A

AC-1
Rated operational current
Conventional free air thermal current, 1 pole
open [I_{th}]
460 A

AC-1
Rated operational current
Conventional free air thermal current, 1 pole
enclosed [I_{th}]
415 A

AC-3
Rated operational current
Open, 3-pole: 50 – 60 Hz

Notes

At maximum permissible ambient temperature
(open.)

AC-3

Rated operational current
Open, 3-pole: 50 – 60 Hz
220 V 230 V [I_e]
170 A

AC-3

Rated operational current
Open, 3-pole: 50 – 60 Hz
240 V [I_e]
170 A

AC-3

Rated operational current
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
170 A

AC-3

Rated operational current
Open, 3-pole: 50 – 60 Hz
415 V [I_e]
170 A

AC-3

Rated operational current
Open, 3-pole: 50 – 60 Hz
440V [I_e]
170 A

AC-3

Rated operational current
Open, 3-pole: 50 – 60 Hz
500 V [I_e]
170 A

AC-3

Rated operational current
Open, 3-pole: 50 – 60 Hz
660 V 690 V [I_e]
100 A

AC-3

Motor rating [P]
220 V 230 V [P]
52 kW

AC-3

Motor rating [P]
240V [P]
57 kW

AC-3
Motor rating [P]
380 V 400 V [P]
90 kW

AC-3
Motor rating [P]
415 V [P]
100 kW

AC-3
Motor rating [P]
440 V [P]
105 kW

AC-3
Motor rating [P]
500 V [P]
120 kW

AC-3
Motor rating [P]
660 V 690 V [P]
96 kW

AC-4
Open, 3-pole: 50 – 60 Hz
220 V 230 V [I_e]
65 A

AC-4
Open, 3-pole: 50 – 60 Hz
240 V [I_e]
65 A

AC-4
Open, 3-pole: 50 – 60 Hz
380 V 400 V [I_e]
65 A

AC-4
Open, 3-pole: 50 – 60 Hz
415 V [I_e]
65 A

AC-4

Open, 3-pole: 50 – 60 Hz
440 V [I_e]
65 A

AC-4
Open, 3-pole: 50 – 60 Hz
500 V [I_e]
65 A

AC-4
Open, 3-pole: 50 – 60 Hz
660 V 690 V [I_e]
50 A

AC-4
MOTOR rating [F]
220 V 230 V [F]
20 kW

AC-4
MOTOR rating [F]
240 V [F]
22 kW

AC-4
MOTOR rating [F]
380 V 400 V [F]
33 kW

AC-4
MOTOR rating [F]
415 V [F]
39 kW

AC-4
MOTOR rating [F]
440 V [F]
41 kW

AC-4
MOTOR rating [F]
500 V [F]
47 kW

AC-4
MOTOR rating [F]
660 V 690 V [F]
48 kW

Rated operational current, open
DC-1
60 V [I_e]
160 A

Rated operational current, open
DC-1
110 V [I_e]
160 A

Rated operational current, open
DC-1
220 V [I_e]
90 A

Current heat loss

3 pole, at I_{th} (60°)
48.7 W

Current heat loss at I_e to AC-3/400 V
41.1 W

Impedance per pole
0.6 m Ω

Magnet systems

Voltage tolerance
AC operated [Pick-up]
0.8 - 1.15 x U_c

Voltage tolerance
Drop-out voltage AC operated [Drop-out]
0.25 - 0.6 x U_c

Power consumption of the coil in a cold state and
1.0 x U_s
50 Hz [Pick-up]
180 VA

Power consumption of the coil in a cold state and
1.0 x U_s
50 Hz [Sealing]
3.1 VA

Power consumption of the coil in a cold state and
1.0 x U_N
50 Hz [Sealing]
2.3 W

Power consumption of the coil in a cold state and
1.0 x U_N
60 Hz [Pick-up]
170 VA

Power consumption of the coil in a cold state and
1.0 x U_N
60 Hz [Sealing]
3.1 VA

Power consumption of the coil in a cold state and
1.0 x U_N
60 Hz [Sealing]
2.3 W

Duty factor
100 % DF

Changeover time at 100 % U_N (recommended
value)
Main contacts
AC operated
Closing delay
28 - 33 ms

Changeover time at 100 % U_N (recommended
value)
Main contacts
AC operated
Opening delay
35 - 41 ms

Changeover time at 100 % U_N (recommended
value)
Arcing time
15 ms

Changeover time at 100 % U_N (recommended
value)
Permissible residual current with actuation of A1 -
A2 by the electronics (with 0 signal).
 1 mA

Electromagnetic compatibility (EMC)

Emitted interference
to EN 60947-1

Interference immunity
to EN 60947-1

Rating data for approved types

Switching capacity
Maximum motor rating
Three-phase
200 V
208 V
50 HP

Switching capacity
Maximum motor rating
Three-phase
230 V
240 V
60 HP

Switching capacity
Maximum motor rating
Three-phase
460 V
480 V
125 HP

Switching capacity
Maximum motor rating
Three-phase
575 V
600 V
125 HP

Switching capacity
Maximum motor rating
Single-phase
115 V
120 V
10 HP

Switching capacity
Maximum motor rating
Single-phase
230 V
240 V
30 HP

Switching capacity

General use
225 A

Short Circuit Current Rating
Basic Rating
SCCR
10 kA

Short Circuit Current Rating
Basic Rating
max. Fuse
600 A

Short Circuit Current Rating
Basic Rating
max. CB
600 A

Short Circuit Current Rating
480 V High Fault
SCCR (fuse)
30/100 kA

Short Circuit Current Rating
480 V High Fault
max. Fuse
300/300 Class J A

Short Circuit Current Rating
480 V High Fault
SCCR (CB)
65 kA

Short Circuit Current Rating
480 V High Fault
max. CB
250 A

Short Circuit Current Rating
600 V High Fault
SCCR (fuse)
30/100 kA

Short Circuit Current Rating
600 V High Fault
max. Fuse
300/600 Class J A

Short Circuit Current Rating
600 V High Fault

SCCR (CB)
30 kA

Short Circuit Current Rating
600 V High Fault
max. CB
350 A

Special Purpose Ratings
Electrical Discharge Lamps (Ballast)
480V 60Hz 3phase, 277V 60Hz 1phase
160 A

Special Purpose Ratings
Electrical Discharge Lamps (Ballast)
600V 60Hz 3phase, 347V 60Hz 1phase
160 A

Special Purpose Ratings
Incandescent Lamps (Tungsten)
480V 60Hz 3phase, 277V 60Hz 1phase
160 A

Special Purpose Ratings
Incandescent Lamps (Tungsten)
600V 60Hz 3phase, 347V 60Hz 1phase
160 A

Special Purpose Ratings
Resistance Air Heating
480V 60Hz 3phase, 277V 60Hz 1phase
160 A

Special Purpose Ratings
Resistance Air Heating
600V 60Hz 3phase, 347V 60Hz 1phase
160 A

Special Purpose Ratings
Refrigeration Control (CSA only)
LRA 480V 60Hz 3phase
540 A

Special Purpose Ratings
Refrigeration Control (CSA only)
FLA 480V 60Hz 3phase
90 A

Special Purpose Ratings
Refrigeration Control (CSA only)

LRA 600V 60Hz 3phase
540 A

Special Purpose Ratings
Refrigeration Control (CSA only)
FLA 600V 60Hz 3phase
90 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to
UL 1995)
LRA 480V 60Hz 3phase
1020 A

Special Purpose Ratings
Definite Purpose Ratings (100,000 cycles acc. to
UL 1995)
FLA 480V 60Hz 3phase
170 A

Special Purpose Ratings
Elevator Control
200V 60Hz 3phase
30 HP

Special Purpose Ratings
Elevator Control
200V 60Hz 3phase
92 A

Special Purpose Ratings
Elevator Control
240V 60Hz 3phase
40 HP

Special Purpose Ratings
Elevator Control
240V 60Hz 3phase
104 A

Special Purpose Ratings
Elevator Control
480V 60Hz 3phase
75 HP

Special Purpose Ratings
Elevator Control
480V 60Hz 3phase
96 A

Special Purpose Ratings
Elevator Control
600V 60Hz 3phase
100 HP

Special Purpose Ratings
Elevator Control
600V 60Hz 3phase
99 A

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]
170 A

Heat dissipation per pole, current-dependent [P_{vid}]
13.7 W

Equipment heat dissipation, current-dependent
[P_{vid}]
41.1 W

Static heat dissipation, non-current-dependent [P_{vs}]
2.3 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+60 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Rated control supply voltage U_s at AC 50HZ
100 - 120 V

Rated control supply voltage U_s at AC 60HZ
100 - 120 V

Rated control supply voltage U_s at DC
0 - 0 V

Voltage type for actuating
AC

Rated operation current I_e at AC-1, 400 V
225 A

Rated operation current I_e at AC-3, 400 V
170 A

Rated operation power at AC-3, 400 V
90 kW

Rated operation current I_e at AC-4, 400 V
65 A

Rated operation power at AC-4, 400 V
33 kW

Rated operation power NEVA
93 kW

Modular version
No

Number of auxiliary contacts as normally open
contact
0

Number of auxiliary contacts as normally closed
contact
0

Type of electrical connection of main circuit
Screw connection

Number of normally closed contacts as main contact
0

Number of main contacts as normally open contact
3

APPROVALS

Product Standards
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No. 60947-4-1-14; CE marking

UL File No.
E29096

UL Category Control No.
NLDX


CSA File No.
012528

CSA Class No.
2411-03, 3211-04

North America Certification
UL listed, CSA certified

Specially designed for North America
No

CHARACTERISTICS




Accessories

1: Overload relay

2: Suppressor

3: Auxiliary contact modules


Side mounting auxiliary contacts



possible variants at auxiliary contact module fitting options

on the side: 2 x DILMB20-XH11(V)-SI; 2 x DILMB20-XH11-SA

Characteristic curve



Squirrel-cage motor

Operating characteristics

Starting: from rest

Stopping: after attaining full running speed

Electrical characteristics

Make: up to 6 x rated motor current

Break: up to 1 x rated motor current

Utilization category

100 % AC-3

Typical applications

Compressors

Lifts

Mixers

Pumps

Escalators

Agitators

Fans

Conveyor belts

Centrifuges


Hinged flaps

Bucket-elevators

Air conditioning system

General drives in manufacturing and processing machines

Characteristic curve



Extreme switching duty

Squirrel-cage motor
 Operating characteristics
 Inching, plugging, reversing
 Electrical characteristics
 Make: up to 6 x rated motor current
 Break: up to 6 x rated motor current
 Utilization category
 100 % AC-4
 Typical applications
 Printing presses
 Wire-drawing machines
 Centrifuges
 Special drives for manufacturing and processing machines

Characteristic curve



Switching conditions for non-motor consumers, 3 pole, 4 pole
 Operating characteristics
 Non inductive and slightly inductive loads
 Electrical characteristics
 Switch on: 1 x rated operational current
 Switch off: 1 x rated operational current
 Utilization category
 100 % AC-1
 Typical examples of application
 Electric heat

DIMENSIONS



Contactor with auxiliary contact module



distance at side to earthed parts: 10 mm

DILM80...DILM170
 DILMC80...DILMC150
 DILMF80...DILMF150

