

DIL CONTACTORS

278236



Overview



Specifications



Resources

How to




Photo is representative




Photo is representative

278236

Eaton Moeller® series DIUL Reversing contactor c
kW, 230 V 50 Hz, 240 V 60 Hz, AC operation



[WIN-WIN with Push-in Terminals](#)

[How to improve wiring](#)

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

278458

Eaton Moeller® series ZB Overload relay, ZB65, Ir= 24 - 40 A, 1 N/O, 1 N/C, Direct mounting, IP00

278459

Eaton Moeller® series ZB Overload relay, ZB65, Ir= 40 - 57 A, 1 N/O, 1 N/C, Direct mounting, IP00

278460

Eaton Moeller® series ZB Overload relay, ZB65, Ir= 50 - 65 A, 1 N/O, 1 N/C, Direct mounting, IP00

281206

Eaton Moeller® series DILM R circuit, 110 - 240 AC V, For use DILM40 - DILM95, DILK33 - DILK35, DILMP63 - DILMP200

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications >

PRODUCT NAME Eaton Moeller® series DIUL contactor combination

CATALOG NUMBER 278236

Product specifications >

MODEL CODE DIULM50/11(230V50HZ,240V60HZ)

EAN 4015082782368

PRODUCT LENGTH/DEPTH 147 mm

PRODUCT HEIGHT 115 mm

PRODUCT WIDTH 110 mm

PRODUCT WEIGHT 1.936 kg

WARRANTY Not Applicable

COMPLIANCES CE Marked
RoHS Compliant

CERTIFICATIONS

CSA Certified
UL Listed
IEC 60947-4-1
EN 60947-4-1
UL File No.: E29096
CSA Class No.: 2411-03, 3211-04
CSA-C22.2 No. 60947-4-1-14
CSA
CSA File No.: 012528
UL Category Control No.: NLDX
IEC/EN 60947-4-1
CE
UL 60947-4-1
UL

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	50 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications must be observed.
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	22 kW
OPERATING VOLTAGE AT AC, 50 HZ - MAX	690 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	230 V
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications must be observed.
NUMBER OF CONTACTS (NORMALLY CLOSED) AS MAIN CONTACT	0
AMPERAGE RATING	50A
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
RATED OPERATIONAL POWER (NEMA)	29.8 kW
OPERATING VOLTAGE AT DC - MAX	0 V
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	230 V
FREQUENCY RATING	50-60 Hz
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
NUMBER OF MAIN CONTACTS (NORMALLY OPEN CONTACT)	6
OPERATING TEMPERATURE	-25° to 60°C
TERMINALS	Screw terminals
OPERATING VOLTAGE AT DC - MIN	0 V
HP RATING - MAX	3, 10/15, 20, 40, 50 hp (1/3PH @120, 240/208, 240/208)
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
FEATURES	Mechanical interlock
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	4.1 W
ELECTRICAL CONNECTION TYPE FOR AUXILIARY-	Screw connection

AND CONTROL-CURRENT CIRCUIT	
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	0 V
NUMBER OF POLES	Three-pole
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
UTILIZATION CATEGORY	AC-4: Normal AC induction motors: starting, plugging AC-3: Normal AC induction motors: starting, switching
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
COIL VOLTAGE	230-240 Vac, 50/60 Hz
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be replaced.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be replaced.
OPERATING VOLTAGE AT AC, 50 HZ - MIN	230 V
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be replaced.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be replaced.
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	4.9 W
APPLICATION	Contactors combinations for starting motors with two rotation
ACTUATING VOLTAGE	230 V 50 Hz, 240 V 60 Hz
VOLTAGE TYPE	AC
PRODUCT CATEGORY	Contactors combinations
OPERATING TEMPERATURE - MIN	-25 °C
RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	30 kW
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	14.6 W
HEAT DISSIPATION CAPACITY PDISS	0 W
SUITABLE FOR	Also motors with efficiency class IE3
OPERATION	Reversing contactor
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0

CONTINUOUS AMPERE RATING	50 A
POWER CONSUMPTION	22 kW
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
OPERATING TEMPERATURE - MAX	60 °C
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
VOLTAGE RATING	400 V
OPERATING VOLTAGE AT AC, 60 HZ - MAX	690 V
NUMBER OF CONTACTS	1 NO 1 NC
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	IP00 NEMA Other
RATED OPERATIONAL POWER AT AC-4, 220/230 V, 50 HZ	6 kW
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
VOLTAGE TYPE OF OPERATING VOLTAGE	AC
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	240 V
RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V	50 A
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
CONNECTION	Screw terminals
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the device.
FUNCTIONS	Reversing safety
OPERATING VOLTAGE AT AC, 60 HZ - MIN	230 V
RATED OPERATIONAL POWER AT AC-4, 660/690 V, 50 HZ	14 kW
FRAME SIZE	55 mm
SERIES	XT IEC
DUTY FACTOR	100 %
TYPE	Full voltage reversing contactor
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV)	Meets the product standard's requirements.

RADIATION

10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V	50 A
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	2

Catalogs

Certification reports

Declarations of conformity

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

System overview

Wiring diagrams

278236



quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.